


PRODUCT SPECIFICATION.

ISSUED BY. 	PRODUCT SPECIFICATION SHEET No <i>PS0007</i>	
	DATE :-21-11-91.	SIGNATURE <i>LEM</i>
	ISSUE No.1	SHEET 1 of 1

No 439-0140 **BLACK.**

235-740

GAC-2



Construction

1 = Jacket:	PVC, \varnothing 5,4mm +/- 0,3mm (colors as specified below).
2 = Shield No. 1:	Bare copper wire (0,10mm)
3 = Shield No. 2:	Bare copper wire (0,10mm)
4 = PVC separation:	\varnothing 3,1mm +/- 0,15mm, white, tube
5 = Insulation (cond.):	PVC white and brown, \varnothing 1,2mm +/- 0,05mm, wrapped, twisted pair
6 = Conductor:	Bare copper wires 48 x 0,07mm (0,18mm ²)

Technical specification

Conductor resistance:	\leq 110 Ohm/km
Shielding resistance:	\leq 20 Ohm/km
Capacitance:	cond-to-cond: \leq 160nF/km
	cond-to-shield: \leq 220nF/km
	cond-to-cond: 500Veff
Test voltage:	cond-to-shield: 2000Veff

Ordering data

Colors:	black, red, yellow, gray, blue, mint, pink
Reels at:	100m
Weight/reel:	4,4kg
Weight/meter:	0,037kg

Operational areas

- microphone cable
- patch cables
- XRL extension cable
- line cables
- Intercom cables
- MUSICAL INSTRUMENT DIGITAL INTERFACE.

No 439-0540 Red
 439-0940 Grey
 439-0240 Blue
 439-0440 Mint
 439-0740 Yellow