



XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB321611-101-3A				Rev: A/2		
DIMENSION : (m/m) <div style="text-align: center; margin: 10px 0;">  </div> <div style="text-align: center; margin: 10px 0;">  </div>				A	3.2±0.2	m/m
				B	1.6±0.2	m/m
				C	1.1±0.2	m/m
				D	0.5±0.3	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
				K		m/m
				L		m/m
				M		m/m
				N		m/m
				O		m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS		
Z	100±25% Ohms	TEST FREQ.	100	MHz	<ul style="list-style-type: none"> ● HP 34401A MULTIMETER ○ HP 4195 NETWORKS/SPECTRUM ANALYZER ○ HP 42841 BIAS CURRENT SOURCE ○ HP 4285A LCR METER ○ HP 4286A RF LCR METER ● HP 4291A RF IMPEDANCE / MATERIAL ANALYZER ○ HP 4338A MILLION OHM METER ○ HP 6632A DC POWER SUPPLY ○ HP4284A PRECISION LCR METER 	
Rdc	0.035 Ohms Max	TEST FREQ.		MHz		
Idc	3000mA MAX.	TEST FREQ.		MHz		
Notes: <ol style="list-style-type: none"> 1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability. 2. Flammability: UL94V-0 3. ASTM oxygen index: > 28% 4. Insulation System: Class F 155°C. UL file E151556 5. Operating Temperature Range: All listed parameters are to be within tolerance from -55°C to +125°C 6. Storage Temperature Range: -55°C to +125°C 7. Aqueous wash compatible 						
DRAWN BY :		CHECKED BY :		APPROVED BY :		
Li Xiaofeng		Liao		BW		