



NOTES:

- 1.DISPLAY TYPE: STN/YELLOW GREEN MODE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: $0^{\circ}\text{C}-50^{\circ}\text{C}$
- 5.STORAGE TEMP: $-20^{\circ}\text{C}-60^{\circ}\text{C}$
- 6.LCD OPERATING VOLTAGE: 4.2V
- 7.DRIVE METHOD: 1/16 DUTY 1/5 BIAS
- 8.BACKLIGHT: LED
- 9.CONTROLLER: KS0066UP-00CC
- 10.UNMARKED TOLERANCE: $\pm 0.3\text{mm}$
- 11.BEZEL IS TO BE PAINTED BLACK
- 12.THERE IS AN ADHESIVE DOUBLE TAPE BETWEEN PCB AND CABLE

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Vss	Vdd	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A	K



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM162XBC7	
CHECKED BY:	DWG NO: 16/7-2002	
APPROVED BY:	DWG NAME:	SCALE: UNIT: mm
CONFIRMED BY:	SHEET NO: OF	