
WP12 Page 1 of 1

# WP12

# 12 Watt Single Output Regulated Power Supplies





#### Features:

N.A. AC input Fully enclosed plastic case Fully regulated output High Efficiency Warranty: 5 years

#### Environmental

Operating temperature...... C to 40 °C Storage temperature.....-55 °C to 85 °C Weight; 0.5 lbs

#### EMI

Meets FCC class B

### Safety

UL 1950

cUL Listed to CSA 22.2 No. 950

Polarity: COM +V

## Electrical specifications

Input

Voltage.......90-132VAC

Current......0.75A

Frequency.......47-63 Hz

Input connector.......2 Pin NEMA 5/15 plug

## Output

Hold up time......12 ms min. at full load 115 V

Over voltage protection.....Built-in Over current protection.....Built-in

Short circuit protection......Pulsing Mode, auto recovery

Ripple/noise(Vp-p).....1%

Output connector......barrel type(5.5 x 2.5 x 9.5mm)

## Output Electrical Specifications

| Model No.  | Voltage | Power | Current |
|------------|---------|-------|---------|
| WP1205-760 | 5       | 12    | 2.4A    |
| WP1212-760 | 12      | 12    | 1A      |
| WP1215-760 | 15      | 12    | 0.8A    |
| WP1218-760 | 18      | 12    | 0.67A   |
| WP1224-760 | 24      | 12    | 0.5A    |

Quality Power Supplies | Agency Certifications | Output Connectors | Custom Requests | About Us | Qu Management Team | Job Opportunites | Elpac News | Sales Representatives | Distributors | Catalog Reque Power Supplies | External Power Supplies | Open Frame Power Supplies | Medical Power Supplies | Custor

Copyright © 2003, Elpac Power Supp