

SUPER COMPACT BODY PORTED
METAL INLINE/ELBOW TYPES

AS1000-M3
AS1200-M3
AS1400-M3

- ✓ Super-compact size and light weight
- ✓ Proportional speed control: To 20ℓ/min(ANR)
- ✓ Three types available:
 - In-line type (AS1000)
 - Direct connection elbow type (AS1200)
 - Direct connection flat elbow type (AS1400)




TECHNICAL
SPECIFICATIONS

Proof Pressure	1.05MPa{10.7kgf/cm ² }
Max operating pressure	0.7MPa{7.1kgf/cm ² }
Min Operating Pressure	0.1MPa{1kgf/cm ² }
Ambient and fluid temperature	5~60°C
Number of needle rotations	10 turns


Model		Port Size	Free Flow Air Flow (ℓ/min) (ANR)	Controlled Flow Effective Orifice (mm ²)	Applicable Cylinder Bore Size (mm)	Weight (g) (g)
In-line type	AS1000-M3	M3	20	0.3	Ø2.5, Ø4, Ø6	4.7
Elbow type	AS1200-M3	M3	20	0.3	Ø2.5, Ø4, Ø6	3
Flat elbow type	AS1400-M3	M3	20	0.3	Ø2.5, Ø4, Ø6	6

SYMBOLS



DIMENSIONS

IN-LINE TYPE AS1000-M3



HOW TO
ORDER

AS1 00 — M3

TYPE


0In-line type
2Direct connection elbow direction
4Direct connection flat elbow type

PORT SIZE

M3 ...M3x0.5


DIMENSIONS

ELBOW TYPE AS1200-M3



DIMENSIONS

FLAT ELBOW TYPE AS1400-M3



FOR FURTHER TECHNICAL
DETAILS ON THIS
PRODUCT REQUEST
CATALOGUE REFERENCE
E201-G

SPEED CONTROLLERS WITH LOW SPEED APPLICATION

SERIES AS12/13 ■ 1FM RESIN BODY WITH ONE TOUCH FITTINGS

SERIES AS12/22 ■ 0M METAL BODY PORTED

- ✓ Suitable for low speed applications; 10-50mm/sec
- ✓ Accurate control of low speed cylinders with effective orifice for control flow at 1/10 of standard types
- ✓ Possible to operate cylinders at low speed for working strokes and high speed for return strokes
- ✓ Easy control with 10 turns (20 turns for M5 type) of needle rotation

TECHNICAL SPECIFICATIONS

WITH ONE TOUCH FITTING

Proof Pressure	1.5MPa {15.3kgf/cm ² }
Max operating Pressure	1MPa {10.2kgf/cm ² }
Min Operating Pressure	0.1MPa {1kgf/cm ² }
Ambient and fluid temperature	0-60°C
Number of needle rotations	10 turns (20 turns - 1 (Note))
Applicable Tube Material ^{Note 2}	Nylon, Soft Nylon, Polyurethane
Option ^{Note 3}	With Sealant Std

Elbow type	AS12*1FM	AS22*1FM-01	AS22*1FM-02
Universal type	AS13*1FM	AS23*1FM-01	AS23*1FM-02
Port Size	M5x0.8	R(PT)1/8	R(PT)1/4
Applicable Cylinder bore (mm)	6, 10, 16, 20	20, 25, 32	20, 25, 32, 40
Applicable Tube OD (mm)	Ø3.2, Ø4, Ø6	Ø3.2, Ø4, Ø6, Ø8	Ø4, Ø6, Ø8, Ø10
Control flow rate ℓ/min (ANR) Nℓ/min	8	22	55
Effective Orifice mm ²	0.13	0.35	0.85
Free flow rate ℓ/min (ANR) Nℓ/min	100	180 230	260 390 460
Effective Orifice mm ²	15	2.7 3.5	4 6 7

At 0.5MPa (5.1kgf/cm²), temperature - 20°C


Note 1: For AS12*1FM type and AS13*1FM type

Note 2: Be careful of maximum operating pressure when soft nylon or polyurethane tubes are used.

Note 3: Not available for M5 models

HOW TO ORDER

WITH ONE TOUCH FITTING



Series AS12/22 □ 0M

Metal body ported

Series AS12/13 □ 1FM
AS22/23 □ 1FM

Resin body with one touch fittings

TECHNICAL SPECIFICATIONS

METAL BODY PORTED

Proof Pressure	1.5MPa {15.3kgf/cm ² }		
Max operating Pressure	1MPa {10.2kgf/cm ² }		
Min Operating Pressure	0.1MPa {1kgf/cm ² }		
Ambient and fluid temperature	5~60°		
Model	AS12*0M-M5	AS22*0M-01	AS22*0M-02
Port Size (Cylinder Side)	M5x0.8	R(PT)1/8	R(PT)1/4
(Tube Side)		Rc(PT)1/8	Rc(PT)1/4
Applicable Cylinder Tube ID(mm)	6, 10, 15, 20, 25	20, 25, 32, 40	20, 25, 32, 40
Number of needle rotations	20 turns	10 turns	
Option	—	With Sealant (std)	
Weight (g)	11.5	36	74
Control flow rate ℓ/min (ANR)	8	22	55
Nℓ / min			
Effective Orifice mm ²	0.13	0.35	0.85
Free flow rate ℓ/min (ANR)	105	280	420
Nℓ / min			
Effective Orifice mm ²	1.6	4.3	6.5

At 0.5MPa (5.1kgf/cm²), temperature - 20°C


Note 4: Difference of appearance between meter-out models and meter-in models
Meter-out - with an electroless nickel plated lock nut

The handle and lock nut of meter-in type are black zinc chromated

Note 5: All brass parts are electroless nickel plated.

HOW TO ORDER

METAL BODY PORTED



DIMENSIONS
SEE STANDARD
MODELS



SEE INSIDE FRONT COVER FOR
DETAILS OF YOUR LOCAL SALES OFFICE



FOR FURTHER TECHNICAL
DETAILS ON THIS
PRODUCT REQUEST
CATALOGUE REFERENCE
E201-G