


1. SCOPE

1.1 Scope. This drawing forms a part of a one part - one part number documentation system (see 6.6 herein). Two product assurance classes consisting of military high reliability (device classes B, Q, and M) and space application (device classes S and V) and a choice of case outlines and lead finishes are available and are reflected in the Part Identifying Number (PIN). Device class M microcircuits represent non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices". When available, a choice of radiation hardness assurance (RHA) levels are reflected in the PIN.

1.2 PIN. PIN shall be as shown in the following example:



1.2.1 Radiation hardness assurance (RHA) designator. Device classes M, B, and S RHA marked devices shall meet the MIL-M-38510 specified RHA levels and shall be marked with the appropriate RHA designator. Device classes Q and V devices shall meet or exceed the electrical performance characteristics specified in table I herein after exposure to the specified irradiation levels specified in the absolute maximum ratings herein and the RHA marked device shall be marked in accordance with MIL-I-38535. A dash (-) indicates a non RHA device.

1.2.2 Device type. The device type shall identify the circuit function as follows:

| Device type | Generic number | Circuit function |
|-------------|----------------|-----------------------|
| 01 | AH5012 | Analog current switch |

1.2.3 Device class designator. This device class designator shall be a single letter identifying the product assurance level as follows:

| Device class | Device requirements documentation |
|--------------|---|
| M | Vendor self-certification to the requirements for non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883 |
| B or S | Certification and qualification to MIL-M-38510 |
| Q or V | Certification and qualification to MIL-I-38535 |

1.2.4 Case outline. Device classes M, B, and S case outline shall meet the requirements in appendix C of MIL-M-38510 and as listed below. Device classes Q and V case outline shall meet the requirements of MIL-I-38535, appendix C of MIL-M-38510, and as listed below.

| Outline letter | Case outline |
|----------------|--|
| E | D-2 (16-lead, .840" x .310" x .200"), dual-in-line package |

1.2.5 Lead finish. The lead finish shall be as specified in MIL-M-38510 for classes M, B, and S or MIL-I-38535 for classes Q and V. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

| | | | |
|---|------------------|------------|---------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | 5962-90880 | |
| | REVISION LEVEL | | SHEET 2 |

1.3 Absolute maximum ratings. 1/

| | | |
|---|-----------|-----------------------------|
| Input voltage | - - - - - | +30 V dc |
| Diode current | - - - - - | 10 mA |
| Positive analog signal voltage | - - - - - | +30 V dc |
| Negative analog signal voltage | - - - - - | -15 V dc |
| Drain current | - - - - - | 30 mA |
| Power dissipation (P_D) | - - - - - | 500 mW |
| Storage temperature range | - - - - - | -65°C to +150°C |
| Lead temperature (soldering, 10 seconds) | - - - - - | 300°C |
| Junction temperature (T_J) | - - - - - | 150°C |
| Thermal resistance, junction-to-case (θ_{JC}) | - - - - - | See MIL-M-38510, appendix C |
| Thermal resistance, junction-to-ambient (θ_{JA}) | - - - - - | 115°C/W |

1.4 Recommended operating conditions.

| | | |
|---|-----------|-----------------|
| Ambient operating temperature range (T_A) | - - - - - | -55°C to +125°C |
|---|-----------|-----------------|

2. APPLICABLE DOCUMENTS

2.1 Government specifications, standards, bulletin, and handbook. Unless otherwise specified, the following specifications, standards, bulletin, and handbook of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATIONS

MILITARY

| | | |
|-------------|---|---|
| MIL-M-38510 | - | Microcircuits, General Specification for. |
| MIL-I-38535 | - | Integrated Circuits, Manufacturing, General Specification for |

STANDARDS

MILITARY

| | | |
|-------------|---|--|
| MIL-STD-480 | - | Configuration Control-Engineering Changes, Deviations and Waivers. |
| MIL-STD-883 | - | Test Methods and Procedures for Microelectronics. |

BULLETIN

MILITARY

| | | |
|-------------|---|---|
| MIL-BUL-103 | - | List of Standardized Military Drawings (SMD's). |
|-------------|---|---|

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 3 |

DESC FORM 193A
SEP 87

U S GOVERNMENT PRINTING OFFICE 1988-850-547

HANDBOOK

MILITARY

MIL-HDBK-780 - Standardized Military Drawings.

(Copies of the specifications, standards, bulletin, and handbook required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device class M shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein. The individual item requirements for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. For device classes B and S a full electrical characterization table for each device type shall be included in this SMD when a qualified source exists. The individual item requirements for device classes Q and V shall be in accordance with MIL-I-38535 and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V and herein.

3.2.1 Case outline. The case outline shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the part number listed in 1.2 herein. Marking for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein). In addition, the manufacturer's part number may also be marked as listed in MIL-BUL-103. Marking for device classes B and S shall be in accordance with MIL-M-38510. Marking for device classes Q and V shall be in accordance with MIL-I-38535.

3.5.1 Quality mark. The quality mark for device class M shall be a "C" as required in MIL-STD-883 (see 3.1 herein). The quality mark for device classes B and S shall be a "J" or "JAN" as required in MIL-M-38510. The quality mark for device classes Q and V shall be a "QML" as required in MIL-I-38535.

3.6 Certificate of compliance. For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.7 herein). For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.7 herein). The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device class M the requirements of MIL-STD-883 (see 3.1 herein), or for device classes Q and V the requirements of MIL-I-38535 and the requirements herein.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 4 |

TABLE 1. Electrical performance characteristics.

| Test | Symbol | Condition 1/ $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ unless otherwise specified | Group A subgroups | Limits | | Unit |
|--|---------------------|--|----------------------|--------|------|---------------|
| | | | | Min | Max | |
| Continuity, G-D, G-S | CONT | $I_S = 0.5 \text{ mA}$ | 1,2,3 | -2.0 | -.10 | V |
| Forward diode voltage drop | V_{DIODE} | $I_D = 0.5 \text{ mA}$ | 1 | | 0.8 | V |
| | | | 2 | | 0.6 | |
| | | | 3 | 1.0 | | |
| Gate breakdown voltage | GATBDWN | $I_S = 100 \mu\text{A}$ | 1,2,3 | 30 | | V |
| Drain-source "ON" resistance (each switch) | $R_{\text{DS(ON)}}$ | $V_{\text{GS}} = .35 \text{ V}, I_S = 2 \text{ mA}$ | 1 | | 150 | Ω |
| | | | 2,3 | | 280 | |
| Resistance match | $R_{\text{D(ON)}}$ | $V_{\text{GS}} = 0 \text{ V}, I_D = 1 \text{ mA}$ | 1 | | 20 | Ω |
| | | | 2,3 | | 100 | |
| Input current "OFF" (each switch) | I_{GSX} | $V_{\text{GD}} = 11 \text{ V}, V_{\text{SD}} = .7 \text{ V}$ | 1 | | .2 | nA |
| | | | 2,3 | | 20 | |
| Drain "OFF" leakage current (each switch) | $I_{\text{D(OFF)}}$ | $V_{\text{GS}} = 3.8 \text{ V}, V_{\text{SD}} = .7 \text{ V}$ | 1 | | .2 | nA |
| | | | 2,3 | | 20 | |
| Leakage current "ON" (each switch) | I_{GON} | $V_{\text{GD}} = 0 \text{ V}, I_S = 1 \text{ mA}$ | 1 | | 1.0 | nA |
| | | | 2,3 | | 350 | |
| | | $V_{\text{GD}} = 0 \text{ V}, I_S = 2 \text{ mA}$ | 1 | | .005 | μA |
| | | | 2,3 | | 20 | |

See footnote at end of table.

**STANDARDIZED
MILITARY DRAWING**

 DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

 SIZE
A

5962-90880

REVISION LEVEL

SHEET 5

 DESC FORM 193A
SEP 87

* U S GOVERNMENT PRINTING OFFICE 1988-550-547

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ unless otherwise specified | Group A subgroups | Limits | | Unit |
|--|--------------|--|----------------------|--------|------|---------------|
| | | | | Min | Max | |
| Leakage current "ON" (each switch) | $I_{G_{ON}}$ | $V_{GD} = 0 \text{ V}, I_S = -2 \text{ mA}$ | 1 | | .010 | μA |
| | | | 2,3 | | 35 | |
| Turn "OFF" time | t_{OFF} | Input step = 5 V | 9,10,11 | | 500 | ns |
| Turn "ON" time | t_{ON} | Input step = 5 V | 9,10,11 | | 500 | ns |

1/ "OFF" and "ON" notations refer to the conduction state of the FET switch.

3.7 Certificate of conformance. A certificate of conformance as required for device class M in MIL-STD-883 (see 3.1 herein) or device classes B and S in MIL-M-38510 or for device classes Q and V in MIL-I-38535 shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DESC-ECS of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-STD-480.

3.9 Verification and review for device class M. For device class M, DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device classes M, B, and S. Device classes M, B, and S devices covered by this drawing shall be in microcircuit group number 070 (see MIL-M-38510, appendix E).

3.11 Serialization for device class S. All device class S devices shall be serialized in accordance with MIL-M-38510.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device class M sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein). For device classes B and S sampling and inspection procedures shall be in accordance with MIL-M-38510 and method 5005 of MIL-STD-883, except as modified herein. For device classes Q and V sampling and inspection procedures shall be in accordance with MIL-I-38535.

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-90880

REVISION LEVEL

SHEET 6

DESC FORM 193A
SEP 87

U S GOVERNMENT PRINTING OFFICE: 1986-850-547

| | |
|-----------------|-----------------|
| Device type | 01 |
| Case outline | E |
| Terminal number | Terminal symbol |
| 1 | Drain 1 |
| 2 | Gate 1 |
| 3 | Source 1 |
| 4 | Common 1 |
| 5 | Common 2 |
| 6 | Source 2 |
| 7 | Gate 2 |
| 8 | Drain 2 |
| 9 | Drain 3 |
| 10 | Gate 3 |
| 11 | Source 3 |
| 12 | Common 3 |
| 13 | Common 4 |
| 14 | Source 4 |
| 15 | Gate 4 |
| 16 | Drain 4 |

FIGURE 1. Terminal connections.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 7 |

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1985-850-547

4.2 Screening. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. For device classes B and S screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to qualification and quality conformance inspection. For device classes Q and V, screening shall be in accordance with MIL-I-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. The following additional criteria shall apply.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A,B,C, or D. For device class M, the test circuit shall be submitted to DESC-ECS for review with the certificate of compliance. For device classes B and S the test circuit shall be submitted to the qualifying activity. For device classes Q and V the test circuit shall be submitted to DESC-ECS with the certificate of compliance and under the control of the device manufacturer's technical review board (TRB) in accordance with MIL-I-38535.

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein.

4.2.1 Additional screening for device class V. Additional screening for device class V beyond the requirements of device class Q shall be as specified in appendix B of MIL-I-38535 and as detailed in table III herein. These additional screens may be used to satisfy space system requirements and shall be reflected in the complete PIN.

4.3 Qualification inspection.

4.3.1 Qualification inspection for device classes B and S. Qualification inspection for device classes B and S shall be in accordance with MIL-M-38510. Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.3.2 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-I-38535. Inspections to be performed shall be those specified in MIL-I-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.4 Conformance inspection. Quality conformance inspection for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein) and as specified herein. Quality conformance inspection for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. Inspections to be performed for device classes M, B, and S shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5). Technology conformance inspection for classes Q and V shall be in accordance with MIL-I-38535 including groups A, B, C, D, and E inspections and as specified herein.

4.4.1 Group A inspection. Group A inspection tests shall be as specified in table II herein.

4.4.2 Group B inspection. The group B inspection end-point electrical parameters shall be as specified in table II herein.

4.4.3 Groups C inspection.

a. End-point electrical parameters shall be as specified in table II herein.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 8 |

DESC FORM 193A
SEP 87

* U S GOVERNMENT PRINTING OFFICE: 1986-850-547

TABLE IIA. Electrical test requirements.

| Test requirements | Subgroups (per method 5005, table I) | | | Subgroups (per MIL-I-38535, table III) | |
|--|---|----------------------|----------------------|--|----------------------|
| | Device class M | Device class B | Device class S | Device class Q | Device class V |
| Interim electrical parameters (see 4.2) | --- | --- | --- | --- | --- |
| Final electrical parameters (see 4.2) | 1,2,3, 1/ 9,10,11 | 1,2,3, 1/ 9,10,11 | 1,2,3, 1/ 9,10,11 | 1,2,3, 1/ 9,10,11 | 1,2,3, 1/ 9,10,11 |
| Group A test requirements (see 4.4) | 1,2,3, 9,10,11 | 1,2,3, 9,10,11 | 1,2,3, 9,10,11 | 1,2,3, 9,10,11 | 1,2,3, 9,10,11 |
| Group B end-point electrical parameters (see 4.4) | --- | --- | 1,2,3, 2/ 9,10,11 | --- | 1,2,3, 9,10,11 |
| Group C end-point electrical parameters (see 4.4) | 1,2,3 | 1,2,3 2/ | --- | 1,2,3 | --- |
| Group D end-point electrical parameters (see 4.4) | 1,2,3 | 1,2,3 | 1,2,3 | 1,2,3 | 1,2,3 |
| Group E end-point electrical parameters (see 4.4) | 1,9 | 1,9 | 1,9 | 1,9 | 1,9 |

1/ PDA applies to subgroup 1.

2/ Delta limits in accordance with table IIC shall be computed with reference to the previous interim electrical parameters.

b. Steady-state life test conditions, method 1005 of MIL-STD-883:

(1) Test condition A, B, C, or D. For device class M the test circuit shall be submitted to DESC-ECS for review with the certificate of compliance. For device classes B and S the test circuit shall be submitted to the qualifying activity. For device classes Q and V the test circuit shall be submitted to DESC-ECS with the certificate of compliance and under the control of the device manufacturer's TRB in accordance with MIL-I-38535.

(2) $T_A = +125^{\circ}\text{C}$, minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.4 Group D inspection. For group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.5 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein). RHA levels for device classes B and S shall be M, D, R, and H and for device class M shall be M and D. RHA quality conformance inspection sample tests shall be performed at the level specified in the purchase order. RHA tests for device classes Q and V shall be performed in accordance with MIL-I-38535 and 1.2.1 herein.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 9 |

DESC FORM 193A
SEP 87

* U S GOVERNMENT PRINTING OFFICE 1988-850-547

Table IIB. Additional screening for device class V.

| Test | MIL-STD-883, test method | Lot requirement |
|---------------------------------|---|-----------------|
| Particle impact noise detection | 2020 | 100% |
| Internal visual | 2010, condition A or approved alternate | 100% |
| Nondestructive bond pull | 2023 | 100% |
| Reverse bias burn-in | 1015 | 100% |
| Burn-in parameters | 1015, total of 240 hours at +125° C | 100% |
| Radiographic | 2012 | 100% |

- a. RHA tests for device classes B and S for levels M, D, R, and H or for device class M for levels M and D shall be performed through each level to determine at what levels the devices meet the RHA requirements. These RHA tests shall be performed for initial qualification and after design or process changes which may affect the RHA performance of the device.
- b. End-point electrical parameters shall be as specified in table IIA herein.
- c. Prior to total dose irradiation, each selected sample shall be assembled in its qualified package. It shall pass the specified group A electrical parameters in table I for subgroups specified in table IIA herein.
- d. For device classes M, B, and S the devices shall be subjected to radiation hardness assured tests as specified in MIL-M-38510 for RHA level being tested, and meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = 25^\circ\text{C} \pm 5$ percent, after exposure.
- e. Prior to and during total dose irradiation testing, the devices shall be biased to establish a worst case condition as specified in the radiation exposure circuit.
 - (1) Inputs tested high, $V_{CC} = \text{volts dc}$, $R_{CC} = \Omega + 5\%$, $V_{IN} = \text{volts dc}$, $R_{IN} = \Omega + 20\%$, and all outputs are open.
 - (2) Inputs tested low $V_{CC} = \text{volts dc}$, $R_{CC} = \Omega + 5\%$, $V_{IN} = 0.0 \text{ V dc}$, and all outputs are open.
- f. For device classes M, B, and S, subgroups 1 and 2 in table V, method 5005 of MIL-STD-883 shall be tested as appropriate for device construction.
- g. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

| | | | |
|---|------------------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-90880 |
| | | REVISION LEVEL | SHEET 10 |

DESC FORM 193A
SEP 87

* U. S. GOVERNMENT PRINTING OFFICE: 1968-550-547

Table IIC. Delta limits at +25°C.

| Parameter 1/ | All device types |
|--------------|--|
| $R_{DS(ON)}$ | ±10 percent of specified value in table I. |
| $I_{D(OFF)}$ | ±10 percent of specified value in table I. |

1/ The above parameters shall be recorded before and after the required burn-in and life tests to determine the delta.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.1.2 Substitutability. Device classes B and Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.3 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and which SMD's are applicable to that system. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-ECS, telephone (513) 296-6022.

6.4 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone (513) 296-5375.

| | | | | |
|---|------------------|----------------|--|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | | 5962-90880 |
| | | REVISION LEVEL | | SHEET 11 |

DESC FORM 193A
SEP 87

* U S GOVERNMENT PRINTING OFFICE 1988-550-547

6.5 Symbols, definitions, and functional descriptions.

6.6 One part - one part number system. The one part - one part number system described below has been developed to allow for transitions between identical generic devices covered by the four major microcircuit requirements documents (MIL-M-38510, MIL-H-38534, MIL-I-38535, and 1.2.1 of MIL-STD-883) without the necessity for the generation of unique PIN's. The four military requirements documents represent different class levels, and previously when a device manufacturer upgraded military product from one class level to another, the benefits of the upgraded product were unavailable to the Original Equipment Manufacturer (OEM), who was contractually locked into the original unique PIN. By establishing a one part number system covering all three documents, the OEM can acquire to the highest class level available for a given generic device to meet system needs without modifying the original contract parts selection criteria.

| <u>Military documentation format</u> | <u>Example PIN under new system</u> | <u>Manufacturing source listing</u> | <u>Document listing</u> |
|---|-------------------------------------|-------------------------------------|-------------------------|
| <u>New</u> MIL-M-38510 Military Detail Specifications (in the SMD format) | 5962-XXXXXZZ(B or S)YY | QPL-38510 (Part 1 or 2) | MIL-BUL-103 |
| <u>New</u> MIL-H-38534 Standardized Military Drawings | 5962-XXXXXZZ(H or K)YY | QML-38534 | MIL-BUL-103 |
| <u>New</u> MIL-I-38535 Standardized Military Drawings | 5962-XXXXXZZ(Q or V)YY | QML-38535 | MIL-BUL-103 |
| <u>New</u> 1.2.1 of MIL-STD-883 Standardized Military Drawings | 5962-XXXXXZZ(M)YY | MIL-BUL-103 | MIL-BUL-103 |

6.7 Sources of supply.

6.7.1 Sources of supply for device classes B and S. Sources of supply for device classes B and S are listed in QPL-38510.

6.7.2 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DESC-ECS and have agreed to this drawing.

6.7.3 Approved sources of supply for device class M. Approved sources of supply for class M is listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-ECS.

| | | | |
|---|------------------|----------------|----------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | 5962-90880 | |
| | | REVISION LEVEL | SHEET 12 |

DESC FORM 193A
SEP 87

U S GOVERNMENT PRINTING OFFICE 1988-850-547

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN

DATE: 11 SEPTEMBER 1990

Approved sources of supply for SMD 5962-90880 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-ECS. This bulletin is superseded by the next dated revision of MIL-BUL-103.

| Standardized Military drawing PIN | Vendor CAGE number | Vendor similar part number 1/ |
|---|--------------------------|-------------------------------------|
| 5962-9088001MEX | 27014 | AH5012J/883 |

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

27014

Vendor name
and address

National Semiconductor Corporation
2900 Semiconductor Drive
P.O. Box 58090
Santa Clara, CA 95052-8090

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.