

P-tec Corp.
 2405 Commerce Circle
 Alamosa Co. 81101
 www.p-tec.net

Tel:(800)688-0613
 Tel:(719) 589 3122
 Fax:(719) 589 3592
 sales@p-tec.net



PL00221 Series SMD LED 0805 Package

Features

- *Flat Lens Thin Package 2.0 x 1.25 x 0.75mm
- *GaP Green LED Chip used
- *Low Current Requirements
- *High Light Output
- *Compatible with IR Solder-Process
- *Industry Standard Footprint
- *2000 or 1000 pcs per Reel
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	40mW
Reverse Voltage (<100µA)	5.0V
Max Forward Current	25mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-40°C to +85°C
Reflow Soldering Temperature.....	260°C for 10 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Dominant Wave Length	Peak Wave Length	Viewing Angle 2θ1/2	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Water Clear Lens			nm	nm	Deg				
PL00221-WCG13	Green	GaP	570	568	120°	2.2	2.6	5.0	12.0

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

