



	NO.	PQ24-101E		
Product Specification and Approval Sheet	Version	3	Page	1/4

Radial Leaded PTC Resettable Fuse: FRV Series

Preliminary



1. Summary

- (a) **RoHS Compliant (Lead Free) Product**
- (b) **Applications: Line Voltage Power Supply, Transformer and Appliances**
- (c) **Product Features: Low hold current, Solid state, Radial leaded product ideal for up to 265V_{AC/DC}**
- (d) **Operation Current: 50mA~550mA**
- (e) **Maximum Operating Voltage: 240V_{AC/DC}**
- (f) **Maximum Interrupt Voltage: 265V_{AC/DC}**
- (g) **Temperature Range : -40°C to 85°C**

2. Agency Recognition

- UL: File No. Pending
- C-UL: File No. Pending
- TÜV: File No. Pending

3. Electrical Characteristics (23°C)


Part Number	Hold Current	Trip Current	Max.Time to Trip	Maximum Current	Rated Voltage	Typical Power	Resistance Tolerance	
							R _{MIN}	R _{1MAX}
	I _H , A	I _T , A	at 5xI _H	I _{MAX} , A	V _{MAX} , V _{AC}	P _d , W	ohms	ohms
FRV005-240F	0.05	0.12	15.0	1.0	240	0.70	18.50	65.00
FRV008-240F	0.08	0.19	15.0	1.2	240	0.80	7.40	26.00
FRV012-240F	0.12	0.30	15.0	1.2	240	1.00	3.00	12.00
FRV016-240F	0.16	0.37	15.0	2.0	240	1.40	2.50	7.80
FRV025-240F	0.25	0.56	18.5	3.5	240	1.50	1.30	3.80
FRV033-240F	0.33	0.74	18.5	4.5	240	1.70	0.83	2.60
FRV040-240F	0.40	0.90	24.0	5.5	240	2.00	0.60	1.90
FRV055-240F	0.55	1.25	26.0	7.0	240	3.40	0.45	1.45

I_H=Hold current-maximum current at which the device will not trip at 23°C still air.
I_T=Trip current-minimum current at which the device will always trip at 23°C still air.
V_{MAX}=Maximum voltage device can withstand without damage at its rated current.
I_{MAX}= Maximum fault current device can withstand without damage at rated voltage (V_{MAX}).
P_d=Typical power dissipated from device when in tripped state in 23°C still air environment.
R_{MIN}=Minimum device resistance at 23°C.
R_{1MAX}=Maximum device resistance at 23°C, 1 hour after tripping.
Physical specifications:
Lead material: FRV005-240F~FRV016-240F Tin plated copper, 24AWG.
FRV025-240F~FRV040-240F Tin plated copper, 22AWG.
FRV055-240F Tin plated copper, 20AWG.
Soldering characteristics: MIL-STD-202, Method 208E.
Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement.



	NO.	PQ24-101E		
Product Specification and Approval Sheet	Version	3	Page	2/4

4. Production Dimensions (millimeter)




FRV 005-240F~FRV016-240F
 Lead Size: 24AWG
 Φ 0.51 mm Diameter

FRV025-240F~FRV040-240F
 Lead Size: 22AWG
 Φ 0.65 mm Diameter

FRV055-240F
 Lead Size: 20AWG
 Φ 0.81 mm Diameter

Part Number	A	B	C	D	E
	Maximum	Maximum	Typical	Minimum	Maximum
FRV005-240F	8.3	10.7	5.1	7.6	3.8
FRV008-240F	8.3	10.7	5.1	7.6	3.8
FRV012-240F	8.3	10.7	5.1	7.6	3.8
FRV016-240F	9.9	12.5	5.1	7.6	3.8
FRV025-240F	9.6	17.4	5.1	7.6	3.8
FRV033-240F	11.4	16.5	5.1	7.6	3.8
FRV040-240F	11.5	19.5	5.1	7.6	3.8
FRV055-240F	14.0	21.7	5.1	7.6	4.1

5. Thermal Derating Curve






	NO.	PQ24-101E		
Product Specification and Approval Sheet	Version	3	Page	3/4

6. Typical Time-To-Trip at 23°C

- A= FRV005-240F
- B= FRV008-240F
- C= FRV012-240F
- D= FRV016-240F
- E= FRV025-240F
- F= FRV033-240F
- G= FRV040-240F
- H= FRV055-240F





7. Material Specification


Lead material : FRV005-240F~FRV016-240F Tin plated copper, 24AWG.
 FRV025-240F~FRV040-240F Tin plated copper, 22AWG.
 FRV055-240F Tin plated copper, 20AWG.
 Soldering characteristics: MIL-STD-202, Method 208E.
 Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement.

8. Part Numbering and Marking System

Part Numbering System



Part Marking System





DB LECTRO^U
COMPOSANTS ÉLECTRONIQUES
ELECTRONIC COMPONENTS

	NO.	PQ24-101E		
Product Specification and Approval Sheet	Version	3	Page	4/4

- Warning:** - Each product should be carefully evaluated and tested for their suitability of application.
- Operation beyond the specified maximum rating or improper use may result in damage and possible electrical arcing and/or flame.
 - PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
 - Avoid contact of PPTC device with chemical solvent, including some inert material such as silicone based oil, lubricant and etc. Prolonged contact will damage the device performance.
 - Additional protection mechanism are strongly recommended to be used in conjunction with the PPTC device for protection against abnormal or failure conditions.
 - Avoid use of PPTC device in a constrained space such as potting material, housing and containers where have limited space to accommodate device thermal expansion and/or contraction.