



SAW Components

Data Sheet B4119

Data Sheet

An abstract, grayscale graphic featuring a stylized, three-dimensional representation of the EPCOS logo. The logo is rendered in a glowing, metallic style, with the word "EPCOS" in large, bold, sans-serif letters. The background is dark and textured, with a faint, circular pattern that suggests a globe or a complex circuit board layout.



SAW Components

B4119

Low-Loss Filter for Mobile Communication

942,5 MHz

Data Sheet




Ceramic package **DCC6D**

Features

- Low-loss RF filter for mobile telephone EGSM systems, receive path
- Low amplitude ripple
- Usable passband 35 MHz
- Unbalanced to balanced Operation
- Ceramic package for **Surface Mounted Technology (SMT)**

Terminals


- Ni, gold-plated



Dimensions in mm, approx. weight 0,037 g

Pin configuration

- 2 Input, unbalanced
- 4, 6 Balanced outputs
- 1, 3, 5 To be grounded
- 1, 3, 5 Case ground



Type	Ordering code	Marking and Package according to	Packing according to
B4119	B39941-B4119-U510	C61157-A7-A68	F61074-V8089-Z000

Electrostatic **S**ensitive **D**evice (**ESD**)

Maximum ratings

Operable temperature range	T	- 30 / + 80	°C	source and load impedance 50 Ω peak power of GSM signal, duty cycle 1 : 8 continuous wave
Storage temperature range	T_{stg}	- 40 / + 85	°C	
DC voltage	V_{DC}	3	V	
Input power max.	P_{IN}	15	dBm	
880 ... 915 MHz				
elsewhere		0	dBm	



SAW Components

B4119

Low-Loss Filter for Mobile Communication

942,5 MHz

Data Sheet



Characteristics

Operating temperature range:	$T = 25 \pm 2 \text{ }^{\circ}\text{C}$
Terminating source impedance:	$Z_S = 50 \text{ } \Omega$
Terminating load impedance:	$Z_L = 50 \text{ } \Omega$ (balanced)

		min.	typ.	max.	
Center frequency	f_C	—	942,5	—	MHz
Maximum insertion attenuation	α_{\max}				
925,0 ... 960,0 MHz		—	2,7	3,5	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
925,0 ... 960,0 MHz		—	1,0	2,0	dB
Attenuation	α				
0,0 ... 850,0 MHz		50	60	—	dB
850,0 ... 880,0 MHz		40	55	—	dB
880,0 ... 905,0 MHz		28	40	—	dB
905,0 ... 915,0 MHz		19	28	—	dB
980,0 ... 1050,0 MHz		22	25	—	dB
1050,0 ... 1680,0 MHz		45	53	—	dB
1680,0 ... 2000,0 MHz		40	45	—	dB
2000,0 ... 3000,0 MHz		30	40	—	dB
3000,0 ... 6000,0 MHz		15	25	—	dB



SAW Components

B4119

Low-Loss Filter for Mobile Communication

942,5 MHz

Data Sheet



Characteristics

Operating temperature range: $T = -20^{\circ}\text{C}$ to $+75^{\circ}\text{C}$
Terminating source impedance: $Z_S = 50\ \Omega$
Terminating load impedance: $Z_L = 50\ \Omega$ (balanced)

		min.	typ.	max.	
Center frequency	f_C	—	942,5	—	MHz
Maximum insertion attenuation	α_{\max}				
925,0 ... 960,0 MHz		—	3,1	4,0	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
925,0 ... 960,0 MHz		—	1,4	2,5	dB
Attenuation	α				
0,0 ... 850,0 MHz		50	60	—	dB
850,0 ... 880,0 MHz		40	55	—	dB
880,0 ... 905,0 MHz		28	35	—	dB
905,0 ... 915,0 MHz		15	25	—	dB
980,0 ... 1050,0 MHz		20	23	—	dB
1050,0 ... 1680,0 MHz		45	53	—	dB
1680,0 ... 2000,0 MHz		40	45	—	dB
2000,0 ... 3000,0 MHz		30	40	—	dB
3000,0 ... 6000,0 MHz		15	25	—	dB



SAW Components

B4119

Low-Loss Filter for Mobile Communication

942,5 MHz

Data Sheet



Characteristics

Operating temperature range: $T = -30^{\circ}\text{C}$ to $+80^{\circ}\text{C}$
Terminating source impedance: $Z_S = 50\ \Omega$
Terminating load impedance: $Z_L = 50\ \Omega$ (balanced)

		min.	typ.	max.	
Center frequency	f_C	—	942,5	—	MHz
Maximum insertion attenuation	α_{\max}				
925,0 ... 960,0 MHz		—	3,3	4,3	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
925,0 ... 960,0 MHz		—	1,6	2,8	dB
Attenuation	α				
0,0 ... 850,0 MHz		50	60	—	dB
850,0 ... 880,0 MHz		40	55	—	dB
880,0 ... 905,0 MHz		28	35	—	dB
905,0 ... 915,0 MHz		13	23	—	dB
980,0 ... 1050,0 MHz		19	22	—	dB
1050,0 ... 1680,0 MHz		45	53	—	dB
1680,0 ... 2000,0 MHz		40	45	—	dB
2000,0 ... 3000,0 MHz		30	40	—	dB
3000,0 ... 6000,0 MHz		15	25	—	dB



SAW Components

B4119


Low-Loss Filter for Mobile Communication

942,5 MHz


Data Sheet



Transfer function



Transfer function (wide band)





SAW Components	B4119
Low-Loss Filter for Mobile Communication	942,5 MHz
Data Sheet	SMD

Published by EPCOS AG
Surface Acoustic Wave Components Division, OFW E MF
P.O. Box 80 17 09, D-81617 München

© EPCOS AG 1999. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.