

0.5 mm-pitch Rotary-lock Type

XF2H

New rotary-lock concept achieves high reliability and superior work efficiency.

- The unique rotary lock construction significantly improves work efficiency during FPC mounting.
- Double-sided contacts maintain a stable contact force. Discrimination between FPC upper and lower contacts is unnecessary.
- Low-profile, protruding only 2 mm on the PCB.



Specifications

Rated current	0.5 A
Rated voltage	50 VDC
Contact resistance	30 mΩ max. (max. 20 mV, max. 100 mA)
Insulation resistance	100 MΩ min. (at 250 VDC)
Withstand voltage	250 VAC 1 min. (leakage current: 1 mA max.)
Insertion tolerance	20 times
Ambient temperature	-30 to +85°C (No condensation at low temperatures.)

Materials/Finish

Housing	PA46 resin (UL94V-0)/natural
Slider	LCP resin (UL94V-0)/black
Contact	Copper-alloy/nickel spring substrate (2 μm) plated with tin alloy (2 μm)
Hold-down	Copper-alloy/copper substrate (2 μm) plated with tin alloy (2 μm)

Dimensions

XF2H-□□15-1








Table of Dimensions

Poles	Model	A	B	C	D	E	F
10	XF2H-1015-1	9.1	4.5	5.6	8.5	6.5	10.1
20	XF2H-2015-1	14.1	9.5	10.6	13.5	11.5	15.1
24	XF2H-2415-1	16.1	11.5	12.6	15.5	13.5	17.1
30	XF2H-3015-1	19.1	14.5	15.6	18.5	16.5	20.1
35	XF2H-3515-1	21.6	17.0	18.1	21.0	19.0	22.6
40	XF2H-4015-1	24.1	19.5	20.6	23.5	21.5	25.1
45	XF2H-4515-1	26.6	22.0	23.1	26.0	24.0	27.6
50	XF2H-5015-1	29.1	24.5	25.6	28.5	26.5	30.1

Printed Circuit Board Matching Dimensions (Top View)



Applicable FPC Dimensions



Ordering Information

Poles	Model	Quantity per reel*
10	XF2H-1015-1	1,500
20	XF2H-2015-1	
24	XF2H-2415-1	
30	XF2H-3015-1	
35	XF2H-3515-1	
40	XF2H-4015-1	
45	XF2H-4515-1	
50	XF2H-5015-1	

* Order an integer multiple of the quantity per reel.

0.5 mm-pitch ZIF-Slide Type

XF2J

Top-entry ZIF Connector

- Slider achieves secure locking.
- Low-profile, protruding only 4.15 mm on the PCB.
- Adhesion face on top of the connector suits automatic mounting.



Specifications

Rated current	0.5 A
Rated voltage	50 VDC
Contact resistance	30 mΩ max. (max. 20 mV, max. 100 mA)
Insulation resistance	100 MΩ min. (at 100 VDC)
Withstand voltage	250 VAC 1 min. (leakage current: 1 mA max.)
Insertion tolerance	30 times
Ambient temperature	-30 to +85°C (No condensation at low temperatures.)

Materials/Finish

Housing	PA46 resin (UL94V-0)/natural
Slider	PPS resin (UL94V-0)/black
Contact	Copper-alloy/nickel spring substrate (2 μm) plated with tin alloy (2 μm)
Hold-down	Copper-alloy/copper substrate (2 μm) plated with tin alloy (2 μm)

Dimensions

XF2J-□□24-11







Table of Dimensions

Poles	Model	A	B	C	D
6	XF2J-0624-11	7.5	2.5	3.6	6.9
8	XF2J-0824-11	8.5	3.5	4.6	7.9
12	XF2J-1224-11	10.5	5.5	6.6	9.9
14	XF2J-1424-11	11.5	6.5	7.6	10.9
16	XF2J-1624-11	12.5	7.5	8.6	11.9
22	XF2J-2224-11	15.5	10.5	11.6	14.9
28	XF2J-2824-11	18.5	13.5	14.6	17.9

Printed Circuit Board Matching Dimensions (Top View)



Applicable FPC Dimensions



Ordering Information

Poles	Model	Quantity per reel*
6	XF2J-0624-11	1,000
8	XF2J-0824-11	
12	XF2J-1224-11	
14	XF2J-1424-11	
16	XF2J-1624-11	
22	XF2J-2224-11	
28	XF2J-2824-11	

* Order an integer multiple of the quantity per reel.

Ultra-low-profile Connector (SMT Terminal) Side-entry Non-ZIF Type

XF2E

Optimum low-profile design.
Ultra-low-profile FPC/FFC connector only
1.5 mm above the PCB.



- Ultra-low-profile only 1.5 mm on the PCB allows mounting in spaces with restricted height.
- 0.8 mm-pitch SMT connectors allow high-density mounting.
- Modified-PA-resin housing is compatible with VPS, IR reflow, etc.
- Double-sided contacts maintain a stable contact force.
- Standard tape packing compatible with automatic mounting.

Specifications


Rated current	0.5 A
Rated voltage	50 VDC
Contact resistance	30 m max. (max. 20 mV, max. 100 mA)
Insulation resistance	100 MΩmin. (at 100 VDC)
Withstand voltage	500 VAC 1 min. (leakage current: 1 mA max.)
Total insertion force	Poles x 2.0 N (200 gf) max.
Total removal force	Poles x 0.3 N (200 gf) max.
Insertion tolerance	10 times
Ambient temperature	-30 to +85°C (No condensation at low temperatures.)

Dimensions

XF2E-□□15-1(SMT Terminal)



Mounted Image




Materials/Finish

Housing	Modified PA resin containing glass (UL94V-0)/opal
Contact	Copper-alloy/nickel spring substrate (2 μm) plated with tin alloy (2 μm)

Table of Dimensions

Poles	A	B	C	D
5	7.6	4.9	3.2	6.2
6	8.4	5.7	4.0	7.0
7	9.2	6.5	4.8	7.8
8	10.0	7.3	5.6	8.6
9	10.8	8.1	6.4	9.4
10	11.6	8.9	7.2	10.2
12	13.2	10.5	8.8	11.8
15	15.6	12.9	11.2	14.2
17	17.2	14.5	12.8	15.8
20	19.6	16.9	15.2	18.2

Applicable FPC Dimensions



Ordering Information

Poles	Model	Quantity per reel*
5	XF2E-0515-1	4,000
6	XF2E-0615-1	
7	XF2E-0715-1	
8	XF2E-0815-1	
9	XF2E-0915-1	
10	XF2E-1015-1	
12	XF2E-1215-1	
15	XF2E-1515-1	
17	XF2E-1715-1	
20	XF2E-2015-1	

* Order an integer multiple of the quantity per reel.


Non-ZIF Type

XF2K/XF2G

XF2K 0.5 mm-pitch Non-ZIF Type

- Low-profile, protruding only 1.5 mm on the PCB.
- Double-sided contacts maintain a stable contact force. Discrimination between FPC upper and lower contacts is unnecessary.

■ Dimensions




■ Poles

6

■ Quantity Per Reel

4,000


■ Applicable FPC Dimensions



XF2G 0.5 mm-pitch N-ZIF Type

- Low-profile, protruding only 4.15 mm on the PCB.
- Adhesion face on top of the connector suits automatic mounting.

■ Dimensions




■ Poles

16, 20, 30

■ Quantity Per Reel

1,000

■ Applicable FPC Dimensions



Precautions

Recommended Reflow Conditions

Pre-heat

temperature: 150 ± 10°C

Time: 60 to 120 seconds

Soldering

temperature: 200 to 240°C

Time: Not exceeding 30 seconds
(Not exceeding 10 seconds at 240°C maximum temperature.)

Storage

Do not store under high humidity levels as this may cause deterioration of the insulation.

Handling the FPC

Do not forcibly bend or pull an FPC which has been mounted and locked. This may cause discontinuities in the FPC.

OMRON SALES OFFICES

ASIA/OCEANIA

■ OMRON CORPORATION

28F Crystal Tower Bldg. 1-2-27, Shiromi, Chuo-ku
Osaka 540-6028 **Japan**
Phone:81-6-6949-6010 Fax:81-6-6949-6019

■ OMRON ELECTRONICS ASIA LTD.

Unit 601-10 Tower 2, The Gateway
NO.25 Canton Road, Tsimshatsui,
Kowloon **Hong Kong**
Phone:852-2375-3827 Fax:852-2375-1475

■ OMRON ASIA-PACIFIC PTE. LTD. INDONESIA REPRESENTATIVE OFFICE

Danamon Aetna Lifetower, Suite 1602
JL.Jend Sudirman Kav 45-46
Jakarta 12930 **Indonesia**
Phone:62-21-577-0833 Fax:62-21-577-0840

■ OMRON KOREA CO.LTD.

3F, New Seoul Bldg. #618-3, Sin Sa-Dong,
Kang Nam-Gu Seoul **Korea**
Phone:82-2-549-2766 Fax:82-2-517-9033

■ OMRON ELECTRONICS SALES AND SERVICE(M) SDN. BHD. (222675-U)

10th Floor, Block B Menara PKNS-PJ
No. 17, Jalan Yong Shook Lin
46050 Petaling Jaya
Selangor Darul Ehsan **Malaysia**
Phone:60-3-754-7323 Fax:60-3-754-6618

■ OMRON ASIA-PACIFIC PTE.LTD.

83 Clemenceau Avenue, #11-01, UE Square
239920 **Singapore**
Phone:65-835-3011 Fax:65-835-2711

■ OMRON TAIWAN ELECTRONICS INC. HEAD QUARTERS

6F, Home Young Bldg., NO. 363,
Fu-Shing N. Road. Taipei **Taiwan**
Phone:886-2-2715-3331 Fax:886-2-2712-6712

■ OMRON ELECTRONICS CO.LTD.

Rasa Tower 20TH Floor, 555 Phaholyothin
Road, Ladyao Chatuchak, Bangkok 10900 **Thailand**
Phone:66-2-937-0500 Fax:66-2-937-0501

■ OMRON ELECTRONICS PTY.LTD.

71 Epping Road North Ryde N. S. W 2113 **Australia**
Phone:61-2-9878-6377 Fax:61-2-9878-6981

■ OMRON ELECTRONICS LTD.

65 Boston Road Private Bag 92620
Symonds Street Auckland **New Zealand**
Phone:64-9-358-4400 Fax:64-9-358-4411

NOATH/SOUTH AMERICA

■ OMRON ELECTRONICS INC.

1300 North Basswood Suite 300
Schaumburg, IL 60173 **U.S.A**
Phone:1-847-843-7910 Fax:1-847-843-3887

■ OMRON CANADA INC.

885 Milner Avenue Scarborough,
Ontario M1B 5V8 **Canada**
Phone:1-416-286-6465 Fax:1-416-286-6648

■ OMRON ELETRONICA DO BRASIL LTDA.

Av. Santa Catarina, 935/939 04378-300
Sao Paulo-SP **Brazil**
Phone:55-11-5564-6488 Fax:55-11-5564-7751

EUROPE

■ OMRON EUROPE B.V.

Wegalaan 67-69, NL-2132
JD Hoofddorp **The Netherlands**
Phone:31-2356-81-300 Fax:31-2356-81-388

■ OMRON ELECTRONICS G.m.b.H

Altmannsdorferstrasse
142 A-1231 Vienna **Austria**
Phone:43-1-801-90-0 Fax:43-1-804-48-46

■ OMRON ELECTRONICS N.V./S.A.

Stationsstraat 24 B-1702
Groot Bijgaarden **Belgium**
Phone:32-2-466-2480 Fax:32-2-466-0687

■ OMRON ELECTRONICS SPOL. S.R.O.

Srobarova 6 CZ-100 10 Prague 10 **Czech**
Phone:42-2-67311-254 Fax:42-2-740333

■ OMRON ELECTRONICS A/S

Odinsvej 15 DK-2600
Glostrup **Denmark**
Phone:45-43-44-00-11 Fax:45-43-44-02-11

■ OMRON ELECTRONICS O.Y.

Metsanpojanukuja 5 FIN-02130
Espoo **Finland**
Phone:358-9-5495800 Fax:358-9-54958150

■ OMRON ELECTRONICS S.a.r.l

19, Rue Du Bois
Galon/B.P. 33 F-94121
Fontenay Sous Bois/Cedex **France**
Phone:33-1-4974-7000 Fax:33-1-4876-0930

NOATH/SOUTH AMERICA

■ OMRON ELECTRONICS G.m.b.H

Itterpark 2-4 D-40724
Hilden **Germany**
Phone:49-2103-203-3 Fax:49-2103-203-474

■ OMRON ELECTRONICS LTD.

Kiss Erno u. 1-13 H-1046
Budapest **Hungary**
Phone:36-1-399-3050 Fax:36-1-399-3060

■ OMRON ELECTRONICS S.r.l.

Viale Certosa 49I-20149
Milano **Italy**
Phone:39-2-32-68-1 Fax:39-2-32-51-54

■ OMRON ELECTRONICS B.V.

Wegalaan 61, NL-2132
JD Hoofddorp **The Netherlands**
Phone:31-23-56-81100 Fax:31-23-56-81188

■ OMRON ELECTRONICS NORWAY A/S

Ole Deviksvet 4 N-0666 Oslo **Norway**
Phone:47-22-65-75-00 Fax:47-22-65-83-00

■ OMRON ELECTRONICS LDA

Edificio OMRON Rua de Sao
Tome, Lote 131 P-2685
Prior Velho **Portugal**
Phone:351-1-942-9400 Fax:351-1-941-7899

■ OMRON ELECTRONICS S.A.

C/Arturo Soria 95 E-23027
Madrid **Spain**
Phone:34-1-3-77-9000 Fax:34-1-3-77-9056

■ OMRON ELECTRONICS A.B.

Norgegaten 1 S-164 29
Kista **Sweden**
Phone:46-8-632-35-00 Fax:46-8-632-35-10

■ OMRON ELECTRONICS A.G.

Sennweidstrasse 44
CH-6312 Steinhausen **Switzerland**
Phone:41-41-748-1313 Fax:41-41-748-1345

■ OMRON ELECTRONICS LTD.

1 Apsley Way, Staples Corner
London NW2 7HF **United Kingdom**
Phone:44-181-450-4646 Fax:44-181-450-8087

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

Cat. No. G011-E1-01 In the interest of product improvement, specifications are subject to change without notice.

OMRON Corporation

C&C Components Division H.Q.

Mechanical - Components Division

28th Fl., Crystal Tower Bldg.,

1-2-27, Shiromi, Chuo-ku,

Osaka 540-6028 Japan

Phone: (81)6-6949-6017 Fax: (81)6-6949-6034

Printed in Japan
0199-1M (0199) (W)