



WORLDWIDE



T-1 3/4 Wire Terminal (standard)

**T-1 3/4 Wire Terminal (standard)**



| Part Number | Design Voltage | Amps | MSCP | Life Hours | Filament Type |
|-------------|----------------|------|------|------------|---------------|
| CM1739      | 6.30           | .070 | .230 | 1,000      | C-2R          |
| CM2037      | 6.30           | .200 | .400 | 20,000     | C-2R          |
| CM2039      | 6.30           | .075 | .230 | 1,000      | C-2R          |
| CM2112      | 6.30           | .200 | .550 | 5,000      | C-2R          |
| CM2179      | 6.30           | .040 | .030 | 20,000     | C-2V          |
| CM2180      | 6.30           | .040 | .020 | 20,000     | C-2V          |
| CM2181      | 6.30           | .200 | .400 | 20,000     | C-2F          |
| CM8350      | 6.30           | .150 | .450 | 3,000      | C-2R          |
| CM2178      | 8.00           | .085 | .150 | 25,000     | C-2F          |
| CM1869      | 10.00          | .014 | .002 | 50,000     | C-2F          |
| CM2107      | 10.00          | .040 | .080 | 5,000      | C-2F          |
| CM2149      | 10.00          | .014 | .002 | 50,000     | C-2F          |
| CM8946      | 11.00          | .022 | .030 | 10,000     | C-2F          |
| CM2174      | 12.00          | .040 | .100 | 10,000     | C-2F          |
| CM1705      | 14.00          | .080 | .500 | 1,500      | C-2F          |
| CM2162      | 14.00          | .100 | .500 | 10,000     | C-2F          |
| CM2182      | 14.00          | .080 | .300 | 40,000     | C-2F          |
| CM2382      | 14.00          | .080 | .300 | 40,000     | C-2F          |
| CM2102      | 18.00          | .040 | .150 | 10,000     | C-2F          |
| CM8425      | 22.00          | .040 | .300 | 2,000      | C-2F          |
| CM2041      | 24.00          | .060 | .500 | 5,000      | C-2F          |
| CM2176      | 24.00          | .050 | .500 | 1,000      | C-2F          |
| CM476       | 28.00          | .060 | .340 | 25,000     | C-2F          |
| CM1749      | 28.00          | .060 | .340 | 25,000     | C-2F          |
| CM1762      | 28.00          | .040 | .340 | 4,000      | C-2F          |
| CM1764      | 28.00          | .040 | .340 | 4,000      | C-2F          |
| CM2185      | 28.00          | .040 | .150 | 10,000     | C-2F          |
| CM2187      | 28.00          | .040 | .300 | 7,000      | C-2F          |
| CM2287      | 28.00          | .040 | .300 | 7,000      | C-2F          |
| CM2370      | 28.00          | .050 | .700 | 1,000      | C-2F          |
| CM6033      | 28.00          | .024 | .150 | 4,000      | CC-2F         |
| CM8361      | 28.00          | .065 | .650 | 5,000      | C-2F          |
| CM8461      | 28.00          | .050 | .500 | 5,000      | C-2F          |
| CM1918      | 32.00          | .040 | .300 | 7,000      | C-2F          |
| CM6748      | 48.00          | .025 | .200 | 5,000      | CC-2F         |



America:  
 CML Innovative Technologies, Inc.  
 147 Central Avenue  
 Hackensack -NJ 07601 -USA  
 Tel:1-201-489 -8989  
 Fax:1-201-489 -6911  
 e-mail:americas@cml-it.com

Europe:  
 CML Technologies GmbH &Co.KG  
 Robert-Bunsen-Str.1  
 67098 Bad Dürkheim -GERMANY  
 Tel:+49 (0)6322 9567-0  
 Fax:+49 (0)6322 9567-88  
 e-mail:europe@cml-it.com

Asia:  
 CML Innovative Technologies, Inc.  
 61 Aida Street  
 Singapore 459975  
 Tel:(65)9630 -5003  
 e-mail:asia@cml-it.com