



<b>STK4703 SERIES</b>	thick film hybrid IC	CIRCUIT DRAWING No.6026
<b>2-CHANNEL 10 TO 50W MIN AF POWER AMP.(DUAL-SUPPLY)</b>		 4029


**Features**

- AF Output Power    STK4773: 10Wmin.    STK4793: 15Wmin.    STK4803: 20Wmin.  
                          STK4813: 20Wmin.    STK4833: 25Wmin.    STK4843: 30Wmin.  
                          STK4853: 30Wmin.    STK4863: 35Wmin.    STK4873: 35Wmin.  
                          STK4893: 40Wmin.    STK4913: 50Wmin.
- Contains emitter follower circuit for upgrading.
- Case temperature 125°C is guaranteed, thereby enabling great reduction of heat sink.
- By attaching muting circuit externally, pop noise at the time of power ON/OFF can be rejected.

<b>STK5320 SERIES</b>	thick film hybrid IC	CIRCUIT DRAWING No.6028
<b>2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS</b>		 4036      4037      4039


**Features**

- |           |                  |                  |                  |                  |
|-----------|------------------|------------------|------------------|------------------|
|           | STK5321          | STK5322          | STK5324          | STK5325          |
| Output 1: | 9.5±0.1V (1.6A)  | 9.5±0.1V (1.6A)  | 12.0±0.1V (1.6A) | 12.0±0.1V (1.6A) |
| Output 2: | 12.0±0.3V (2.5A) | 15.0±0.3V (2.5A) | 12.0±0.3V (2.5A) | 14.0±0.3V (2.5A) |
- |           |                  |                  |
|-----------|------------------|------------------|
|           | STK5326          | STK5327          |
| Output 1: | 12.0±0.1V (1.6A) | 15.0±0.3V (2.5A) |
| Output 2: | 13.0±0.3V (2.5A) | 13.5±0.3V (1.6A) |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.
- Package Number: 4036 (STK5324)  
                                          4037 (STK5325, 5326, 5327)  
                                          4039 (STK5321, 5322)

<b>STK5346</b>	thick film hybrid IC	CIRCUIT DRAWING No.6027
<b>2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS</b>		 4038

**Features**

- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.

<b>STK5352,5353</b>	thick film hybrid IC	CIRCUIT DRAWING No.6029
<b>2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS</b>		 4064

**Features**

- |           |                  |                  |
|-----------|------------------|------------------|
|           | STK5352          | STK5353          |
| Output 1: | 6.0±0.1V (0.5A)  | 5.1±0.1V (0.5A)  |
| Output 2: | 12.0±0.1V (1.5A) | 12.0±0.1V (1.5A) |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology)
- Contains power supply for microcomputer.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance