

Zener diode

EMZ6.8N

● Applications

Constant voltage control


● Features

- 1) Small surface mounting type. (EMD3)
- 2) Composite type with two anode common elements
- 3) High reliability


● Construction

Silicon epitaxial planar

● External dimensions (Units: mm)



● Circuit



● Absolute maximum ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit
Power dissipation*	P	150	mW
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55~+150	$^\circ\text{C}$

* Total of 2 elements

● Electrical characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Zener voltage	V_z	6.47	—	7.14	V	$I_z=5\text{mA}$
Reverse current	I_R	—	—	0.5	μA	$V_R=3.5\text{V}$
Operating resistance	Z_z	—	—	40	Ω	$I_z=5\text{mA}$
Capacitance between terminals	C_T	—	9	—	pF	$f=1\text{MHz}, V_R=5\text{V}$

Diodes

● Others

Item	Standard1	IEC1000-4-2
Device configuration	Charge/discharge capacitance : 200pF±10% Discharge resistance : 400Ω ±10%	Charge/discharge capacitance : 150pF Discharge resistance : 330Ω
Judgment contents	5 repetitions No spark or smoke emitted : ±25kV No element destruction : ±20kV No malfunction : ± 8kV	10 repetitions No malfunction Contact : ± 8kV Suspended : ±15kV

● Electrical characteristic curves (Ta=25°C)




Fig.1 Zener voltage characteristic




Fig.2 Operating resistance Zener current characteristic




Fig.3 Derating curve