

SPECIFICATION SHEET

JFW MODEL 50P-1782

SOLID STATE PROGRAMMABLE ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 15-2000 MHz
Impedance 50 Ohms nominal
Attenuation Range 0-127 dB in 1 dB steps
Attenuation Steps 1, 2, 4, 8, 16, 32 and 64 dB
VSWR 1.5:1 maximum
Attenuation Accuracy ± 0.4 dB or 2% of programmed
(whichever is greater)
Insertion Loss 6.0 dB maximum
2.0 dB typical @ 15 MHz
5.5 dB typical @ 2000 MHz
RF Input Power +10 dBm operating
+30 dBm (no damage)
Switching Speed 10 microseconds
DC Supply +5 Vdc @ 300 mA
Control Logic (7 Lines) TTL Low for Thru Path
TTL High for Attenuation
RF Connector SMA female
Operating Temperature Range 0°C to +70°C
Physical Size See outline drawing 092-5410-01

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/04/2007		TRS 05/04/2007	17693	09/16/2009	C	CLK 09/16/2009
15807	05/02/2008	A	TRS 05/02/2008				
16012	06/12/2008	B	TRS 06/12/2008				