



EIC8596-2

UPDATED 07/25/2007

8.50-9.60 GHz 2-Watt Internally-Matched Power FET

FEATURES

- 8.50-9.60GHz Bandwidth
- Input/Output Impedance Matched to 50 Ohms
- +33.5 dBm Output Power at 1dB Compression
- 8.0 dB Power Gain at 1dB Compression
- 30% Power Added Efficiency
- -46 dBc IM3 at PO = 22.5 dBm SCL
- 100% Tested for DC, RF, and R_{TH}

ELECTRICAL CHARACTERISTICS (T_a = 25°C)

SYMBOL	PARAMETERS/TEST CONDITIONS ¹	MIN	TYP	MAX	UNITS
P_{1dB}	Output Power at 1dB Compression V _{DS} = 10 V, I _{DSQ} ≈ 550mA f = 8.50-9.60GHz	32.5	33.5		dBm
G_{1dB}	Gain at 1dB Compression V _{DS} = 10 V, I _{DSQ} ≈ 550mA f = 8.50-9.60GHz	7.0	8.0		dB
ΔG	Gain Flatness V _{DS} = 10 V, I _{DSQ} ≈ 550mA f = 8.50-9.60GHz		±0.6	+ 0.8	dB
PAE	Power Added Efficiency at 1dB Compression V _{DS} = 10 V, I _{DSQ} ≈ 550mA f = 8.50-9.60GHz		30		%
I_{d1dB}	Drain Current at 1dB Compression f = 8.50-9.60GHz		600	700	mA
IM3	Output 3rd Order Intermodulation Distortion Δf = 10 MHz 2-Tone Test; P _{out} = 22.5 dBm S.C.L. ² V _{DS} = 10 V, I _{DSQ} ≈ 65% IDSS f = 9.60GHz	-43	-46		dBc
I_{DSS}	Saturated Drain Current V _{DS} = 3 V, V _{GS} = 0 V		1000	1250	mA
V_P	Pinch-off Voltage V _{DS} = 3 V, I _{DS} = 10 mA		-2.5	-4.0	V
R_{TH}	Thermal Resistance ³		11	12	°C/W

Notes:

1. Tested with 100 Ohm gate resistor.
2. S.C.L. = Single Carrier Level.
3. Overall R_{th} depends on case mounting.

MAXIMUM RATING AT 25 °C^{1,2}

SYMBOLS	PARAMETERS	ABSOLUTE ¹	CONTINUOUS ²
V_{ds}	Drain-Source Voltage	15	10V
V_{gs}	Gate-Source Voltage	-5	-4V
I_{gsf}	Forward Gate Current	21.6mA	7.2mA
I_{gsr}	Reverse Gate Current	-3.6mA	-1.2mA
P_{in}	Input Power	32.5dBm	@ 3dB Compression
T_{ch}	Channel Temperature	175 °C	175 °C
T_{stg}	Storage Temperature	-65 to +175 °C	-65 to +175 °C
P_t	Total Power Dissipation	12.5W	12.5W

Note: 1. Exceeding any of the above ratings may result in permanent damage.

2. Exceeding any of the above ratings may reduce MTTF below design goals.

Specifications are subject to change without notice.

Excelics Semiconductor, Inc. 310 De Guigne Drive, Sunnyvale, CA 94085
Phone: 408-737-1711 Fax: 408-737-1868 Web: www.excelics.com

page 1 of 2
Revised July 2007
www.DataSheet4U.com



EIC8596-2


UPDATED 07/25/2007

8.50-9.60 GHz 2-Watt Internally-Matched Power FET


PACKAGES OUTLINE

Dimensions in inches, Tolerance $\pm .005$ unless otherwise specified

EIC8596-2 (Hermetic)



EIC8596-2NH (Non-Hermetic)



Caution! ESD sensitive device.



Caution! ESD sensitive device.

ORDERING INFORMATION

Part Number	Packages	Grade ¹	f _{Test} (GHz)	P _{1dB} (min)	IM ₃ (min) ²
EIC8596-2	Hermetic	Industrial	8.50-9.60GHz	32.5	-43
EIC8596-2NH	Non-Hermetic	Industrial	8.50-9.60GHz	32.5	-43

Notes: 1. Contact factory for military and hi-rel grades.
2. Exact test conditions are specified in "Electrical Characteristics" table.

DISCLAIMER

EXCELICS SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. EXCELICS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN.

LIFE SUPPORT POLICY

EXCELICS SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF EXCELICS SEMICONDUCTOR, INC. AS HERE IN:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness

Specifications are subject to change without notice.

Excelics Semiconductor, Inc. 310 De Guigne Drive, Sunnyvale, CA 94085
Phone: 408-737-1711 Fax: 408-737-1868 Web: www.excelics.com

page 2 of 2
Revised July 2007
www.DataSheet4U.com