



FAITHFUL TECHNICAL SERIES	
TECH SHEET	03/0004
HAZARD AREA.	FLAME, HEAT AND WELD SPLATTER
FABRIC:	COTTON WITH PROBAN FINISH
FAITHFUL FABRIC CODE	C4
FABRIC COMPOSITION	100% Cotton fibre
FABRIC WEIGHT	320 grammes per square metre
NORMS	Conforms to BS EN 531, A, B1, C1 (Heat exposure) BS EN 470 (Welders clothing)
STOCK FABRIC SHADES	FAITHFUL SUPPLIER  Navy Red  White Maroon  Orange Black  Spruce Green Gold
MINIMUM DYE QUANTITY NON-STOCK SHADES	2500 metres
CLEANING INSTRUCTIONS	To maintain full FR protection, do not use soap or bleach. Maximum wash temperature 40°C (75°C industrial clean) or Dry Clean
END USES 1	To be used where the wearer may briefly come into contact with flame, radiant or convective heat, or for welders clothing.
FAITHFUL OPINION	Excellent value for money fabric. If processed correctly, the finish will last the life of the garment
OTHER INFORMATION	Like all cotton products, wearer comfort level is good.
SIMILAR PRODUCTS	i. Pyrovatex (Dale) ii. Indura (Westex) iii. Hercules (Klopman)