

SPECIFICATION SHEET

JFW MODEL 75R-056

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-10 dB in 1 dB steps
VSWR	1.3:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHz
Insertion Loss	0.4 dB maximum
Attenuation Accuracy	± 0.1 dB DC-30 MHz ± 0.2 dB 30-500 MHz ± 0.3 dB 500-1000 MHz
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Counter-Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-002-01 (BNC) 092-002-02 (F) 092-002-03 (BNC/F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	02/01/1995						
9999	05/19/2003	A	BAC 02/05/2004				
17378	07/02/2009	B	TRS 07/02/2009				