

Multi-Position/Miniature Slide/PC SLS Series

MATERIAL SPECIFICATIONS:

Contacts Silver plate over copper alloy
Case Material Steel
Actuator Material Polycarbonate
Terminals/Fixed Contacts Silver plate over brass
Terminal Seal Epoxy

ENVIRONMENTAL SPECIFICATIONS:



Operating Temperature 14°F to +140°F (-10°C to +60°C)
Storage Temperature 14°F to +140°F (-10°C to +60°C)

TYPICAL PERFORMANCE CHARACTERISTICS:

Contact Rating 250 mA @ 125 VAC, 150 mA @ 12 VDC
Initial Contact Resistance 30 Milliohms max.
Contact Timing Break before make
Insulation Resistance 500 Megohms min.
Dielectric Strength 500 VAC
Actuation Force 250 Grams + 150 - 100
Actuator Travel126" (3.20)
Life Expectancy 10,000 Cycles

B


2 TO 6 POSITIONS



SLS250PC



SLS220PC



SLS240PCA





SLS230PC

Model	Type	Dim. A	Dim. B
SLS220PC	2 Positions	.272(6.91)	.535(13.59)
SLS230PC	3 Positions	.398(10.11)	.661(16.79)
SLS240PC	4 Positions	.524(13.31)	.787(19.99)
SLS250PC	5 Positions	.650(16.51)	.913(23.19)
SLS260PC	6 Positions	.776(19.71)	1.039(26.39)

Multi-Position/PC Terminals/Silver Plate Contacts Standard SL Series


2 TO 10 POSITIONS



SL660
(with KSS KNOB)



SL550



SL770

Model	Type	Dim. A	Dim. B	Dim. C	Knob Model	Description	Dim. D	Dim. E
SL220	2 Positions	.95(24.13)	.750(19.05)	.750(19.05)	KSS10A	Aluminum-Clear Anodize	.270(6.86)	.500(12.70)
SL330	3 Positions	1.11(28.19)	.910(23.1)	.910(23.1)	KSS10B	Aluminum-Black Anodize	.270(6.86)	.500(12.70)
SL550	5 Positions	1.42(36.07)	1.22(30.99)	1.22(31.1)	KSS20A	Aluminum-Clear Anodize	.305(7.75)	.512(13.00)
SL660	6 Positions	1.58(40.13)	1.38(35.05)	1.38(35.1)	KSS20B	Aluminum-Black Anodize	.305(7.75)	.512(13.00)
SL770	7 Positions	1.74(44.20)	1.54(39.12)	1.54(39.1)				
SL880	8 Positions	1.89(48.01)	1.70(43.18)	1.70(43.1)				
SL1000	10 Positions	2.21(56.13)	2.01(51.05)	2.01(51.5)				

Need more technical information?

Consult your local Augat sales office
listed on the back cover

B43

AUGAT Inc.
452 John L. Dietsch Blvd.
Attleboro Falls, MA 02763 USA
(508) 699-9800 FAX (800) 533-2526