

E-Series Surface Mount Mixer

5 - 1000 MHz

EMRSL-2LH

V3.00

Features

- LO Power +10 dBm
- Up to +5 dBm RF
- Surface Mount

Specifications @ 25°C

Frequency Range		
RF		5 - 1000 MHz
LO		5 - 1000 MHz
IF		DC - 1000 MHz
Conversion Loss (dB)	Typical	Maximum
10 - 500 MHz	6.5	8.0
5 - 1000 MHz	7.5	9.5
Isolation (dB)	Typical	Minimum
LO to RF		
5 - 50 MHz	58	40
50 - 500 MHz	39	20
500 - 1000 MHz	22	16
LO to IF		
5 - 50 MHz	52	30
50 - 500 MHz	30	17
500 - 1000 MHz	18	11

Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+5 dBm
DC Polarity	Negative


Ordering Information

Part No.	Packaging
EMRSL-2LH	Tubes
EMRSL-2LHTR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	50 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

SM-24



Dimensions in () are in mm.
Unless Otherwise Noted: .x = ±0.04 (1.00)
.xx = ±0.02 (0.50)
.xxx = ±0.010 (0.250)

Pin Configuration

Function	Pin No.
LO	1
RF	4
IF	5
Ground	2,3,6

S 0558 B