

# SPECIFICATION

Device Name : High Voltage Silicon Diode

Type Name : ESJA89-12A

Spec. No. :

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Fuji Electric Co.,Ltd.  
Matsumoto Factory

|         | DATE | NAME | APPROVED |  | Fuji Electric Co.,Ltd. |  |
|---------|------|------|----------|--|------------------------|--|
| DRAWN   |      |      |          |  |                        |  |
| CHECKED |      |      |          |  |                        |  |
|         |      |      |          |  |                        |  |
|         |      |      |          |  |                        |  |
|         |      |      |          |  |                        |  |

## 1. SCOPE

This specification provide the ratings and the requirements for high voltage silicon diode ESJA82-12A made by FUJI ELECTRIC CO.,LTD.

## 2. OUT VIEW

Shape and dimensions are described in Fig.3.

## 3. IDENTIFICATION

The diode shall be marked with Cathode Mark and Lot No..

## 4. RATINGS AND CHARACTERISTICS

### 4.1 ABSOLUTE MAX. RATINGS. ( Ta=25 °C unless otherwise noted. )

| Items                                 | Conditions                     | Symbols   | Ratings | Units  |
|---------------------------------------|--------------------------------|-----------|---------|--------|
| Repetitive peak reverse voltage.      |                                | $V_{RRM}$ | 12      | kVpeak |
| Non-Repetitive peak forward current.  | 50Hz Sine-half wave peak value | $I_{FSM}$ | 0.5     | Apeak  |
| Average forward current.              | 50Hz Sine Wave                 | $I_{AV}$  | 5       | mA     |
| Allowable junction temperature.       |                                | $T_j$     | 120     | °C     |
| Storage temperature range.            |                                | $T_{stg}$ | -40~120 | °C     |
| Allowable operating case temperature. |                                | $T_c$     | 100     | °C     |

### 4.2 ELECTRICAL CHARACTERISTICS ( Ta=25 °C unless otherwise noted. )

| Items                         | Conditions               | Symbols  | Ratings | Units   |
|-------------------------------|--------------------------|----------|---------|---------|
| Maximum forward voltage drop  | $I_F=10mA$               | $V_F$    | 49.5    | V       |
| Maximum reverse current       | $V_R=12kV$               | $I_{R1}$ | 2       | $\mu A$ |
| Maximum reverse current       | $V_R=12kV, 100^{\circ}C$ | $I_{R2}$ | 5       | $\mu A$ |
| Maximum reverse recovery time | $I_F=2mA, I_R=4mA$       | $t_{rr}$ | 0.06    | $\mu S$ |
| Maximum junction capacitance  | $f=1MHz, V_R=0V$         | $C_j$    | 1       | pF      |

### 4.3 MECHANICAL CHARACTERISTICS

Weight : Ca. 0.3 gr.

Vibration proof : 5 G

Fuji Electric Co.,Ltd

DWG.NO.

H04-004-03




Fig.2 Reverse characteristic[VR-IR]




Fig.4 Reverse recovery time characteristic[ $T_a$ - $t_{rr}$ ]




Fig.1 Forward characteristic[ $V_F$ - $I_F$ ]




Fig.3 Avalanche characteristic [ $V_z$ - $I_z$ ]

Dimensions

Unit : mm

ESJA89-□□A

