


Multilayer Ferrite Beads



MECHANICAL SPECIFICATIONS

Solderability: 90 % coverage after 5 second dip in 235 °C solder following 60 second preheat at 120 °C to 150 °C and type R flux dip

Resistance To Solder Heat: 10 seconds in 260 °C solder after preheat and flux per above

Terminal Strength: 0.6 kilograms (1.32 pounds) minimum for 30 seconds

FEATURES

- High reliability
- Surface mountable
- Magnetically self shielded
- Nickel barrier plating virtually eliminates silver migration
- 100 % lead (Pb)-free and RoHS compliant



RoHS
COMPLIANT

Beam Strength: 1 kilogram (2.2 pounds) minimum

Flex: 0.079" [2 mm] minimum mounted on 0.063" [1.6 mm] thick PC board

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: - 55 °C to + 125 °C

Thermal Shock: 100 cycles, - 40 °C to + 125 °C

Bias Humidity: 85 % RH at 85 °C, 1000 hours at full rated current





STANDARD ELECTRICAL SPECIFICATIONS		
Z at 100 MHz (± 25 %)	DCR MAX. (OhMs)	RATED DC CURRENT (mA)
7	0.06	600
11	0.06	600
17	0.06	600
26	0.06	600
32	0.06	600
40	0.15	300
50	0.15	300
60	0.15	300
75	0.15	300
80	0.15	300
90	0.15	300
100	0.15	300
120	0.15	300
150	0.15	300
180	0.20	200
220	0.20	200
300	0.20	200
400	0.30	200
420	0.30	200
600	0.30	200
1000	0.35	100
1500	0.40	100
2000	0.50	80
2200	0.60	80

PACKAGING OPTIONS
<ul style="list-style-type: none"> • Tape and Reel: Embossed plastic carrier tape Per EIA481-1 4000 pieces on a 7" [178 mm] reel

DIMENSIONS in inches [millimeters]			
Dimensional Outline			
A	B	C	D
0.079 ± 0.008 [2.0 ± 0.2]	0.049 ± 0.008 [1.25 ± 0.2]	0.020 ± 0.012 [0.5 ± 0.3]	0.035 ± 0.008 [0.9 ± 0.2]
Suggested Pad Layout			
E	F	G	H
0.120 [3.0]	0.039 [1.0]	0.039 [1.0]	0.039 [1.0]

DESCRIPTION																		
ILBB-0805 MODEL	11 IMPEDANCE VALUE	± 25 % IMPEDANCE TOLERANCE	ER PACKAGE CODE	e3 JEDEC LEAD (Pb)-FREE STANDARD														
GLOBAL PART NUMBER																		
<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>I</td><td>L</td><td>B</td><td>B</td></tr> </table> MODEL	I	L	B	B	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>0</td><td>8</td><td>0</td><td>5</td></tr> </table> SIZE	0	8	0	5	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>E</td><td>R</td></tr> </table> PACKAGE CODE	E	R	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>1</td><td>1</td><td>0</td></tr> </table> IMPEDANCE VALUE	1	1	0	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>V</td></tr> </table> IMPEDANCE TOLERANCE	V
I	L	B	B															
0	8	0	5															
E	R																	
1	1	0																
V																		







TAPE AND REEL SPECIFICATIONS 0805 SIZE PER EIA-481-1 in inches [millimeters]




A_0	0.059 ± .004 [1.50 ± 0.1]	P_2	0.079 ± .002 [2.00 ± 0.05]
B_0	0.093 ± .006 [2.35 ± 0.15]	W	0.327 Max. [8.3 Max.]
D_0	0.059 + .004/- 0.000 [1.5 + 1/- 0.0]	T	0.008 ± .002 [0.2 ± 0.05]
D_1	0.039 Min. [1.0 Min.]	A	7.000 ± .079 [178 ± 2.0]
E_1	0.069 ± .004 [1.75 ± 0.1]	N	2.500 [63.5]
F	0.138 ± .002 [3.50 ± 0.05]	C	0.512 ± .020/- 0.008 [13 + 0.5/- 0.2]
K_0	0.049 ± .002 [1.24 ± 0.05]	W_1	0.315 + 0.059/- 0.00 [8.00 + 1.50]
P_0	0.157 ± .004 [4.00 ± 0.1]	T_1	0.079 ± .002 [2.00 ± 0.05]
P_1	0.157 ± .004 [4.00 ± 0.1]		









TYPICAL CURVES - FREQUENCY CHARACTERISTICS OF R, X AND Z




TYPICAL CURVES - FREQUENCY CHARACTERISTICS OF R, X AND Z



TYPICAL CURVES - FREQUENCY CHARACTERISTICS OF R, X AND Z



TYPICAL CURVES - FREQUENCY CHARACTERISTICS OF R, X AND Z





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.