

# Single Channel, High Speed Optocouplers

## Technical Data

**6N135/6**  
**HCNW135/6**  
**HCNW4502/3**  
**HCPL-0452/3**  
**HCPL-0500/1**  
**HCPL-4502/3**

### Features

- 15 kV/ $\mu$ s Minimum Common Mode Transient Immunity at  $V_{CM} = 1500$  V (4503/0453)
- High Speed: 1 Mb/s
- TTL Compatible
- Available in 8-Pin DIP, SO-8, Widebody Packages
- Open Collector Output
- Guaranteed Performance from Temperature: 0°C to 70°C
- Safety Approval
  - UL Recognized – 2500 V rms for 1 minute (5000 V rms for 1 minute for HCNW and Option 020 devices) per UL1577
  - CSA Approved
  - VDE 0884 Approved
  - $-V_{IORM} = 630$  V peak for HCPL-4503#060
  - $-V_{IORM} = 1414$  V peak for HCNW devices
  - BSI Certified (HCNW devices only)
- Dual Channel Version Available (253X/4534/053X/0534)
- MIL-STD-1772 Version Available (55XX/65XX/4N55)


### Applications

- High Voltage Isolation
- Video Signal Isolation
- Power Transistor Isolation in Motor Drives
- Line Receivers
- Feedback Element in Switched Mode Power Supplies
- High Speed Logic Ground Isolation – TTL/TTL, TTL/CMOS, TTL/LSTTL
- Replaces Pulse Transformers
- Replaces Slow Phototransistor Isolators
- Analog Signal Ground Isolation

### Description

These diode-transistor optocouplers use an insulating layer between a LED and an integrated photodetector to provide electrical insulation between input and output. Separate connections for the photodiode bias and output-transistor collector increase the speed up to a hundred times that of a conventional phototransistor coupler by reducing the base-collector capacitance.

### Functional Diagram



\* NOTE: FOR 4502/3, 0452/3, PIN 7 IS NOT CONNECTED.

| TRUTH TABLE<br>(POSITIVE LOGIC) |       |
|---------------------------------|-------|
| LED                             | $V_O$ |
| ON                              | LOW   |
| OFF                             | HIGH  |

A 0.1  $\mu$ F bypass capacitor must be connected between pins 5 and 8.

**CAUTION:** It is advised that normal static precautions be taken in handling and assembly of this component to prevent damage and/or degradation which may be induced by ESD.

These single channel optocouplers are available in 8-Pin DIP, SO-8 and Widebody package configurations.

The 6N135, HCPL-0500, and HCNW135 are for use in TTL/CMOS, TTL/LSTTL or wide bandwidth analog applications. Current transfer ratio (CTR) for these devices is 7% minimum at  $I_F = 16$  mA.


The 6N136, HCPL-0501, and HCNW136 are designed for high speed TTL/TTL applications. A standard 16 mA TTL sink current through the input LED will provide enough output current

for 1 TTL load and a 5.6 k $\Omega$  pull-up resistor. CTR for these devices is 19% minimum at  $I_F = 16$  mA.

The HCPL-4502, HCPL-0452, and HCNW4502 provide the electrical and switching performance of the 6N136, HCPL-0501, and HCNW136 with increased ESD protection.

The HCPL-4503, HCPL-0453, and HCNW4503 are similar to the HCPL-4502, HCPL-0452, and HCNW4502 optocouplers but have increased common mode transient immunity of 15 kV/ $\mu$ s minimum at  $V_{CM} = 1500$  V guaranteed.

## Schematic



\* NOTE: FOR HCPL-4502/-3, HCPL-0452/3, HCNW4502/3, PIN 7 IS NOT CONNECTED.

## Selection Guide

| Minimum CMR        |              | Current Transfer Ratio (%) | 8-Pin DIP (300 Mil)    |                       | Small-Outline SO-8      |                       | Widebody (400 Mil)     | Hermetic                          |
|--------------------|--------------|----------------------------|------------------------|-----------------------|-------------------------|-----------------------|------------------------|-----------------------------------|
| dV/dt (V/ $\mu$ s) | $V_{CM}$ (V) |                            | Single Channel Package | Dual Channel Package* | Single Channel Package  | Dual Channel Package* | Single Channel Package | Single and Dual Channel Packages* |
| 1,000              | 10           | 7                          | 6N135                  | HCPL-2530             | HCPL-0500               | HCPL-0530             | HCNW135                |                                   |
|                    |              | 19                         | 6N136<br>HCPL-4502†    | HCPL-2531             | HCPL-0501<br>HCPL-0452† | HCPL-0531             | HCNW136<br>HCNW4502†   |                                   |
| 15,000             | 1500         | 19                         | HCPL-4503†             | HCPL-4534             | HCPL-0453†              | HCPL-0534             | HCNW4503†              |                                   |
| 1,000              | 10           | 9                          |                        |                       |                         |                       |                        | HCPL-55XX<br>HCPL-65XX<br>4N55    |

\*Technical data for these products are on separate HP publications.

†Pin 7, transistor base, is not connected.

## Ordering Information

Specify Part Number followed by Option Number (if desired).

Example:

HCPL-4503#XXX

- 020 = UL 5000 V rms/1 Minute Option\*
- 060 = VDE 0884  $V_{IORM} = 630$  V peak Option\*\*
- 300 = Gull Wing Surface Mount Option†
- 500 = Tape and Reel Packaging Option

Option data sheets available. Contact your Hewlett-Packard sales representative or authorized distributor for information.


\*For 6N135/6 and HCPL-4502/3 only.

\*\*For HCPL-4503 only. Combination of Option 020 and Option 060 is not available.


†Gull wing surface mount option applies to through hole parts only.

## Package Outline Drawings


### 8-Pin DIP Package (6N135/6, HCPL-4502/3)




### 8-Pin DIP Package with Gull Wing Surface Mount Option 300 (6N135/6, HCPL-4502/3)




### Small Outline SO-8 Package (HCPL-0500/1, HCPL-0452/3)




### 8-Pin Widebody DIP Package (HCNW135/6, HCNW4502/3)



### 8-Pin Widebody DIP Package with Gull Wing Surface Mount Option 300 (HCNW135/6, HCNW4502/3)



### Solder Reflow Temperature Profile (HCPL-0500/1, HCPL-0452/3, and Gull Wing Surface Mount Option Parts)



Note: Use of Non-Chlorine Activated Fluxes is Recommended.

**Regulatory Information**

The devices contained in this data sheet have been approved by the following organizations:

**UL**

Recognized under UL 1577, Component Recognition Program, File E55361.

**CSA**

Approved under CSA Component Acceptance Notice #5, File CA 88324.

**VDE**

Approved according to VDE 0884/06.92 (HCNW and Option 060 devices only).

**BSI**

Certification according to BS451:1994, (BS EN60065:1994); BS EN60950:1992 (BS7002:1992) and EN41003:1993 for Class II applications (HCNW devices only).

**Insulation and Safety Related Specifications**

| Parameter                                         | Symbol | 8-Pin DIP<br>(300 Mil)<br>Value | SO-8<br>Value | Widebody<br>(400 Mil)<br>Value | Units | Conditions                                                                                                                                                 |
|---------------------------------------------------|--------|---------------------------------|---------------|--------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Minimum External Air Gap (External Clearance)     | L(101) | 7.1                             | 4.9           | 9.6                            | mm    | Measured from input terminals to output terminals, shortest distance through air.                                                                          |
| Minimum External Tracking (External Creepage)     | L(102) | 7.4                             | 4.8           | 10.0                           | mm    | Measured from input terminals to output terminals, shortest distance path along body.                                                                      |
| Minimum Internal Plastic Gap (Internal Clearance) |        | 0.08                            | 0.08          | 1.0                            | mm    | Through insulation distance, conductor to conductor, usually the direct distance between the photoemitter and photodetector inside the optocoupler cavity. |
| Minimum Internal Tracking (Internal Creepage)     |        | NA                              | NA            | 4.0                            | mm    | Measured from input terminals to output terminals, along internal cavity.                                                                                  |
| Tracking Resistance (Comparative Tracking Index)  | CTI    | 200                             | 200           | 200                            | Volts | DIN IEC 112/VDE 0303 Part 1                                                                                                                                |
| Isolation Group                                   |        | IIIa                            | IIIa          | IIIa                           |       | Material Group (DIN VDE 0110, 1/89, Table 1)                                                                                                               |

Option 300 - surface mount classification is Class A in accordance with CECC 00802.

**VDE 0884 Insulation Related Characteristics  
(HCPL-4503 OPTION 060 ONLY)**

| Description                                                                                                                                                                      | Symbol                                   | Characteristic    | Units             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------|-------------------|
| Installation classification per DIN VDE 0110/1.89, Table 1<br>for rated mains voltage $\leq 300$ V rms<br>for rated mains voltage $\leq 450$ V rms                               |                                          | I-IV              |                   |
|                                                                                                                                                                                  |                                          | I-III             |                   |
| Climatic Classification                                                                                                                                                          |                                          | 55/100/21         |                   |
| Pollution Degree (DIN VDE 0110/1.89)                                                                                                                                             |                                          | 2                 |                   |
| Maximum Working Insulation Voltage                                                                                                                                               | $V_{IORM}$                               | 630               | V <sub>peak</sub> |
| Input to Output Test Voltage, Method b*<br>$V_{IORM} \times 1.875 = V_{PR}$ , 100% Production Test with $t_m = 1$ sec,<br>Partial Discharge $< 5$ pC                             | $V_{PR}$                                 | 1181              | V <sub>peak</sub> |
| Input to Output Test Voltage, Method a*<br>$V_{IORM} \times 1.5 = V_{PR}$ , Type and sample test,<br>$t_m = 60$ sec, Partial Discharge $< 5$ pC                                  | $V_{PR}$                                 | 945               | V <sub>peak</sub> |
| Highest Allowable Overvoltage*<br>(Transient Overvoltage, $t_{ini} = 10$ sec)                                                                                                    | $V_{IOTM}$                               | 6000              | V <sub>peak</sub> |
| Safety Limiting Values<br>(Maximum values allowed in the event of a failure,<br>also see Figure 9, Thermal Derating curve.)<br>Case Temperature<br>Input Current<br>Output Power | $T_S$<br>$I_{S,INPUT}$<br>$P_{S,OUTPUT}$ | 175<br>230<br>600 | °C<br>mA<br>mW    |
| Insulation Resistance at $T_S$ , $V_{IO} = 500$ V                                                                                                                                | $R_S$                                    | $\geq 10^9$       | $\Omega$          |

**VDE 0884 Insulation Related Characteristics (HCNW135/6, HCNW4502/3 ONLY)**

| Description                                                                                                                                                                      | Symbol                                   | Characteristic    | Units             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------|-------------------|
| Installation classification per DIN VDE 0110/1.89, Table 1<br>for rated mains voltage $\leq 600$ V rms<br>for rated mains voltage $\leq 1000$ V rms                              |                                          | I-IV              |                   |
|                                                                                                                                                                                  |                                          | I-III             |                   |
| Climatic Classification                                                                                                                                                          |                                          | 55/85/21          |                   |
| Pollution Degree (DIN VDE 0110/1.89)                                                                                                                                             |                                          | 2                 |                   |
| Maximum Working Insulation Voltage                                                                                                                                               | $V_{IORM}$                               | 1414              | V <sub>peak</sub> |
| Input to Output Test Voltage, Method b*<br>$V_{IORM} \times 1.875 = V_{PR}$ , 100% Production Test with $t_m = 1$ sec,<br>Partial Discharge $< 5$ pC                             | $V_{PR}$                                 | 2652              | V <sub>peak</sub> |
| Input to Output Test Voltage, Method a*<br>$V_{IORM} \times 1.5 = V_{PR}$ , Type and sample test,<br>$t_m = 60$ sec, Partial Discharge $< 5$ pC                                  | $V_{PR}$                                 | 2121              | V <sub>peak</sub> |
| Highest Allowable Overvoltage*<br>(Transient Overvoltage, $t_{ini} = 10$ sec)                                                                                                    | $V_{IOTM}$                               | 8000              | V <sub>peak</sub> |
| Safety Limiting Values<br>(Maximum values allowed in the event of a failure,<br>also see Figure 9, Thermal Derating curve.)<br>Case Temperature<br>Input Current<br>Output Power | $T_S$<br>$I_{S,INPUT}$<br>$P_{S,OUTPUT}$ | 150<br>400<br>700 | °C<br>mA<br>mW    |
| Insulation Resistance at $T_S$ , $V_{IO} = 500$ V                                                                                                                                | $R_S$                                    | $\geq 10^9$       | $\Omega$          |

\*Refer to the front of the optocoupler section of the current catalog, under Product Safety Regulations section (VDE 0884), for a detailed description.

Note: Isolation characteristics are guaranteed only within the safety maximum ratings which must be ensured by protective circuits in application.

### Absolute Maximum Ratings

| Parameter                                                                                                                          | Symbol                | Device                 | Min.                                        | Max. | Units | Note |
|------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------|---------------------------------------------|------|-------|------|
| Storage Temperature*                                                                                                               | T <sub>S</sub>        |                        | -55                                         | 125  | °C    |      |
| Operating Temperature*                                                                                                             | T <sub>A</sub>        | 8-Pin DIP<br>SO-8      | -55                                         | 100  | °C    |      |
|                                                                                                                                    |                       | Widebody               | -55                                         | 85   |       |      |
| Average Forward Input Current*                                                                                                     | I <sub>F(AVG)</sub>   |                        |                                             | 25   | mA    | 1    |
| Peak Forward Input Current*<br>(50% duty cycle, 1 ms pulse width)<br>(50% duty cycle, 1 ms pulse width)                            | I <sub>F(PEAK)</sub>  | 8-Pin DIP<br>SO-8      |                                             | 50   | mA    | 2    |
|                                                                                                                                    |                       | Widebody               |                                             | 40   |       |      |
| Peak Transient Input Current*<br>(≤ 1 μs pulse width, 300 pps)                                                                     | I <sub>F(TRANS)</sub> | 8-Pin DIP<br>SO-8      |                                             | 1    | A     |      |
|                                                                                                                                    |                       | Widebody               |                                             | 0.1  |       |      |
| Reverse LED Input Voltage* (Pin 3-2)                                                                                               | V <sub>R</sub>        | 8-Pin DIP<br>SO-8      |                                             | 5    | V     |      |
|                                                                                                                                    |                       | Widebody               |                                             | 3    |       |      |
| Input Power Dissipation*                                                                                                           | P <sub>IN</sub>       | 8-Pin DIP<br>SO-8      |                                             | 45   | mW    | 3    |
|                                                                                                                                    |                       | Widebody               |                                             | 40   |       |      |
| Average Output Current* (Pin 6)                                                                                                    | I <sub>O(AVG)</sub>   |                        |                                             | 8    | mA    |      |
| Peak Output Current*                                                                                                               | I <sub>O(PEAK)</sub>  |                        |                                             | 16   | mA    |      |
| Emitter-Base Reverse Voltage*<br>(Pin 5-7, except 4502/3, 0452/3)                                                                  | V <sub>EBR</sub>      |                        |                                             | 5    | V     |      |
| Supply Voltage (Pin 8-5)                                                                                                           | V <sub>CC</sub>       |                        | -0.5                                        | 30   | V     |      |
| Output Voltage (Pin 6-5)                                                                                                           | V <sub>O</sub>        |                        | -0.5                                        | 20   | V     |      |
| Supply Voltage* (Pin 8-5)                                                                                                          | V <sub>CC</sub>       |                        | -0.5                                        | 15   | V     |      |
| Output Voltage* (Pin 6-5)                                                                                                          | V <sub>O</sub>        |                        | -0.5                                        | 15   | V     |      |
| Base Current* (Pin 7, except 4502/3, 0452/3)                                                                                       | I <sub>B</sub>        |                        |                                             | 5    | mA    |      |
| Output Power Dissipation*                                                                                                          | P <sub>O</sub>        |                        |                                             | 100  | mW    | 4    |
| Lead Solder Temperature*<br>(Through-Hole Parts Only)<br>1.6 mm below seating plane, 10 seconds<br>up to seating plane, 10 seconds | T <sub>LS</sub>       | 8-Pin DIP              |                                             | 260  | °C    |      |
|                                                                                                                                    |                       | Widebody               |                                             | 260  | °C    |      |
| Reflow Temperature Profile                                                                                                         | T <sub>RP</sub>       | SO-8 and<br>Option 300 | See <b>Package Outline Drawings</b> section |      |       |      |

\*Data has been registered with JEDEC for the 6N135/6N136.

## Electrical Specifications (DC)

Over recommended temperature ( $T_A = 0^\circ\text{C}$  to  $70^\circ\text{C}$ ) unless otherwise specified. See note 13.

| Parameter                                  | Symbol                          | Device                                                                    | Min. | Typ.** | Max. | Units | Test Conditions                                                       |                                               |                                                    | Fig.       | Note  |
|--------------------------------------------|---------------------------------|---------------------------------------------------------------------------|------|--------|------|-------|-----------------------------------------------------------------------|-----------------------------------------------|----------------------------------------------------|------------|-------|
| Current Transfer Ratio                     | CTR*                            | 6N135                                                                     | 7    | 18     | 50   | %     | T <sub>A</sub> = 25°C                                                 | V <sub>O</sub> = 0.4 V                        | I <sub>F</sub> = 16 mA,<br>V <sub>CC</sub> = 4.5 V | 1, 2,<br>4 | 5, 11 |
|                                            |                                 | HCPL-0500<br>HCNW135                                                      | 5    | 19     |      |       |                                                                       | V <sub>O</sub> = 0.5 V                        |                                                    |            |       |
|                                            |                                 | 6N136<br>HCPL-4502/3<br>HCPL-0501                                         | 19   | 24     | 50   |       | T <sub>A</sub> = 25°C                                                 | V <sub>O</sub> = 0.4 V                        |                                                    |            |       |
|                                            |                                 | HCPL-0452/3<br>HCNW136<br>HCNW4502/3                                      | 15   | 25     |      |       |                                                                       | V <sub>O</sub> = 0.5 V                        |                                                    |            |       |
|                                            |                                 |                                                                           |      |        |      |       |                                                                       |                                               |                                                    |            |       |
| Logic Low Output Voltage                   | V <sub>OL</sub>                 | 6N135                                                                     |      | 0.1    | 0.4  | V     | T <sub>A</sub> = 25°C                                                 | I <sub>O</sub> = 1.1 mA                       | I <sub>F</sub> = 16 mA,<br>V <sub>CC</sub> = 4.5 V |            |       |
|                                            |                                 | HCPL-0500<br>HCNW135                                                      |      | 0.1    | 0.5  |       |                                                                       | I <sub>O</sub> = 0.8 mA                       |                                                    |            |       |
|                                            |                                 | 6N136<br>HCPL-4502/3<br>HCPL-0501<br>HCPL-0452/3<br>HCNW136<br>HCNW4502/3 |      | 0.1    | 0.4  |       | T <sub>A</sub> = 25°C                                                 | I <sub>O</sub> = 3.0 mA                       |                                                    |            |       |
|                                            |                                 |                                                                           | 0.1  | 0.5    |      |       | I <sub>O</sub> = 2.4 mA                                               |                                               |                                                    |            |       |
|                                            |                                 |                                                                           |      |        |      |       |                                                                       |                                               |                                                    |            |       |
| Logic High Output Current                  | I <sub>OH</sub> *               |                                                                           |      | 0.003  | 0.5  | μA    | T <sub>A</sub> = 25°C                                                 | V <sub>O</sub> = V <sub>CC</sub> = 5.5 V      | I <sub>F</sub> = 0 mA                              | 7          |       |
|                                            |                                 |                                                                           |      | 0.01   | 1    |       | T <sub>A</sub> = 25°C                                                 | V <sub>O</sub> = V <sub>CC</sub> = 15 V       |                                                    |            |       |
|                                            |                                 |                                                                           |      |        | 50   |       |                                                                       |                                               |                                                    |            |       |
| Logic Low Supply Current                   | I <sub>CCL</sub>                |                                                                           |      | 50     | 200  | μA    | I <sub>F</sub> = 16 mA, V <sub>O</sub> = Open, V <sub>CC</sub> = 15 V |                                               |                                                    |            | 13    |
| Logic High Supply Current                  | I <sub>CCH</sub> *              |                                                                           |      | 0.02   | 1    | μA    | T <sub>A</sub> = 25°C                                                 | I <sub>F</sub> = 0 mA, V <sub>O</sub> = Open, |                                                    |            | 13    |
|                                            |                                 |                                                                           |      | 2      |      |       | V <sub>CC</sub> = 15 V                                                |                                               |                                                    |            |       |
| Input Forward Voltage                      | V <sub>F</sub> *                | 8-Pin DIP<br>SO-8                                                         |      | 1.5    | 1.7  | V     | T <sub>A</sub> = 25°C                                                 | I <sub>F</sub> = 16 mA                        |                                                    | 3          |       |
|                                            |                                 |                                                                           |      |        | 1.8  |       |                                                                       |                                               |                                                    |            |       |
|                                            |                                 | Widebody                                                                  | 1.45 | 1.68   | 1.85 |       | T <sub>A</sub> = 25°C                                                 | I <sub>F</sub> = 16 mA                        |                                                    |            |       |
|                                            |                                 |                                                                           | 1.35 |        | 1.95 |       |                                                                       |                                               |                                                    |            |       |
| Input Reverse Breakdown Voltage            | BV <sub>R</sub> *               | 8-Pin DIP<br>SO-8                                                         | 5    |        |      | V     | I <sub>R</sub> = 10 μA                                                |                                               |                                                    |            |       |
|                                            |                                 | Widebody                                                                  | 3    |        |      |       | I <sub>R</sub> = 100 μA                                               |                                               |                                                    |            |       |
| Temperature Coefficient of Forward Voltage | $\frac{\Delta V_F}{\Delta T_A}$ | 8-Pin DIP<br>SO-8                                                         |      | -1.6   |      | mV/°C | I <sub>F</sub> = 16 mA                                                |                                               |                                                    |            |       |
|                                            |                                 | Widebody                                                                  |      | -1.9   |      |       |                                                                       |                                               |                                                    |            |       |
| Input Capacitance                          | C <sub>IN</sub>                 | 8-Pin DIP<br>SO-8                                                         |      | 60     |      | pF    | f = 1 MHz, V <sub>F</sub> = 0 V                                       |                                               |                                                    |            |       |
|                                            |                                 | Widebody                                                                  |      | 90     |      |       |                                                                       |                                               |                                                    |            |       |
| Transistor DC Current Gain                 | h <sub>FE</sub>                 | 8-Pin DIP<br>SO-8                                                         |      | 150    |      |       | V <sub>O</sub> = 5 V, I <sub>O</sub> = 3 mA                           |                                               |                                                    |            |       |
|                                            |                                 |                                                                           |      | 130    |      |       | V <sub>O</sub> = 0.4 V, I <sub>B</sub> = 20 μA                        |                                               |                                                    |            |       |
|                                            |                                 | Widebody                                                                  |      | 180    |      |       | V <sub>O</sub> = 5 V, I <sub>O</sub> = 3 mA                           |                                               |                                                    |            |       |
|                                            |                                 |                                                                           |      | 160    |      |       | V <sub>O</sub> = 0.4 V, I <sub>B</sub> = 20 μA                        |                                               |                                                    |            |       |

\*For JEDEC registered parts.

\*\*All typicals at  $T_A = 25^\circ\text{C}$ .

### Switching Specifications (AC)

Over recommended temperature ( $T_A = 0^\circ\text{C}$  to  $70^\circ\text{C}$ ),  $V_{CC} = 5\text{ V}$ ,  $I_F = 16\text{ mA}$  unless otherwise specified.

| Parameter                                                 | Sym.        | Device      | Min. | Typ.** | Max. | Units                   | Test Conditions            |                                                                                                              | Fig.     | Note    |
|-----------------------------------------------------------|-------------|-------------|------|--------|------|-------------------------|----------------------------|--------------------------------------------------------------------------------------------------------------|----------|---------|
| Propagation Delay Time to Logic Low at Output             | $t_{PHL}^*$ | 6N135       |      | 0.2    | 1.5  | $\mu\text{s}$           | $T_A = 25^\circ\text{C}$   | $R_L = 4.1\text{ k}\Omega$                                                                                   | 5, 6, 11 | 8, 9    |
|                                                           |             | HCPL-0500   |      |        | 2.0  |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCNW135     |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | 6N136       |      | 0.2    | 0.8  |                         | $T_A = 25^\circ\text{C}$   | $R_L = 1.9\text{ k}\Omega$                                                                                   |          |         |
| Propagation Delay Time to Logic High at Output            | $t_{PLH}^*$ | HCPL-4502/3 |      |        |      | $\mu\text{s}$           |                            |                                                                                                              | 5, 6, 11 | 8, 9    |
|                                                           |             | HCPL-0501   |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCPL-0452/3 |      |        | 1.0  |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCNW136     |      |        |      |                         |                            |                                                                                                              |          |         |
| Common Mode Transient Immunity at Logic High Level Output | $ CM_H $    | HCNW4502/3  |      |        |      | $\text{kV}/\mu\text{s}$ |                            |                                                                                                              | 12       | 7, 8, 9 |
|                                                           |             | 6N135       |      | 1      |      |                         | $R_L = 4.1\text{ k}\Omega$ | $I_F = 0\text{ mA}$ , $T_A = 25^\circ\text{C}$ ,<br>$V_{CM} = 10\text{ V}_{p-p}$<br>$C_L = 15\text{ pF}$     |          |         |
|                                                           |             | HCPL-0500   |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCNW135     |      |        |      |                         |                            |                                                                                                              |          |         |
| Common Mode Transient Immunity at Logic Low Level Output  | $ CM_L $    | 6N136       |      | 1      |      | $\text{kV}/\mu\text{s}$ | $R_L = 1.9\text{ k}\Omega$ |                                                                                                              | 12       | 7, 8, 9 |
|                                                           |             | HCPL-4502   |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCPL-0501   |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCPL-0452   |      |        |      |                         |                            |                                                                                                              |          |         |
| Bandwidth                                                 | BW          | HCNW4502    |      |        |      | $\text{MHz}$            |                            |                                                                                                              | 8, 10    | 10      |
|                                                           |             | HCPL-4503   | 15   | 30     |      |                         | $R_L = 1.9\text{ k}\Omega$ | $I_F = 0\text{ mA}$ , $T_A = 25^\circ\text{C}$ ,<br>$V_{CM} = 1500\text{ V}_{p-p}$ ,<br>$C_L = 15\text{ pF}$ |          |         |
|                                                           |             | HCPL-0453   |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCNW4503    |      |        |      |                         |                            |                                                                                                              |          |         |
| Bandwidth                                                 | BW          | 6N135/6     |      | 9      |      | $\text{MHz}$            | See Test Circuit           |                                                                                                              | 8, 10    | 10      |
|                                                           |             | HCPL-0500/1 |      |        |      |                         |                            |                                                                                                              |          |         |
|                                                           |             | HCNW135/6   |      | 11     |      |                         |                            |                                                                                                              |          |         |

\*For JEDEC registered parts.

\*\*All typicals at  $T_A = 25^\circ\text{C}$ .

## Package Characteristics

Over recommended temperature ( $T_A = 0^\circ\text{C}$  to  $70^\circ\text{C}$ ) unless otherwise specified.

| Parameter                                  | Sym.             | Device                 | Min.                   | Typ.*     | Max. | Units         | Test Conditions                                                                     | Fig. | Note      |
|--------------------------------------------|------------------|------------------------|------------------------|-----------|------|---------------|-------------------------------------------------------------------------------------|------|-----------|
| Input-Output Momentary Withstand Voltage** | $V_{\text{ISO}}$ | 8-Pin DIP              | 2500                   |           |      | V rms         | RH < 50%,<br>t = 1 min.,<br>$T_A = 25^\circ\text{C}$                                |      | 6, 14     |
|                                            |                  | SO-8                   |                        |           |      |               |                                                                                     |      |           |
|                                            |                  | Widebody               | 5000                   |           |      |               |                                                                                     |      | 6, 15     |
|                                            |                  | 8-Pin DIP (Option 020) | 5000                   |           |      |               |                                                                                     |      | 6, 12, 15 |
|                                            | $I_{\text{I-O}}$ | 8-Pin DIP              |                        |           | 1    | $\mu\text{A}$ | 45% RH, t = 5 s,<br>$V_{\text{I-O}} = 3 \text{ kVdc}$ ,<br>$T_A = 25^\circ\text{C}$ |      | 6, 16     |
| Input-Output Resistance                    | $R_{\text{I-O}}$ | 8-Pin DIP              |                        | $10^{12}$ |      | $\Omega$      | $V_{\text{I-O}} = 500 \text{ Vdc}$                                                  |      | 6         |
|                                            |                  | SO-8                   |                        |           |      |               |                                                                                     |      |           |
|                                            |                  | Widebody               | $10^{12}$<br>$10^{11}$ | $10^{13}$ |      |               | $T_A = 25^\circ\text{C}$<br>$T_A = 100^\circ\text{C}$                               |      |           |
| Input-Output Capacitance                   | $C_{\text{I-O}}$ | 8-Pin DIP              |                        | 0.6       |      | pF            | f = 1 MHz                                                                           |      | 6         |
|                                            |                  | SO-8                   |                        |           |      |               |                                                                                     |      |           |
|                                            |                  | Widebody               |                        | 0.5       | 0.6  |               |                                                                                     |      |           |

\*All typicals at  $T_A = 25^\circ\text{C}$ .

\*\*The Input-Output Momentary Withstand Voltage is a dielectric voltage rating that should not be interpreted as an input-output continuous voltage rating. For the continuous voltage rating refer to the VDE 0884 Insulation Related Characteristics Table (if applicable), your equipment level safety specification or HP Application Note 1074 entitled "Optocoupler Input-Output Endurance Voltage," publication number 5963-2203E.

### Notes:

- Derate linearly above  $70^\circ\text{C}$  free-air temperature at a rate of  $0.8 \text{ mA}/^\circ\text{C}$  (8-Pin DIP).  
Derate linearly above  $85^\circ\text{C}$  free-air temperature at a rate of  $0.5 \text{ mA}/^\circ\text{C}$  (SO-8).
- Derate linearly above  $70^\circ\text{C}$  free-air temperature at a rate of  $1.6 \text{ mA}/^\circ\text{C}$  (8-Pin DIP).  
Derate linearly above  $85^\circ\text{C}$  free-air temperature at a rate of  $1.0 \text{ mA}/^\circ\text{C}$  (SO-8).
- Derate linearly above  $70^\circ\text{C}$  free-air temperature at a rate of  $0.9 \text{ mW}/^\circ\text{C}$  (8-Pin DIP).  
Derate linearly above  $85^\circ\text{C}$  free-air temperature at a rate of  $1.1 \text{ mW}/^\circ\text{C}$  (SO-8).
- Derate linearly above  $70^\circ\text{C}$  free-air temperature at a rate of  $2.0 \text{ mW}/^\circ\text{C}$  (8-Pin DIP).  
Derate linearly above  $85^\circ\text{C}$  free-air temperature at a rate of  $2.3 \text{ mW}/^\circ\text{C}$  (SO-8).
- CURRENT TRANSFER RATIO in percent is defined as the ratio of output collector current,  $I_O$ , to the forward LED input current,  $I_F$ , times 100.
- Device considered a two-terminal device: Pins 1, 2, 3, and 4 shorted together and Pins 5, 6, 7, and 8 shorted together.
- Common mode transient immunity in a Logic High level is the maximum tolerable (positive)  $dV_{\text{CM}}/dt$  on the leading edge of the common mode pulse signal,  $V_{\text{CM}}$ , to assure that the output will remain in a Logic High state (i.e.,  $V_O > 2.0 \text{ V}$ ). Common mode transient immunity in a Logic Low level is the maximum tolerable (negative)  $dV_{\text{CM}}/dt$  on the trailing edge of the common mode pulse signal,  $V_{\text{CM}}$ , to assure that the output will remain in a Logic Low state (i.e.,  $V_O < 0.8 \text{ V}$ ).
- The  $1.9 \text{ k}\Omega$  load represents 1 TTL unit load of  $1.6 \text{ mA}$  and the  $5.6 \text{ k}\Omega$  pull-up resistor.
- The  $4.1 \text{ k}\Omega$  load represents 1 LSTTL unit load of  $0.36 \text{ mA}$  and  $6.1 \text{ k}\Omega$  pull-up resistor.
- The frequency at which the ac output voltage is 3 dB below its mid-frequency value.
- The JEDEC registration for the 6N136 specifies a minimum CTR of 15%. HP guarantees a minimum CTR of 19%.
- See Option 020 data sheet for more information.
- Use of a  $0.1 \mu\text{F}$  bypass capacitor connected between pins 5 and 8 is recommended.
- In accordance with UL 1577, each optocoupler is proof tested by applying an insulation test voltage  $\geq 3000 \text{ V rms}$  for 1 second (leakage detection current limit,  $I_{\text{I-O}} \leq 5 \mu\text{A}$ ). This test is performed before the 100% Production test shown in the VDE 0884 Insulation Related Characteristics Table if applicable.
- In accordance with UL 1577, each optocoupler is proof tested by applying an insulation test voltage  $\geq 6000 \text{ V rms}$  for 1 second (leakage detection current limit,  $I_{\text{I-O}} \leq 5 \mu\text{A}$ ). This test is performed before the 100% Production test shown in the VDE 0884 Insulation Related Characteristics Table if applicable.
- This rating is equally validated by an equivalent ac proof test.




Figure 1. DC and Pulsed Transfer Characteristics.




Figure 2. Current Transfer Ratio vs. Input Current.




Figure 3. Input Current vs. Forward Voltage.




Figure 4. Current Transfer Ratio vs. Temperature.




Figure 5. Propagation Delay vs. Temperature.




Figure 6. Propagation Delay Time vs. Load Resistance.




Figure 7. Logic High Output Current vs. Temperature.




Figure 8. Small-Signal Current Transfer Ratio vs. Quiescent Input Current.




Figure 9. Thermal Derating Curve, Dependence of Safety Limiting Value with Case Temperature per VDE 0884.







Figure 10. Frequency Response.




Figure 11. Switching Test Circuit.




Figure 12. Test Circuit for Transient Immunity and Typical Waveforms.

[www.hp.com/go/isolator](http://www.hp.com/go/isolator)

For technical assistance or the location of your nearest Hewlett-Packard sales office, distributor or representative call:

**Americas/Canada:** 1-800-235-0312 or 408-654-8675

**Far East/Australasia:** Call your local HP sales office.

**Japan:** (81 3) 3335-8152

**Europe:** Call your local HP sales office.

Data subject to change.

Copyright © 1998 Hewlett-Packard Co.

Obsoletes 5965-3605E

Printed in U.S.A. 5968-1092E (7/98)