



Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

General Description


The MAX4464/MAX4470/MAX4471/MAX4472/MAX4474 family of micropower op amps operate from a single +1.8V to +5.5V supply and draw only 750nA of supply current. The MAX4470 family feature ground-sensing inputs and rail-to-rail output. The ultra-low supply current, low-operating voltage, and rail-to-rail output capabilities make these operational amplifiers ideal for use in single lithium ion (Li+), or two-cell NiCd or alkaline battery systems.

The rail-to-rail output stage of the MAX4464/MAX4470/MAX4471/MAX4472/MAX4474 amplifiers is capable of driving the output voltage to within 4mV of the rail with a 100k Ω load, and can sink and source 11mA with a +5V supply. These amplifiers are available in both fully compensated and decompensated versions. The single MAX4470, dual MAX4471, and the quad MAX4472 are unity-gain stable. The single MAX4464 and the dual MAX4474 are stable for closed-loop gain configurations of $\geq +5V/V$. These amplifiers are available in space-saving WLP, SC70, SOT23, μ MAX[®], and TSSOP packages.

Applications

| | |
|--------------------------|-----------------------------|
| Battery-Powered Systems | Electrometer Amplifiers |
| Portable Instrumentation | Solar-Powered Systems |
| Pagers and Cellphones | Remote Sensor Active Badges |
| Micropower Thermostats | pH Meters |

Pin Configurations



μ MAX is a registered trademark of Maxim Integrated Products, Inc.

Features

- ◆ Ultra-Low 750nA Supply Current Per Amplifier
- ◆ Ultra-Low +1.8V Supply Voltage Operation
- ◆ Ground-Sensing Input Common-Mode Range
- ◆ Outputs Swing Rail-to-Rail
- ◆ Outputs Source and Sink 11mA of Load Current
- ◆ No Phase Reversal for Overdriven Inputs
- ◆ High 120dB Open-Loop Voltage Gain
- ◆ Low 500 μ V Input Offset Voltage
- ◆ 9kHz Gain-Bandwidth Product (MAX4470/MAX4471/MAX4472)
- ◆ 40kHz Gain-Bandwidth Product (MAX4464/MAX4474)
- ◆ 250pF (min) Capacitive Load Capability
- ◆ Available in Tiny, 6-Bump WLP, 5-Pin SC70, and 8-Pin SOT23 Packages

Ordering Information

| PART | TEMP RANGE | PIN-PACKAGE | TOP MARK |
|--------------|----------------|-------------|----------|
| MAX4464EXK+T | -40°C to +85°C | 5 SC70 | +ABT |
| MAX4464EUK+T | -40°C to +85°C | 5 SOT23 | +ADPI |
| MAX4470EXK+T | -40°C to +85°C | 5 SC70 | +ABS |
| MAX4470EUK+T | -40°C to +85°C | 5 SOT23 | +ADPH |
| MAX4470EWT+ | -40°C to +85°C | 6 WLP | +BP |
| MAX4471EKA+T | -40°C to +85°C | 8 SOT23 | +AAEK |
| MAX4471ESA+ | -40°C to +85°C | 8 SO | — |
| MAX4472EUD+ | -40°C to +85°C | 14 TSSOP | — |
| MAX4472ESD+ | -40°C to +85°C | 14 SO | — |
| MAX4474EKA+T | -40°C to +85°C | 8 SOT23 | +AAEL |
| MAX4474EUA+ | -40°C to +85°C | 8 μ MAX | — |
| MAX4474ESA+ | -40°C to +85°C | 8 SO | — |

+Denotes a lead(Pb)-free/RoHS-compliant package.

Selector Guide

| PART | NO. OF AMPLIFIERS | GAIN-BANDWIDTH | MINIMUM STABLE GAIN |
|---------|-------------------|----------------|---------------------|
| MAX4464 | 1 | 40kHz | 5V/V |
| MAX4470 | 1 | 9kHz | 1V/V |
| MAX4471 | 2 | 9kHz | 1V/V |
| MAX4472 | 4 | 9kHz | 1V/V |
| MAX4474 | 2 | 40kHz | 5V/V |

MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

ABSOLUTE MAXIMUM RATINGS

| | | | |
|--|--|--|-----------------|
| V _{DD} to V _{SS} | -0.3V to +6V | 8-Pin SO (derate 5.88mW/°C above +70°C)..... | 471mW |
| IN ₊ or IN ₋ | (V _{SS} - 0.3V) to (V _{DD} + 0.3V) | 14-Pin TSSOP (derate 9.1mW/°C above +70°C) | 727mW |
| OUT ₋ Shorted to V _{SS} or V _{DD} | Continuous | 14-Pin SO (derate 8.33mW/°C above +70°C)..... | 667mW |
| Continuous Power Dissipation (T _A = +70°C) | | Operating Temperature Range | -40°C to +85°C |
| 5-Pin SC70 (derate 3.1mW/°C above +70°C)..... | .247mW | Junction Temperature | +150°C |
| 5-Pin SOT23 (derate 7.1mW/°C above +70°C)..... | .571mW | Storage Temperature Range | -65°C to +150°C |
| 6-Bump WLP (derate 10.5mW/°C above +70°C) | .840mW | Lead Temperature (soldering, 10s) | +300°C |
| 8-Pin SOT23 (derate 8.9mW/°C above +70°C)..... | .714mW | Soldering Temperature (reflow) | +260°C |
| 8-Pin μMAX (derate 4.5mW/°C above +70°C)..... | .362mW | | |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V_{DD} = +5V, V_{SS} = 0V, V_{CM} = 0V, V_{OUT} = V_{DD}/2, R_L = ∞ to V_{DD}/2, T_A = +25°C, unless otherwise noted.)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|---------------------------------|------------------|---|------------------------|-------|----------------------|---------|----|
| Supply Voltage Range | V _{DD} | Guaranteed by PSRR tests | 1.8 | | 5.5 | V | |
| Supply Current (Per Amplifier) | I _{DD} | V _{DD} = +1.8V | | 0.6 | | μA | |
| | | V _{DD} = +5.0V | | 0.75 | 1.2 | | |
| Input Offset Voltage | V _{OS} | | | ±0.5 | ±7.0 | mV | |
| Input Bias Current | I _B | | | ±200 | ±1500 | pA | |
| Input Offset Current | I _{OS} | | | ±12.5 | | pA | |
| Input Common-Mode Voltage Range | V _{CM} | Guaranteed by the CMRR test | V _{SS} | | V _{DD} -1.1 | V | |
| Common-Mode Rejection Ratio | CMRR | Specified with V _{SS} ≤ V _{CM} ≤ (V _{DD} - 1.1V) | 70 | 95 | | dB | |
| Power-Supply Rejection Ratio | PSRR | +1.8V ≤ V _{DD} ≤ +5.5V | 70 | 90 | | dB | |
| Large-Signal Voltage Gain | A _{VOL} | R _L = 1MΩ, V _{OUT} = 50mV to V _{DD} - 50mV | 90 | 120 | | dB | |
| | | R _L = 100kΩ, V _{OUT} = 200mV to V _{DD} - 200mV | 90 | 112 | | | |
| | | R _L = 10kΩ, V _{OUT} = 200mV to V _{DD} - 200mV | | 100 | | | |
| Output Voltage Swing | V _{OH} | Swing high specified as V _{DD} - V _{OH} | R _L = 1MΩ | | 1 | 4 | mV |
| | | | R _L = 100kΩ | | 4 | 10 | |
| | | | R _L = 10kΩ | | 40 | | |
| | V _{VOL} | Swing low specified as V _{VOL} - V _{SS} | R _L = 1MΩ | | 0.5 | 5 | |
| | | | R _L = 100kΩ | | 1 | 5 | |
| | | | R _L = 10kΩ | | 10 | | |
| Gain-Bandwidth Product | GBW | MAX4470/MAX4471/MAX4472 | | 9 | | kHz | |
| | | MAX4464/MAX4474 | | 40 | | | |
| Phase Margin | φ _M | MAX4470/MAX4471/MAX4472 | | 90 | | degrees | |
| | | MAX4464/MAX4474 | | 80 | | | |

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

ELECTRICAL CHARACTERISTICS (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $V_{OUT} = V_{DD}/2$, $R_L = \infty$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)

| PARAMETER | SYMBOL | CONDITIONS | | MIN | TYP | MAX | UNITS |
|------------------------------|------------|--------------------------------|-------------------------|-----|-----|-----|-----------------|
| Slew Rate | SR | $V_{OUT} = 4V$ step | MAX4470/MAX4471/MAX4472 | | 2 | | V/ms |
| | | | MAX4464/MAX4474 | | 20 | | |
| Input Voltage Noise | e_n | f = 1kHz | | | 150 | | nV/ \sqrt{Hz} |
| | | f = 10kHz | | | 120 | | |
| Output Short-Circuit Current | | Shorted to V_{SS} (sourcing) | | | 11 | | mA |
| | | Shorted to V_{DD} (sinking) | | | 36 | | |
| Power-On Time | t_{ON} | | | | 3 | | ms |
| Power-Off Time | t_{OFF} | | | | 2 | | μs |
| Capacitive Load | C_{LOAD} | No sustained oscillations | | 250 | | | pF |

ELECTRICAL CHARACTERISTICS

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $V_{OUT} = V_{DD}/2$, $R_L = \infty$ to $V_{DD}/2$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.) (Note 1)

| PARAMETER | SYMBOL | CONDITIONS | | MIN | TYP | MAX | UNITS |
|--|------------|--|--------------------|----------|-----|----------------|------------------|
| Supply Voltage Range | V_{DD} | Guaranteed by PSRR tests | | 1.8 | | 5.5 | V |
| Supply Current (Per Amplifier) | I_{DD} | $V_{DD} = +5.0V$ | | | | 1.5 | μA |
| Input Offset Voltage | V_{OS} | | | | | ± 15 | mV |
| Input Offset Voltage Temperature Coefficient | TCV_{OS} | | | | 8 | | $\mu V/^\circ C$ |
| Input Bias Current | I_B | | | | | 4.25 | nA |
| Input Common-Mode Voltage Range | V_{CM} | Guaranteed by the CMRR test | | V_{SS} | | $V_{DD} - 1.1$ | V |
| Common-Mode Rejection Ratio | CMRR | $V_{SS} \leq V_{CM} \leq (V_{DD} - 1.1V)$ | | 56 | | | dB |
| Power-Supply Rejection Ratio | PSRR | $+1.8V \leq V_{DD} \leq +5.5V$, $0^\circ C \leq T_A \leq +85^\circ C$ | | 65 | | | dB |
| | | $+2V \leq V_{DD} \leq +5.5V$, $-40^\circ C \leq T_A \leq +85^\circ C$ | | 65 | | | |
| Large-Signal Voltage Gain | A_{VOL} | $V_{OUT} = 50mV$ to $V_{DD} - 50mV$, $R_L = 1M\Omega$ | | 75 | | | dB |
| | | $V_{OUT} = 200mV$ to $V_{DD} - 200mV$, $R_L = 100k\Omega$ | | 75 | | | |
| Output Voltage Swing | V_{OH} | Swing high specified as $V_{DD} - V_{OH}$ | $R_L = 1M\Omega$ | | | 5 | mV |
| | | | $R_L = 100k\Omega$ | | | 15 | |
| | V_{OL} | Swing low specified as $V_{OL} - V_{SS}$ | $R_L = 1M\Omega$ | | | 5 | |
| | | | $R_L = 100k\Omega$ | | | 5 | |


Note 1: All devices are production tested at $T_A = +25^\circ C$. All temperature limits are guaranteed by design.

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps


Typical Operating Characteristics

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


SUPPLY CURRENT PER AMPLIFIER vs. SUPPLY VOLTAGE




SUPPLY CURRENT PER AMPLIFIER vs. TEMPERATURE




OFFSET VOLTAGE vs. TEMPERATURE




OFFSET VOLTAGE vs. COMMON-MODE VOLTAGE




INPUT BIAS CURRENT vs. TEMPERATURE




INPUT BIAS CURRENT vs. COMMON-MODE VOLTAGE




POWER-SUPPLY REJECTION RATIO vs. FREQUENCY



OUTPUT VOLTAGE SWING LOW vs. TEMPERATURE



OUTPUT VOLTAGE SWING HIGH vs. TEMPERATURE




Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps


Typical Operating Characteristics (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


COMMON-MODE REJECTION RATIO vs. TEMPERATURE




MINIMUM SUPPLY VOLTAGE vs. TEMPERATURE




AVOL vs. OUTPUT VOLTAGE SWING




MAX4470/MAX4471/MAX4472 GAIN AND PHASE vs. FREQUENCY




MAX4470/MAX4471/MAX4472 GAIN AND PHASE vs. FREQUENCY




CROSSTALK vs. FREQUENCY




MAX4470/MAX4471/MAX4472 TOTAL HARMONIC DISTORTION PLUS NOISE vs. FREQUENCY



VOLTAGE NOISE DENSITY vs. FREQUENCY



MAX4470/MAX4471/MAX4472 STABILITY vs. CAPACITIVE AND RESISTIVE LOADS












MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Typical Operating Characteristics (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)




Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps


Typical Operating Characteristics (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


MAX4470/MAX4471/MAX4472
SMALL-SIGNAL GAIN vs. FREQUENCY




MAX4470/MAX4471/MAX4472
LARGE-SIGNAL GAIN vs. FREQUENCY




MAX4470/MAX4471/MAX4472
LARGE-SIGNAL GAIN vs. FREQUENCY




MAX4470/MAX4471/MAX4472
LARGE-SIGNAL GAIN vs. FREQUENCY




MAX4464/MAX4474
GAIN AND PHASE vs. FREQUENCY




MAX4464/MAX4474
GAIN AND PHASE vs. FREQUENCY




MAX4464/MAX4474
TOTAL HARMONIC DISTORTION PLUS NOISE vs. FREQUENCY



MAX4464/MAX4474
STABILITY vs. CAPACITIVE AND RESISTIVE LOADS



MAX4464/MAX4474
SMALL-SIGNAL STEP RESPONSE




MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps


Typical Operating Characteristics (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


MAX4464/MAX4474
SMALL-SIGNAL STEP RESPONSE




MAX4464/MAX4474
SMALL-SIGNAL STEP RESPONSE




MAX4464/MAX4474
LARGE-SIGNAL STEP RESPONSE




MAX4464/MAX4474
LARGE-SIGNAL STEP RESPONSE




MAX4464/MAX4474
PERCENT OVERSHOOT vs. CAPACITIVE LOAD



MAX4464/MAX4474
SMALL-SIGNAL NORMALIZED GAIN vs. FREQUENCY







MAX4464/MAX4474
SMALL-SIGNAL NORMALIZED GAIN vs. FREQUENCY



Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Typical Operating Characteristics (continued)

($V_{DD} = +5V$, $V_{SS} = 0V$, $V_{CM} = 0V$, $R_L = 100k\Omega$ to $V_{DD}/2$, $T_A = +25^\circ C$, unless otherwise noted.)



Pin Description

| PIN | | | | NAME | FUNCTION |
|---------------------|------------------|---------------------|---------|----------|--|
| MAX4464/ MAX4470 | MAX4470 (WLP) | MAX4471/ MAX4474 | MAX4472 | | |
| 1 | A1 | — | — | IN+ | Noninverting Amplifier Input |
| — | — | 3 | 3 | INA+ | Noninverting Amplifier Input (Channel A) |
| 2 | A2 | 4 | 11 | V_{SS} | Negative Power-Supply Voltage |
| 3 | B1 | — | — | IN- | Inverting Amplifier Input |
| 4 | C1 | — | — | OUT | Amplifier Output |
| — | — | 2 | 2 | INA- | Inverting Amplifier Input (Channel A) |

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Pin Description (continued)

| PIN | | | | NAME | FUNCTION |
|---------------------|------------------|---------------------|---------|-----------------|--|
| MAX4464/ MAX4470 | MAX4470 (WLP) | MAX4471/ MAX4474 | MAX4472 | | |
| — | — | 1 | 1 | OUTA | Amplifier Output (Channel A) |
| — | — | 6 | 6 | INB- | Inverting Amplifier Input (Channel B) |
| — | — | 5 | 5 | INB+ | Noninverting Amplifier Input (Channel B) |
| — | — | 7 | 7 | OUTB | Amplifier Output (Channel B) |
| — | — | — | 9 | INC- | Inverting Amplifier Input (Channel C) |
| — | — | — | 10 | INC+ | Noninverting Amplifier Input (Channel C) |
| — | — | — | 8 | OUTC | Amplifier Output (Channel C) |
| — | — | — | 13 | IND- | Inverting Amplifier Input (Channel D) |
| — | — | — | 12 | IND+ | Noninverting Amplifier Input (Channel D) |
| — | — | — | 14 | OUTD | Amplifier Output (Channel D) |
| 5 | B2 | 8 | 4 | V _{DD} | Positive Power-Supply Voltage |
| — | C2 | — | — | N.C. | No Connection. Not internally connected. |

Applications Information

Ground Sensing

The common-mode input range of the MAX4470 family extends down to ground, and offers excellent common-mode rejection. These devices are guaranteed not to undergo phase reversal when the input is overdriven.

Power Supplies and Layout

The MAX4470 family operates from a single +1.8V to +5.5V power supply. Bypass power supplies with a 0.1µF ceramic capacitor placed close to the V_{DD} pin.

Ground layout improves performance by decreasing the amount of stray capacitance and noise at the op amp's inputs and outputs. To decrease stray capacitance, minimize PC board lengths and resistor leads, and place external components close to the op amps' pins.

Bandwidth

The MAX4470/MAX4471/MAX4472 are internally compensated for unity-gain stability and have a typical gain-bandwidth of 9kHz. The MAX4464/MAX4474 have a 40kHz typical gain-bandwidth and are stable for a gain of +5V/V or greater.

Stability

The MAX4464/MAX4470/MAX4471/MAX4472/MAX4474 maintain stability in their minimum gain configuration while driving capacitive loads. Although this product family is primarily designed for low-frequency applications, good layout is extremely important because low-power requirements demand high-impedance circuits. The layout should also minimize stray capacitance at the amplifier inputs. However some stray capacitance may be unavoidable, and it may be necessary to add a 2pF to 10pF capacitor across the feedback resistor as shown in Figure 1. Select the smallest capacitor value that ensures stability.





Figure 1. Compensation for Feedback Node Capacitance

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Pin Configurations (continued)



Chip Information

PROCESS: BiCMOS

MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE | PACKAGE CODE | DOCUMENT NO. | LAND PATTERN NO. |
|--------------|--------------|-------------------------|--|
| 5 SC70 | X5+1 | 21-0076 | 90-0188 |
| 5 SOT23 | U5+1 | 21-0057 | 90-0174 |
| 6 WLP | W61B1+1 | 21-0217 | Refer to Application Note 1891 |
| 8 μMAX | U8+1 | 21-0036 | 90-0092 |
| 8 SOT23 | K8+5 | 21-0078 | 90-0176 |
| 8 SOIC | S8+2 | 21-0041 | 90-0096 |
| 14 SOIC | S14+1 | 21-0041 | 90-0096 |
| 14 TSSOP | U14+1 | 21-0066 | 90-0117 |

TOP VIEW

END VIEW

SIDE VIEW

| COMMON DIMENSIONS | | | |
|-------------------|------------|------|------|
| SYMBOL | MIN | NOM | MAX |
| A | 0.80 | 0.95 | 1.10 |
| A1 | 0.00 | 0.07 | 0.10 |
| A2 | 0.80 | 0.90 | 1.00 |
| b | 0.15 | 0.22 | 0.30 |
| c | 0.10 | 0.14 | 0.18 |
| D | 1.80 | 2.00 | 2.20 |
| e | 0.65 BSC. | | |
| E | 1.15 | 1.25 | 1.35 |
| HE | 1.80 | 2.20 | 2.40 |
| L | 0.26 | 0.34 | 0.46 |
| L1 | 0.425 TYP. | | |
| Q1 | 0.10 | 0.25 | 0.40 |

NOTES:

- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- DIMENSIONS ARE INCLUSIVE OF PLATING.
- DIMENSIONS ARE EXCLUSIVE OF MOLD FLASH & METAL BURR.
- COPLANARITY: 4 MILS. MAX.
- FOOT LENGTH MEASURED AT INTERCEPT POINT BETWEEN DATUM "A" AND LEAD SURFACE.
- MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- LEAD CENTERLINES TO BE AT TRUE POSITION AS DEFINED BY BASIC DIMENSION "e", ±0.05.
- COMPLY TO JEITA SC-88A EXCEPT FOR DIMENSION "L". ALL DIMENSIONS COMPLY TO JEDEC MO-203.
- MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND LEAD FREE (+) PACKAGE CODES.
- PKG CODE: X5-1

-DRAWING NOT TO SCALE-

TITLE:
PACKAGE OUTLINE,
5L SC70


| | | | |
|----------|---------------------------------|-----------|-----|
| APPROVAL | DOCUMENT CONTROL NO. 21-0076 | REV. F | 1/1 |
|----------|---------------------------------|-----------|-----|

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.


MAX4464/MAX4470/MAX4471/MAX4472/MAX4474



Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.




Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.


MAX4464/MAX4470/MAX4471/MAX4472/MAX4474



Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.




Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)


For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

MAX4464/MAX4470/MAX4471/MAX4472/MAX4474



| SYMBOL | INCHES | | MM | |
|--------|--------|------|------|------|
| | MIN. | MAX. | MIN. | MAX. |
| A | .053 | .069 | 1.35 | 1.75 |
| A1 | .004 | .010 | 0.10 | 0.25 |
| b | .014 | .019 | 0.35 | 0.49 |
| c | .007 | .010 | 0.19 | 0.25 |
| E | .150 | .157 | 3.80 | 4.00 |
| e | .050 | BSC | 1.27 | BSC |
| H | .228 | .244 | 5.80 | 6.20 |
| L | .016 | .050 | 0.40 | 1.27 |
| α | 0° | 8° | 0° | 8° |

| VARIATION A | | | | |
|-------------|---|------|------|------|
| SYMBOL | INCHES | | MM | |
| | MIN. | MAX. | MIN. | MAX. |
| D | .189 | .197 | 4.80 | 5.00 |
| N | 8 | | | |
| MS012 | AA | | | |
| PKG. CODE | S8-2, S8-4, S8-5, S8-6F, S8-7F, S8-8F, S8-10F, S8-11F, S8-16F | | | |



| VARIATION B | | | | |
|-------------|--|------|------|------|
| SYMBOL | INCHES | | MM | |
| | MIN. | MAX. | MIN. | MAX. |
| D | .337 | .344 | 8.55 | 8.75 |
| N | 14 | | | |
| MS012 | AB | | | |
| PKG. CODE | S14-1, S14-4, S14-5, S14-6, S14M-4, S14M-5, S14M-6, S14M-7 | | | |

| VARIATION C | | | | |
|-------------|--|------|------|-------|
| SYMBOL | INCHES | | MM | |
| | MIN. | MAX. | MIN. | MAX. |
| D | .386 | .394 | 9.80 | 10.00 |
| N | 16 | | | |
| MS012 | AC | | | |
| PKG. CODE | S16-1, S16-3, S16-5, S16-6, S16-8, S16-7F, S16-9F, S16-10F, S16M-3, S16M-6 | | | |

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
 - MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
 - DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.15 MM (.006") PER SIDE.
 - LEADS TO BE COPLANAR WITHIN 0.10mm (.004").
 - MEETS JEDEC MS012
 - ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PbfREE (+) PKG. CODES.

-DRAWING NOT TO SCALE-

| | | | |
|---|---------------------------------|-----------|-----|
| MAXIM | | | |
| TITLE: PACKAGE OUTLINE, 8L, 14L, 16L SDIC .150 INCH | | | |
| APPROVAL | DOCUMENT CONTROL NO. 21-0041 | REV. C | 1/1 |

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Package Information (continued)

For the latest package outline information and land patterns (footprints), go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| SYMBOL | COMMON DIMENSIONS | | | |
|----------------|-------------------|------|----------------|------|
| | MILLIMETERS | | INCHES | |
| | MIN. | MAX. | MIN. | MAX. |
| A | — | 1.10 | — | .043 |
| A ₁ | 0.05 | 0.15 | .002 | .006 |
| A ₂ | 0.85 | 0.95 | .033 | .037 |
| b | 0.19 | 0.30 | .007 | .012 |
| b ₁ | 0.19 | 0.25 | .007 | .010 |
| c | 0.09 | 0.20 | .004 | .008 |
| c ₁ | 0.09 | 0.14 | .004 | .006 |
| D | SEE VARIATIONS | | SEE VARIATIONS | |
| E | 4.30 | 4.50 | .169 | .177 |
| e | 0.65 BSC | | .026 BSC | |
| H | 6.25 | 6.55 | .246 | .258 |
| L | 0.50 | 0.70 | .020 | .028 |
| N | SEE VARIATIONS | | SEE VARIATIONS | |
| α | 0° | | 8° | |
| kbb | 0.10 MAX | | | |

| JEDEC MO-153 | N | SYMBOL | PKG. CODES | VARIATIONS | | | |
|--------------|----|--------|--|-------------|------|--------|------|
| | | | | MILLIMETERS | | INCHES | |
| | | | | MIN. | MAX. | MIN. | MAX. |
| AB-1 | 14 | D | U14-1, U14-2, U14-3 | 4.90 | 5.10 | .193 | .201 |
| AB | 16 | D | U16-1, U16-2, U16-1F, U16M-1 | 4.90 | 5.10 | .193 | .201 |
| AC | 20 | D | U20-1, U20-2, U20-3, U20-5, U20-1F, U20M-2 | 6.40 | 6.60 | .252 | .260 |
| AD | 24 | D | U24-1, U24-2 | 7.70 | 7.90 | .303 | .311 |
| AE | 28 | D | U28-1, U28-2, U28-3 | 9.60 | 9.80 | .378 | .386 |

NOTES

1. DIMENSIONS D AND E DO NOT INCLUDE FLASH
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED 0.15mm PER SIDE
3. CONTROLLING DIMENSION: MILLIMETER
4. MEETS JEDEC OUTLINE MO-153. SEE JEDEC VARIATIONS TABLE
5. "N" REFERS TO NUMBER OF LEADS
6. LEAD COPLANARITY 0.10 MM MAX.
7. NUMBER OF LEADS SHOWN ARE FOR REFERENCE ONLY
8. MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY
9. BENT LEAD 0.10 MM MAX.
10. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
11. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PBFREE (+) PKG. CODES.

-DRAWING NOT TO SCALE-

MAXIM

TITLE:
PACKAGE OUTLINE,
TSSOP 4.40mm BODY

| | | |
|----------|---------------------------------|------------|
| APPROVAL | DOCUMENT CONTROL NO. 21-0066 | REV. L 1/1 |
|----------|---------------------------------|------------|

Single/Dual/Quad, +1.8V/750nA, SC70, Rail-to-Rail Op Amps

Revision History

| REVISION NUMBER | REVISION DATE | DESCRIPTION | PAGES CHANGED |
|-----------------|---------------|-------------------------------------|-----------------|
| 3 | 6/10 | Added WLP package | 1, 2, 9, 10, 11 |
| 4 | 7/11 | Updated power-on time specification | 3 |

MAX4464/MAX4470/MAX4471/MAX4472/MAX4474

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 _____ 19