




MPSA92M

PNP EPITAXIAL SILICON TRANSISTOR

HIGH VOLTAGE TRANSISTOR

■ FEATURES

- * Collector-Emitter voltage: $V_{CE0}=-300V$
- * Collector Dissipation: $P_{C(MAX)}=625mW$
- * Low collector-Emitter saturation voltage



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
MPSA92ML-T92-B	MPSA92MG-T92-B	TO-92	E	B	C	Tape Box
MPSA92ML-T92-K	MPSA92MG-T92-K	TO-92	E	B	C	Bulk
MPSA92ML-T92-R	MPSA92MG-T92-R	TO-92	E	B	C	Tape Reel

Note: Pin Assignment: E:EMITTER B:BASE C:COLLECTOR

<p>MPSA92ML-T92-B</p> <p>(1)Packing Type (2)Package Type (3)Lead Free</p>	<p>(1) B: Tape Box, K: Bulk, R: Tape Reel (2) T92: TO-92 (3) Halogen Free, L: Lead Free</p>
---	---

■ ABSOLUTE MAXIMUM RATINGS ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V_{CBO}	-300	V
Collector-Emitter Voltage	V_{CEO}	-300	V
Emitter-Base Voltage	V_{EBO}	-6	V
Collector Dissipation ($T_A=25^\circ\text{C}$)	P_C	625	mW
Collector Current	I_C	-800	mA
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~+150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C=-100\mu\text{A}$, $I_E=0$	-300			V
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C=-1\text{mA}$, $I_B=0$	-300			V
Collector-Emitter Breakdown Voltage	BV_{CES}	$I_C=-100\mu\text{A}$, $V_{BE}=0$	-300			V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E=-100\mu\text{A}$, $I_C=0$	-5			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=-300\text{V}$, $I_E=0$			-100	nA
Collector Cut-Off Current	I_{CES}	$V_{CB}=-300\text{V}$, $V_{BE}=0$			-1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=-4\text{V}$, $I_C=0$			100	nA
DC Current Gain (Note 1)	h_{FE}	$V_{CE}=-10\text{V}$, $I_C=-1\text{mA}$	60			
		$V_{CE}=-10\text{V}$, $I_C=-10\text{mA}$	80		300	
		$V_{CE}=-10\text{V}$, $I_C=-100\text{mA}$	80			
		$V_{CE}=-10\text{V}$, $I_C=-200\text{mA}$	40			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=-30\text{mA}$, $I_B=-1\text{mA}$			-0.20	V
		$I_C=-100\text{mA}$, $I_B=-10\text{mA}$			-0.7	
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=-10\text{mA}$, $I_B=-1\text{mA}$			-0.75	V
Output Capacitance	C_{OB}	$V_{CB}=-20\text{V}$, $I_E=0$, $f=1\text{MHz}$			8	pF

Note: 1. Pulse test: $PW<300\mu\text{s}$, Duty Cycle $<2\%$

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.