C 091 B

Male cable connector, bayonet locking outside

cable outlet 6 mm

cable outlet 8 mm

cable outlet 6.5 mm

Description	Drawing	No. of cont.	Part Number solder termination: Contact plating silver	Part Number solder termination: Contact plating gold [2]	Part Number Crimp termination[1]
Male cable connector, max. cable outlet 6 mm, termination: solder or crimp, contact plating: silver or gold.		3 DIN	T 3279 501	T 3279 518 [4]	T 3279 551
		4 IEC	T 3329 501	T 3329 518 [4]	T 3329 551
		5	T 3379 501	T 3379 518 [4]	T 3379 551
		5 S DIN	T 3399 501	T 3399 518 [4]	T 3399 551 [4]
		6 DIN	T 3429 501	T 3429 518 [4]	T 3429 551
		7	T 3439 501	T 3439 518 [4]	T 3439 551
		7 DIN	T 3449 501 [4]	T 3449 518 [4]	T 3449 551 [4]
		8 DIN	T 3529 501 [4]	T 3529 518 [4]	T 3529 551 [4]
		12	T 3629 501 [4]	T 3629 518 [4]	–
		14	T 3649 501 [4]	T 3649 518 [4]	–
Male cable connector, max. cable outlet 8 mm, termination: solder or crimp, contact plating: silver or gold.		3 DIN	T 3279 502	T 3279 528 [4]	T 3279 552
		4 IEC	T 3329 502	T 3329 528 [4]	T 3329 552
		5	T 3379 502	T 3379 528 [4]	T 3379 552
		5 S DIN	T 3399 502	T 3399 528 [4]	T 3399 552 [4]
		6 DIN	T 3429 502	T 3429 528 [4]	T 3429 552
		7	T 3439 502	T 3439 528 [4]	T 3439 552
		7 DIN	T 3449 502 [4]	T 3449 528 [4]	T 3449 552 [4]
		8 DIN	T 3529 502	T 3529 528 [4]	T 3529 552 [4]
		12	T 3629 502 [4]	T 3629 528 [4]	–
		14	T 3649 502	T 3649 528 [4]	–
Male cable connector, max. cable outlet 6.5 mm, termination: solder or crimp, contact plating: silver or gold.		3 DIN	T 3279 504 [4]	T 3279 548 [4]	T 3279 554 [4]
		4 IEC	T 3329 504 [4]	T 3329 548 [4]	T 3329 554 [4]
		5	T 3379 504 [4]	T 3379 548 [4]	T 3379 554 [4]
		5 S DIN	T 3399 504 [4]	T 3399 548 [4]	T 3399 554 [4]
		6 DIN	T 3429 504 [4]	T 3429 548 [4]	T 3429 554 [4]
		7	T 3439 504 [4]	T 3439 548 [4]	T 3439 554 [4]
		7 DIN	T 3449 504 [4]	T 3449 548 [4]	T 3449 554 [4]
		8 DIN	T 3529 504 [4]	T 3529 548 [4]	T 3529 554 [4]
		12	T 3629 504 [4]	T 3629 548 [4]	–
		14	T 3649 504 [4]	T 3649 548 [4]	–

[1] Please order crimp contacts separately, see page 46 [2] see remark page 23 [4] Available upon request. Min. order qty.100 pcs/type.

C 091 B

Male cable connector, bayonet locking outside, assembling instructions

Male cable connector, max. cable outlet 6 mm

Male cable connector, max. cable outlet 6.5 mm or 8 mm