
## Leadless Type PTC Thermistor

## Leadless Type PTC Thermistor



## ◆For Heater (Leadless Type)

	Part No.	Initial Characteristic						Dimensions	
		Resistance R25		Operating Voltage	Maximum Current	Temperature	D	T	
		(Ω)	(%)	(V)	(A)	(°C)	(mm)	(mm)	
	PFE-040M090-100□□	4.0	±20	DC15	4.7	By individual Spec.	<b>ф</b> 10.0	2.5	
	PFE-100M090-100□□	10.0	±20	DC15	1.5	By individual Spec.	<b>ф</b> 10.0	2.5	
	PFE-200M100-100□□	10.0	±20	DC15	1.1	By individual Spec.	<b>ф</b> 10.0	2.5	

## ◆For Heater (Custom Type)

	Part No.	Initial Characteristic						Dimensions	
		Resistance R25		Operating Voltage	Maximum Current	Temperature	D	Т	
		(Ω)	(%)	(V)	(A)	(°C)	(mm)	(mm)	
	Ring Heater			AC100	0.5	By individual Spec.	By individual Spec. By individual Spec. By individual Spec.		
	Ring Heater			AC220	1.5	By individual Spec.			
	Ring Heater (Transformer less)			AC100/AC220	1.5	By individual Spec.			

XValues mentioned in the catalog are for reference. For details please give your inquiry to our sales office.