



Scale 5:1

### Features

- ▶ Ultra low profile - 0.6mm high
- ▶ Miniature ceramic package
- ▶ High shock & vibration resistance
- ▶ Industrial and Extended temperature ranges
- ▶ Low power consumption

### Specifications

Parameters	Product	Option	
	CX8V	Code	
Terminations:	Gold plated pads	■	T1A
Frequency range:	32.768kHz	■	
Calibration tolerance:	±20ppm ±100ppm	■ □	specify
Operating temperature range:	-40 to +85°C -55 to +125°C	■ □	M
Storage temperature range:	-55 to +125°C	■	
Circuit condition:	7pF 9pF 12.5pF Other values	□ □ ■ □	specify specify specify
Static capacitance (C <sub>0</sub> ):	1.1pF typ	■	
Motional capacitance (C <sub>p</sub> ):	3.5fF typ	■	
Equivalent series resistance:	90kΩ max	■	
Ageing:	±3ppm max first year	■	
Drive level:	0.5μW max	■	
Turnover temperature (T <sub>0</sub> ):	+25°C ±5°C	■	
Frequency / temp coefficient:	-0.035ppm/°C <sup>2</sup> typ	■	
Shock resistance:	±5ppm, 5,000g, 0.3ms, ½ sine	■	
Vibration resistance:	±5ppm, 20g, 10.0 ~ 2,000Hz	■	
Soldering condition:	Reflow, 260°C, 20 sec max	■	

■ Standard. □ Optional - Please specify required code(s) when ordering

### Ordering Information

Product name + termination + option codes (if any) + frequency + calibration tolerance  
 eg: **CX8V-T1A 32.768kHz ±20ppm** -40+85°C  
**CX8V-T1A/M 32.768kHz ±100ppm** -55+125°C  
 Option code X (eg CX8V-T1A/X) denotes a custom spec.

- ◆ Available on T&R 1k, 3k or 14k pcs/reel.
- ◆ Refer to our website for T&R and soldering details.
- ◆ Ask about higher shock & vibration specifications.