

DO NOT SCALE FROM THIS PRINT

UNLESS OTHERWISE NOTED
 DIMENSIONS ARE IN INCHES
 TOLERANCES ARE:
 ONE PLACE DECIMALS: ± .1
 TWO PLACE DECIMALS: ± .01
 THREE PLACE DECIMALS: ± .005
 FOUR PLACE DECIMALS: ± .0020
 ANGLES
 ± 5°






FIG. 1




SECT "A-A"




SECT "B-B"

- RSM-1XX-XX-XXX-D-XX
- BODY LENGTH SPECIFICATION**
 -02 THRU -40 POSITIONS
- LEAD STYLE**
 -02: C-64-02-X
- PLATING SPECIFICATIONS**
 -S: SELECTIVE GOLD (USE C-64-02-S-X)
 -P: FLASHED GOLD PALLADIUM NICKEL (USE C-64-02-P-X)
 -F: FLASH GOLD (USE C-64-02-F-X)
 -L: LIGHT SELECTIVE GOLD (USE C-64-02-L-X)
 -T: TIN (USE C-64-02-T-X)
 -STL: SELECTIVE TIN LEAD (USE C-64-02-STL-X)
 -H: HEAVY GOLD (USE C-64-02-H-X)
 -TM: MATTE TIN (USE C-64-02-T-X)
 -SM: HEAVY SELECTIVE GOLD, MATTE TIN TAIL (USE C-64-02-S-X)
 -LM: LIGHT SELECTIVE GOLD, MATTE TIN TAIL (USE C-64-02-L-X)
 -FM: FLASH SELECTIVE GOLD, MATTE TIN TAIL (USE C-64-02-F-X)
- OPTIONS**
 -LC: LOCKING CLIP (USE LC-05-TM)(SEE FIG 2, SHT 2)(SEE NOTE 4)
 -P: PICK AND PLACE PAD (AVAILABLE ON POS. 5 THRU 40 ONLY) (USE MPP-02)(SEE FIG 3, SHT 2)
 -K: POLYIMIDE FILM PAD (AVAILABLE ON POS. 5 THRU 40 ONLY) (.005 [.13] THICKNESS WITH SILICONE ADHESIVE)(SEE FIG 4, SHT 2) (USE K-500-300)
 -TR: TAPE & REEL
- BODY SPECIFICATION**
 -D: DOUBLE ROW (USE RSM-XX-D)



1. WILL LOSE A POSITION FOR EVERY CUT MADE ON A SOCKET STRIP; CUT FLASH TO BE .010 [.25] MAX WITH NO FLASH ALLOWED IN HOLES OR EXTENDING BELOW LEADS.
2. Ⓢ REPRESENTS A CRITICAL DIMENSION.
3. MINIMUM RETENTION FORCE: 1.0 LB.
4. DUE TO THE HIGH AMOUNT OF INSERTION FORCE NEEDED, THE -LC OPTION IS NOT COMPATIBLE WITH AUTO PLACEMENT. SAMTEC RECOMMENDS MANUAL PLACEMENT FOR ALL ASSEMBLIES WITH THE -LC OPTION.



PACKAGING

- NOTES:
1. 1st POSITION TO BE LOADED IN TUBE IN THE DIRECTION OF THE ARROW.
 2. LAYER PACKAGE POSITIONS 2-4, TUBE PACKAGE POSITIONS 5-36
 3. ENDWALLS TO BE .020±.003"

TABLE 1		
OPTION	TUBE	PLUG
-K, -LC, -K-LC	PT-1-24-04-64	TP-03
NONE, -P, -P-LC	PT-1-24-05-38	TP-09



EXISPROD\ASSEMBLY\050
 RSM-DASM

samtec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
 PHONE (812) 944-6733 P.O. BOX 1147
 CODE 55322

MADE BY: GREG REIDINGER 11-24-92

RSM-1XX-XX-XXX-D-XX
 SHEET 1 OF 2



PROPRIETARY NOTE
 THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC INC.