



**CABLE**

Flat cable LIYZ 2x0.14mm<sup>2</sup>  
 colour white, ends tinned  
*Flachkabel LIYZ 2x0.14 mm<sup>2</sup>*  
*Farbe weiss, Enden verzinkt*

tolerances acc. to DIN ISO 2768-m  
 Abmessungen/dimensions in mm

**MARKING**

MEDER-Label, Type  
 Production code EN60062/  
 Factory code  
 circuit diagram  
**MEDER-Logo, Typ**  
**Produktionscode**  
**EN60062/Fertigungsstätte**  
**Schaltbild**

**CIRCUIT DIAGRAM**



Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C	57		75	AT
Test equipment		KMS-14+PK002+SA002			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	V
operating ampere	DC or Peak AC			1,25	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive Sensor deactivated			280	mOhm
Housing material		PBT glass fibre reinforced			
Case color		white			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		70	°C
Operating temperature	cable moved	-5		70	°C
Storage temperature		-30		70	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		flat cable			
Cable material		PVC			
Cross section		0,14 sq-mm			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a series resistor is recommended.			
mounting advice 1		Decreased switching distances by mounting on iron			
mounting advice 2		Magnetically conductive screws must not be used			
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm

Modifications in the sense of technical progress are reserved