

**PARALLEL SPLICES**



| Wire Range<br>AWG    | Order No.  | Krimptite®  |             |                  | Insulkrimp®<br>(PVC Insulation) |                  | Versakrimp™ |              |              | Nylakrimp®<br>(Nylon Insulation) |             |                  |
|----------------------|------------|-------------|-------------|------------------|---------------------------------|------------------|-------------|--------------|--------------|----------------------------------|-------------|------------------|
|                      |            | ID Minimum  | OD Maximum  | Max. Length<br>L | Order No.                       | Max. Length<br>L | Order No.   | ID Minimum   | OD Maximum   | Max. Length<br>L                 | Order No.   | Max. Length<br>L |
| 18-22<br>(0.80-0.35) |            |             |             |                  | 19206-0002*                     | 18.10 (.712)     | 19207-0001* | 1.50 (.060)  | 3.30 (.130)  | 8.40 (.332)                      | 19207-0002* | 17.00 (.670)     |
| 14-16<br>(2.00-1.30) | 19208-0001 | 2.10 (.084) | 4.20 (.165) | 8.60 (.340)      | 19206-0004                      | 18.70 (.735)     | 19205-0001* | 2.30 (.091)  | 4.10 (.160)  | 8.40 (.330)                      | 19207-0004* | 16.40 (.645)     |
|                      |            |             |             |                  | 19206-0005*                     | 18.70 (.735)     |             |              |              |                                  |             |                  |
| 10-12<br>(5.00-3.30) | 19208-0002 | 3.30 (.128) | 5.80 (.230) | 8.40 (.330)      | 19206-0008                      | 12.10 (.831)     | 19205-0003* | 3.30 (.130)  | 5.70 (.225)  | 8.40 (.330)                      | 19207-0005* | 17.50 (.688)     |
|                      |            |             |             |                  | 19206-0010*                     | 12.10 (.831)     |             |              |              |                                  |             |                  |
| 8 (8.50)             |            |             |             |                  |                                 |                  | 19205-0004  | 4.20 (.165)  | 7.50 (.295)  | 10.40 (.408)                     |             |                  |
| 6                    |            |             |             |                  |                                 |                  | 19205-0006  | 5.80 (.230)  | 9.50 (.374)  | 12.10 (.477)                     |             |                  |
| 4                    |            |             |             |                  |                                 |                  | 19205-0007  | 7.00 (.277)  | 11.60 (.457) | 13.90 (.547)                     |             |                  |
| 2                    |            |             |             |                  |                                 |                  | 19205-0008  | 9.00 (.357)  | 13.70 (.538) | 17.20 (.680)                     |             |                  |
| 1/0                  |            |             |             |                  |                                 |                  | 19205-0009  | 11.20 (.439) | 15.70 (.620) | 20.10 (.790)                     |             |                  |
| 2/0                  |            |             |             |                  |                                 |                  | 19205-0010  | 12.60 (.496) | 17.70 (.697) | 19.80 (.779)                     |             |                  |
| 3/0                  |            |             |             |                  |                                 |                  | 19215-0049  | 13.80 (.545) | 19.30 (.760) | 20.30 (.800)                     |             |                  |
| 4/0                  |            |             |             |                  |                                 |                  | 19215-0050  | 15.80 (.621) | 21.80 (.860) | 20.80 (.820)                     |             |                  |

| Product Specifications |                  |                                  |             |
|------------------------|------------------|----------------------------------|-------------|
| Wire Range AWG         | Insulation Color | Maximum Wire Insulation Diameter |             |
|                        |                  | Insulkrimp                       | Nylakrimp®  |
| 18-22 (0.80-0.35)      | Red              | 3.70 (.145)                      | 3.00 (.120) |
| 14-16 (2.00-1.30)      | Blue             | 4.40 (.175)                      | 3.80 (.150) |
| 10-12 (5.00-3.30)      | Yellow           | 6.60 (.260)                      | 5.30 (.210) |

**3 AND 4 WAY CONNECTORS**

| Wire Range<br>AWG | Material: Copper               |                                |                                |                                |
|-------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
|                   | Insulkrimp<br>(PVC Insulation) | Insulkrimp<br>(PVC Insulation) | Avikrimp<br>(Nylon Insulation) | Avikrimp<br>(Nylon Insulation) |
|                   | Order No.                      |                                |                                |                                |
| 18-22 (0.80-0.35) | 19204-0004                     | 19204-0003                     | 19204-0009                     | 19204-0008                     |
| 14-16 (2.00-1.30) | 19204-0014                     | 19204-0013                     | 19204-0018                     | 19204-0017                     |
| 10-12 (5.00-3.30) | 19204-0026                     | 19204-0025                     | 19204-0030                     | 19204-0029                     |

\* Part has seamless barrel instead of butted seam