



Dual Varicap Diode



18108

MECHANICAL DATA

Case: SOT-23

Weight: approx. 8.1 mg

Packaging codes/options:

08/3 k per 7" reel (8 mm tape), 15 k/box

FEATURES

- Silicon epitaxial planar diode
- Common cathode
- High capacitance ratio
- AEC-Q101 qualified
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- Find out more about Vishay's Automotive Grade Product requirements at: www.vishay.com/applications

AUTOMOTIVE GRADE


RoHS
 COMPLIANT
GREEN
 [5-2008]**

APPLICATIONS

- Tuning of separate resonant circuits
- Push-pull circuits in FM range
- Especially for car radios

PARTS TABLE

PART	TYPE DIFFERENTIATION	ORDERING CODE	TYPE MARKING	REMARKS
BB824-2-V-GH	$V_{RRM} = 20\text{ V}$, $C_{D2} = 42.5\text{ pF}$ to 43.8 pF	BB824-2-V-GH-08	TH	Tape and reel
BB824-3-V-GH	$V_{RRM} = 20\text{ V}$, $C_{D2} = 43.7\text{ pF}$ to 45 pF	BB824-3-V-GH-08	TH	Tape and reel

ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Repetitive peak reverse voltage		V_{RRM}	20	V
Reverse voltage		V_R	18	V
Forward current		I_F	50	mA

THERMAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Junction temperature		T_j	125	$^{\circ}\text{C}$
Storage temperature range		T_{stg}	- 55 to + 150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




PARAMETER	TEST CONDITIONS	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Reverse current	$V_R = 16\text{ V}$		I_R			20	nA
	$V_R = 16\text{ V}$, $T_j = 60\text{ }^{\circ}\text{C}$		I_R			200	nA
Diode capacitance (1)	$V_R = 2\text{ V}$	BB824-2-V-GH	C_{D2}	42.5		43.8	pF
		BB824-3-V-GH	C_{D2}	43.7		45	pF
	$V_R = 8\text{ V}$	BB824-2-V-GH	C_{D8}	17.5		19.2	pF
		BB824-3-V-GH	C_{D8}	18.0		19.8	pF
Capacitance ratio	$V_R = 2\text{ V}$, 8 V , $f = 1\text{ MHz}$		C_{D2}/C_{D8}	2.25		2.45	
Series resistance	$V_R = 2\text{ V}$, $f = 100\text{ MHz}$		R_s			0.5	Ω

Note


 (1) In the reverse voltage range of $V_R = (2\text{ V to } 8\text{ V})$ for diodes 4 taped in sequence the max. deviation is 3 %

 ** Please see document "Vishay Material Category Policy": www.vishay.com/doc?99902

PACKAGE DIMENSIONS in millimeters (inches): SOT-23



Foot print recommendation:



Document no.: 6.541-5014.01-4

Rev. 8 - Date: 23.Sept.2009

17418



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.