


SBC



PMB-601LF

**New Intel® Q965 ATX
Motherboard Supports
Intel® Core 2 Duo
Processors for Best in
Class Performance**

Features :

- Support Intel® Core 2 Duo, Intel Celeron® D, Intel® Pentium® D and Intel® Pentium® 4 processors
- Equipped with Intel Q965 Chipset with FSB 1066MHz
- Memory Supports DDR 800 SDRAM up to 8GB
- Expansion Slots for PCI-E x16, PCI & ISA
- Applications such as gaming, medical, multimedia systems, digital image storage servers and more



PROTECH SYSTEMS

It's the right choice

No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C.

Tel: +886-2-8751-1111

Fax: +886-2-8751-1199

Email: sales@protech.com.tw

<http://www.protech.com.tw>




ISO CERTIFIED

9001 14001

PMB-601LF

New Intel® Q965 ATX Motherboard Supports Intel® Core 2 Duo Processors for Best in Class Performance



Specifications	
System	
CPU Type	Intel® Celeron® D, Pentium® 4, Pentium® D, Core 2 Duo processor
Chipset	Intel® Q965 + ICH8DO + FWB (FSB : 533/667/800/1066MHz)
DRAM	4 x 240-pin DDR2 DIMM, support DDR2 800 SDRAM up to 8GB
BIOS	PhoenixAward PnP BIOS, with VGA BIOS
Watchdog	1~255 secs Watchdog timer selectable w / Reset
Power Supply	Support ATX Power
Power Requirement	+5V, +12V, +3.3V, -12V, +5VSB
Power Consumption	+5V : 3.2A / +12V : 10.45A / +3.3V : 5.32A / -12V : 0.06A / +5VSB : 0.52A (Pentium® 4 3.4GHz)
Dimension	305mm x 244mm (12" x 9.61")
I/O Ports	
SATA Port	Six ports S-ATA connector
FDD Interface	One FDD connector with 34-pin Boxheader on board
Function BUS	1 x PCI-E 16X ; 1 x PCI-E 4X ; 4 x PCI ; 1 x ISA
Serial Port	COM1/3/4 for RS-232, COM2 for R232/422/485 (COM 3/4 can output +5V or +12V, and use Jumper settings)
Parallel Port	1 x parallel (SPP / EPPP / ECP)
IrDA	1 (SIR)
Keyboard	Mini DIN connector
Mouse	Mini DIN connector

LAN	Lan 1 : Intel® 82573V (10/100/1000Mbps) Lan 2 : Intel® 82573V (10/100/1000Mbps) Supports Wake-on-LAN
Audio	HD Codec, Realtek ALC262, with Mic / Line-out / Line-in
USB	10 ports, support USB 2.0
Display	
Graphic	Built-in Intel® Q965, share system memory, Support CRT, PCI-E 16X (SDVO)
Environment	
Operation Temp.	0°~60°C (32°~140°F)
Storage Temp.	-40°~85°C (-40°~185°F)
Humidity	Operation humidity 20~90%, Storage humidity 20~95%

Ordering Information	
PMB-601LF	ATX S775 Core 2 Duo w VGA / Audio / 2LAN / 4COM / ISA (10/100/1000Mbps)
Certificate: CE, FCC CLASS A	

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in JAN. 2007.