




LSR102 - LSR106

1.0 AMP. Surface Mount Schottky Barrier Rectifiers

MELF

Features

- ✧ Surge overload ratings to 25 amperes peak
- ✧ Ideal for printed circuit board
- ✧ Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- ✧ Terminal : Pure tin plated, lead free
- ✧ Mounting position: Any
- ✧ Weight: 0.12 grams



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	LSR102	LSR103	LSR104	LSR105	LSR106	Units
Maximum Recurrent Peak Reverse Voltage	VRRM	20	30	40	50	60	V
Maximum RMS Voltage	VRMS	14	21	28	35	42	V
Maximum DC Blocking Voltage	VDC	20	30	40	50	60	V
Maximum Average Forward Rectified Current See Fig. 1	IF(AV)	1.0					A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	IFSM	25					A
Maximum Instantaneous Forward Voltage @1.0A	VF	0.55			0.70		V
Maximum DC Reverse Current at @ TA=25 °C Rated DC Blocking Voltage(Note 1)@ TA=125 °C	IR	1.0 10					mA mA
Typical Junction Capacitance (Note 2)	Cj	110			80		pF
Typical Thermal Resistance	REJA	15					°C/W
Operating Temperature Range	TJ	- 65 to + 125			- 65 to + 150		°C
Storage Temperature Range	TSTG	- 65 to + 150					°C

Note: 1. Pulse Test with PW=300 usec, 1% Duty Cycle

2. Measured at 1 MHz and Applied Reverse Voltage of 4.0 V D.C

RATINGS AND CHARACTERISTIC CURVES (LSR102 THRU LSR106)

