

# Single N-channel MOSFET

## ELM17402FA-S

### ■ General description

ELM17402FA-S uses advanced trench technology to provide excellent  $R_{ds(on)}$ , low gate charge and operation with gate voltages as low as 1.8V.

### ■ Features

- $V_{ds}=20V$
- $I_d=1.6A$  ( $V_{gs}=4.5V$ )
- $R_{ds(on)} < 90m\Omega$  ( $V_{gs}=4.5V$ )
- $R_{ds(on)} < 105m\Omega$  ( $V_{gs}=2.5V$ )
- $R_{ds(on)} < 130m\Omega$  ( $V_{gs}=1.8V$ )

### ■ Maximum absolute ratings


Parameter	Symbol	Limit	Unit	Note	
Drain-source voltage	$V_{ds}$	20	V		
Gate-source voltage	$V_{gs}$	$\pm 8$	V		
Continuous drain current	$I_d$	$T_a=25^\circ C$	1.6	A	1
		$T_a=70^\circ C$	1.2		
Pulsed drain current	$I_{dm}$	10	A	2	
Power dissipation	$P_d$	$T_a=25^\circ C$	0.35	W	1
		$T_a=70^\circ C$	0.22		
Junction and storage temperature range	$T_j, T_{stg}$	-55 to 150	$^\circ C$		

### ■ Thermal characteristics

Parameter		Symbol	Typ.	Max.	Unit	Note
Maximum junction-to-ambient	$t \leq 10s$	$R_{\theta ja}$	300	360	$^\circ C/W$	1
Maximum junction-to-ambient	Steady-state		340	425	$^\circ C/W$	
Maximum junction-to-lead	Steady-state	$R_{\theta jl}$	280	320	$^\circ C/W$	3


### ■ Pin configuration

SC-70(TOP VIEW)



Pin No.	Pin name
1	GATE
2	SOURCE
3	DRAIN

### ■ Circuit



# Single N-channel MOSFET

## ELM17402FA-S

### ■Electrical characteristics

Ta=25°C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
<b>STATIC PARAMETERS</b>						
Drain-source breakdown voltage	BVdss	Id=250μA, Vgs=0V	20			V
Zero gate voltage drain current	Idss	Vds=16V, Vgs=0V			1	μA
		Tj=55°C			5	
Gate-body leakage current	Igss	Vds=0V, Vgs=±8V			100	nA
Gate threshold voltage	Vgs(th)	Vds=Vgs, Id=250μA	0.40	0.55	0.80	V
On state drain current	Id(on)	Vgs=4.5V, Vds=5V	10			A
Static drain-source on-resistance	Rds(on)	Vgs=4.5V, Id=1.6A		75	90	mΩ
		Tj=125°C		106	130	
		Vgs=2.5V, Id=1.5A		86	105	
		Vgs=1.8V, Id=1.4A		103	130	
Forward transconductance	Gfs	Vds=5V, Id=1.6A		5.5		S
Diode forward voltage	Vsd	Is=1A, Vgs=0V		0.69	1.00	V
Max. body-diode continuous current	Is				0.5	A
<b>DYNAMIC PARAMETERS</b>						
Input capacitance	Ciss			458		pF
Output capacitance	Coss	Vgs=0V, Vds=10V, f=1MHz		76		pF
Reverse transfer capacitance	Crss			54		pF
Gate resistance	Rg	Vgs=0V, Vds=0V, f=1MHz		3		Ω
<b>SWITCHING PARAMETERS</b>						
Total gate charge	Qg			6.05		nC
Gate-source charge	Qgs	Vgs=4.5V, Vds=10V, Id=1.6A		0.70		nC
Gate-drain charge	Qgd			1.45		nC
Turn-on delay time	td(on)			7.3		ns
Turn-on rise time	tr	Vgs=5V, Vds=10V		5.6		ns
Turn-off delay time	td(off)	RI=6.25Ω, Rgen=6Ω		40.0		ns
Turn-off fall time	tf			11.0		ns
Body diode reverse recovery time	trr	If=1.6A, dl/dt=100A/μs		12.20		ns
Body diode reverse recovery charge	Qrr	If=1.6A, dl/dt=100A/μs		3.23		nC

#### NOTE :

1. The value of Rθja is measured with the device mounted on 1in<sup>2</sup> FR-4 board of 2oz. Copper, in still air environment with Ta=25°C. The value in any given applications depends on the user's specific board design, The current rating is based on the t ≤ 10s thermal resistance rating.
2. Repetitive rating, pulse width limited by junction temperature.
3. The Rθja is the sum of the thermal impedance from junction to lead Rθjl and lead to ambient.
4. The static characteristics in Figures 1 to 6 are obtained using 80μs pulses, duty cycle 0.5%max.
5. These tests are performed with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with Ta=25°C. The SOA curve provides a single pulse rating.

# Single N-channel MOSFET

ELM17402FA-S

## ■ Typical electrical and thermal characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

# Single N-channel MOSFET

## ELM17402FA-S




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance