

SMD Power Inductor CDRH60D28/A



Under Development

RoHS



Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 6.6 × 6.5 × 3.0 mm Max.
- Product weight: 0.35g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Qualification to AEC-Q200.

Environmental Data

- Operating temperature range: -40°C ~ +125°C (excluding coil's self temperature rise).
- Storage temperature range: -40°C ~ +85°C
- Solder reflow temperature: 260 °C peak.


Packaging

- Carrier tape and reel packaging.


Applications

- Automotive and other high temperature, high reliability application.

Dimension - [mm]



Land pattern and Schematics - [mm]



SMD Power Inductor CDRH60D28/A



Under Development

Electrical Characteristics

Part No.	Stamp	Inductance (μ H) ※1 [within]	D.C.R. (m Ω) Max. (Typ.) (at 20°C)	Rated Current (A) ※2 (at 125°C)
CDRH60D28ANP-4R7N	A	4.7 μ H \pm 30%	64(51)	1.70
CDRH60D28/ANP-6R8N	B	6.8 μ H \pm 30%	75(60)	1.37
CDRH60D28/ANP-100N	C	10 μ H \pm 30%	103(82)	1.24
CDRH60D28/ANP-150N	D	15 μ H \pm 30%	155(124)	0.95
CDRH60D28/ANP-220N	E	22 μ H \pm 30%	234(187)	0.80
CDRH60D28/ANP-330N	F	33 μ H \pm 30%	384(307)	0.65
CDRH60D28/ANP-470N	G	47 μ H \pm 30%	598(478)	0.54
CDRH60D28/ANP-680N	H	68 μ H \pm 30%	760(608)	0.45
CDRH60D28/ANP-101N	J	100 μ H \pm 30%	1250(997)	0.38
CDRH60D28/ANP-151N	K	150 μ H \pm 30%	1790(1430)	0.32
CDRH60D28/ANP-221N	L	220 μ H \pm 30%	2250(1800)	0.26
CDRH60D28/ANP-331N	M	330 μ H \pm 30%	3680(2940)	0.21
CDRH60D28/ANP-471N	N	470 μ H \pm 30%	5450(4360)	0.18

※1. Inductance measuring condition: at 100 kHz.

※2. Rated current: The DC current at which the inductance decreases to 65% of its nominal value or when $\Delta t=30^{\circ}\text{C}$, whichever is lower.













SMD Power Inductor CDRH60D28/A




Under Development

Saturation Current & Temperature Rise Graph

— L (20°C) — L (125°C) — ΔT



SMD Power Inductor CDRH60D28/A




sumida



Under Development

Saturation Current & Temperature Rise Graph

— L (20°C) — L (125°C) — ΔT



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong
Tel.+852-2880-6688
FAX.+852-2565-9600
sales@hk.sumida.com

Tokyo
Tel.+81-3-5202-7112
FAX.+81-3-5202-7105
sales@jp.sumida.com

Chicago
Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai
Tel.+86-021-5836-3299
FAX.+86-021-5836-3266
shanghai.sales@cn.sumida.com

Seoul
Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Oberzell
Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@sumida-eu.com

Shenzhen
Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore
Tel.+65-6296-3388
FAX.+65-6296-3390
sales@sg.sumida.com

Neumarkt
Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei
Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose
Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com