

## APPLICATIONS

- ✓ Cellular Phones
- ✓ Personal Digital Assistant (PDA)
- ✓ Ground Positioning System (GPS)
- ✓ SMART & PCMCIA Cards

## IEC COMPATIBILITY (EN61000-4)


- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns
- ✓ 61000-4-5 (Surge): 24A, 8/20 $\mu$ s - Level 2(Line-Gnd) & Level 3(Line-Line)

## FEATURES


- ✓ ESD Protection > 25 kilovolts
- ✓ 300 Watts Peak Pulse Power per Line (tp = 8/20 $\mu$ s)
- ✓ Protects up to Four (4) Unidirectional Lines
- ✓ RoHS Compliant

## MECHANICAL CHARACTERISTICS

- ✓ Quad Flip Chip Package
- ✓ Weight 0.73 milligrams (Approximate)
- ✓ Available in Lead-Free Plating
- ✓ Solder Reflow Temperature:  
Lead-Free - Sn/Ag/Cu, 96/3.5/0.5: 260-270°C
- ✓ Consult Factory for Leaded Device Availability
- ✓ Flammability Rating UL 94V-0
- ✓ 8mm Plastic & Paper Tape and Reel Per EIA Standard 481
- ✓ Top Contacts: Solder Bump 0.004" in Height (Nominal)



## PIN CONFIGURATION



# SFC05-4

## DEVICE CHARACTERISTICS


### MAXIMUM RATINGS @ 25°C Unless Otherwise Specified

PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (tp = 8/20μs) - See Figure 1	P <sub>PP</sub>	300	Watts
Operating Temperature	T <sub>A</sub>	-55 to 150	°C
Storage Temperature	T <sub>STG</sub>	-55 to 150	°C


### ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER	RATED STAND-OFF VOLTAGE	MINIMUM BREAKDOWN VOLTAGE	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM LEAKAGE CURRENT	TYPICAL CAPACITANCE
	V <sub>WM</sub> VOLTS	@ 1mA V <sub>(BR)</sub> VOLTS	@ I <sub>p</sub> = 5A V <sub>C</sub> VOLTS	@ 8/20μs V <sub>C</sub> @ I <sub>PP</sub>	@ V <sub>WM</sub> I <sub>D</sub> μA	@ 0V, 1 MHz C <sub>j</sub> pF
SFC05-4	5.0	6.0	9.5	11.0V @ 24A	10	150

**FIGURE 1**  
PEAK PULSE POWER VS PULSE TIME




**FIGURE 2**  
PULSE WAVE FORM




## GRAPHS


**FIGURE 3  
POWER DERATING CURVE**



**FIGURE 4  
OVERSHOOT & CLAMPING VOLTAGE**



**FIGURE 5  
TYPICAL CLAMPING VOLTAGE VS PEAK PULSE CURRENT**





## APPLICATION INFORMATION

PRINTED CIRCUIT BOARD RECOMMENDATIONS	
PARAMETER	VALUE
Pad Size on PCB	0.275mm
Pad Shape	Round
Pad Definition	Non-Solder Mask Defined Pads
Solder Mask Opening	0.325mm Round
Solder Stencil Thickness	0.150mm
Solder Stencil Aperture Opening (laser cut, 5% tapered walls)	0.330mm Round
Solder Paste Type	No Clean
Pad Protective Finish	OSP(Entek Cu Plus 106A)
Tolerance - Edge To Corner Ball	±50µm
Solder Ball Side Coplanarity	±20µm
Maximum Dwell Time Above Liquidous (183°C)	60 Seconds
Soldering Maximum Temperature	270°C


REQUIREMENTS
<p>Temperature:</p> <p><math>T_p</math> for Lead-Free (SnAgCu): 260-270°C</p> <p><math>T_p</math> for Tin-Lead: 240-245°C</p> <p>Preheat time and temperature depends on solder paste and flux activation temperature, component size, weight, surface area &amp; plating.</p>

### RECOMMENDED NON-SOLDER MASK DEFINED PAD ILLUSTRATION




# SFC05-4

## QUAD PACKAGE OUTLINE & DIMENSIONS



# SFC05-4

## QUAD PACKAGE OUTLINE & DIMENSIONS



**COPYRIGHT © ProTek Devices 2007**

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

**ProTek Devices**  
 2929 South Fair Lane, Tempe, AZ 85282  
 Tel: 602-431-8101 Fax: 602-431-2288  
 E-Mail: [sales@protekdevices.com](mailto:sales@protekdevices.com)  
 Web Site: [www.protekdevices.com](http://www.protekdevices.com)