

3-Terminal 1A Positive Voltage Regulator


LM7824

GENERAL DESCRIPTION

The LM7824 series of three terminal positive regulators are available in the TO-220 package and with several fixed output voltages, making them useful in a wide range of applications. Each type employs internal current limiting, thermal shut down and safe operating area protection, making it essentially indestructible. If adequate heat sinking is provided, they can deliver over 1A output current. Although designed primarily as fixed voltage regulators, these devices can be used with external components to obtain adjustable voltages and currents.

ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C)

Parameter	Symbol	Typ	Unit
Input Voltage	V _I	40	V
Output Voltage	V _O	24.0	V
Peak Current	I _{PK}	2.2	A
Operating Temperature Range	T _{OPR}	0~125	°C
Storage Temperature Range	T _{STG}	-65~150	°C



TO-220

ELECTRICAL CHARACTERISTICS (Ta = 25 °C)

(Refer to test circuit, I_O = 500mA, V_i = 33V, C_i = 0.33μF, C_o = 0.1μF unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	V _I = 14.5V to 30V	23.28	24.0	24.72	V
Line Regulation (Note1)	Regline	V _I = 27V to 38V		17	480	mV
		V _I = 30V to 36V		6.0	240	
Load Regulation (Note1)	Regload	I _O = 5.0mA to 1.5A		15	480	mV
		I _O = 250mA to 750mA		5	240	
Quiescent Current	I _Q	T _J = +25 °C		5.2	8	mA
Ripple Rejection	RR	f = 120Hz, V _O = 28V to 38V	50	67		dB
Dropout Voltage	V _{Drop}	I _O = 1A, T _J = +25 °C		2		V
Output Resistance	r _O	f = 1KHz		0.028		Ω
Short Circuit Current	I _{SC}	V _I = 35V, T _A = +25 °C		230		mA
Peak Current	I _{PK}	T _J = +25 °C		2.2		A