


Note:
A. PISA Slot can use for PISA CPU card, another two can use for standard ISA card in the meantime.

Alarm (CN1)



Pin1 : +5VSB
 Pin2 : +12V
 Pin3 : +3.3V
 Pin4 : -12V
 Pin5 : +5V
 Pin6 : SMB_CLK
 Pin7 : SMB_DATA
 Pin8 : GND

SMBus (CN2)



Pin1 : SMB_CLK
 Pin2 : SMB_DATA

PS-ON (CN4)




Pin1 : PS-ON
 Pin2 : GND
 Pin3 : +5VSB

Fan (CN3,5)



Pin1 : GND
 Pin2 : +12V
 Pin3 : NC

Keyboard (KB1,2,3)



Pin1 : KB_CLOCK
 Pin2 : KB_DATA
 Pin3 : NC
 Pin4 : GND
 Pin5 : VCC

PCI Routing Table

Slot	INSEL	Interrupt pin route				gnd
PCI1	AD19	INTA	INTB	INTC	INTD	P_#REC0A
PCI2	AD20	INTD	INTA	INTB	INTC	P_#REC0B
PCI3	AD21	INTC	INTD	INTA	INTB	P_#REC0C
PCI4	AD22/AD26	INTB	INTC	INTD	INTA	P_#REC0D