

MAZ4xxx Series (MA4xxx Series)

Silicon planar type

For stabilization of power supply

■ Features


- High reliability, achieved by the DHD structure
- Allowing to insert to a 5 mm pitch hole
- Finely divided zener-voltage rank
- Sharp rising performance
- Wide voltage range: Zener voltage $V_Z = 2.0\text{ V}$ to 39.0 V

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Forward current (Average)	$I_{F(AV)}$	250	mA
Repetitive peak forward current	I_{FRM}	250	mA
Power dissipation *1	P_D	370	mW
Non-repetitive reverse surge power dissipation *2	P_{ZSM}	30	W
Junction temperature	T_j	200	$^\circ\text{C}$
Storage temperature	T_{stg}	-65 to +200	$^\circ\text{C}$

Note) *1: $P_D = 370\text{ mW}$ achieved with a printed circuit board

*2: $t = 100\ \mu\text{s}$, $T_j = 150^\circ\text{C}$



■ Common Electrical Characteristics $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$ *1

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F = 10\text{ mA}$		0.8	0.9	V
Zener voltage *2	V_Z	I_Z Specified value				V
Zener rise operating resistance	R_{ZK}	I_Z Specified value				Ω
Zener operating resistance	R_Z	I_Z Specified value				Ω
Reverse current	I_{R1}	V_R Specified value	Refer to the list of the electrical characteristics within part numbers			μA
	I_{R2}	V_R Specified value				
Temperature coefficient of zener voltage *3	S_Z	I_Z Specified value				mV/ $^\circ\text{C}$
Terminal capacitance	C_t	$V_R = 0\text{ V}$, $f = 1\text{ MHz}$ Specified value				pF

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 measuring methods for diodes.

2. Absolute frequency of input and output is 50 MHz.

3. *1: The temperature must be controlled 25°C for V_Z measurement.

V_Z value measured at other temperature must be adjusted to $V_Z(25^\circ\text{C})$

*2: V_Z guaranteed 20 ms after current flow.

*3: $T_j = 25^\circ\text{C}$ to 150°C

Note) The part number in the parenthesis shows conventional part number.










■ Electrical Characteristics within Part Numbers $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$





• $V_Z = 2.0\text{ V to } 6.8\text{ V}$ ($I_Z = 5\text{ mA}$)

Part number	Zener voltage		Reverse current				Zener operating resistance	Zener rise operating resistance	Temperature coefficient of zener voltage			Terminal capacitance		Marking symbol (Color indication) Main body: Light green			
	V_Z (V) $I_Z = 5\text{ mA}$		I_{R1} (μA)		I_{R2} (μA)		R_Z (Ω)	R_{ZK} (Ω)	S_Z (mV/ $^\circ\text{C}$)			C_t (pF)		1st.	2nd.	3rd.	
	Min	Max	V_R (V)	Max	V_R (V)	Max	I_Z (mA)	Max	Min	Typ	Max	Typ	Max				
MAZ4020	1.88	2.24	0.5	120	—	—	100	1	2000	-3.5	-1.5	0	375	450	Red	Black	Black
MAZ4022	2.08	2.45	0.7	120	—	—	100	1	2000	-3.5	-1.5	0	375	450	Red	Red	Red
MAZ4024	2.28	2.70	1.0	120	—	—	100	1	2000	-3.5	-1.6	0	375	450	Red	Yellow	Yellow
MAZ4027	2.50	2.90	1.0	100	—	—	100	1	1000	-3.5	-2.0	0	350	450	Red	Purple	Purple
MAZ4030	2.80	3.20	1.0	50	—	—	100	1	1000	-3.5	-2.1	0	350	450	Orange	Black	Black
MAZ4033	3.10	3.50	1.0	20	—	—	100	1	1000	-3.5	-2.4	0	325	450	Orange	Orange	Orange
MAZ4036	3.40	3.80	1.0	10	—	—	100	1	1000	-3.5	-2.4	0	300	450	Orange	Blue	Blue
MAZ4039	3.70	4.10	1.0	10	—	—	100	1	1000	-3.5	-2.5	0	300	450	Orange	White	White
MAZ4043	4.00	4.60	1.0	10	—	—	100	1	1000	-3.5	-2.5	0	275	450	Yellow	Orange	Orange
MAZ4047	4.40	5.00	1.0	3	—	—	80	1	900	-3.5	-1.4	0.2	130	180	Yellow	Purple	Purple
MAZ4051	4.80	5.40	2.0	2	—	—	60	1	800	-2.7	-0.8	1.2	110	160	Green	Brown	Brown
MAZ4056	5.30	6.00	2.0	1	—	—	40	1	500	-2.0	1.2	2.5	95	140	Green	Blue	Blue
MAZ4062	5.80	6.60	4.0	3	5.3	60	20	0.5	300	0.4	2.3	3.7	90	130	Blue	Red	Red
MAZ4068	6.40	7.20	4.0	2	5.9	60	15	0.5	140	1.2	3.0	4.5	85	110	Blue	Gray	Gray
MAZ4075	7.00	7.90	5	1	6.5	60	15	0.5	120	2.5	4.0	5.3	80	100	Purple	Green	Green
MAZ4082	7.70	8.70	5	0.5	7.2	60	15	0.5	120	3.2	4.6	6.2	75	95	Gray	Red	Red
MAZ4091	8.50	9.60	6	0.2	8.0	60	15	0.5	130	3.8	5.5	7.0	70	90	White	Brown	Brown
MAZ4100	9.40	10.60	7	0.2	8.9	60	20	0.5	130	4.5	6.4	8.0	70	90	Brown	Black	—
MAZ4110	10.40	11.60	7	0.1	9.9	60	20	0.5	170	5.4	7.4	9.0	65	85	Brown	Brown	—
MAZ4120	11.40	12.70	8	0.1	10.9	60	25	0.5	170	6.0	8.4	10.0	65	85	Brown	Red	—
MAZ4130	12.40	14.10	9	0.1	11.9	60	30	0.5	170	7.0	9.4	11.0	60	80	Brown	Orange	—
MAZ4140	13.65	14.35	9	0.1	13.1	60	30	0.5	170	7.0	10.0	13.0	60	80	Brown	Yellow	—
MAZ4150	13.90	15.60	10	0.05	13.4	60	30	0.5	170	9.2	11.4	13.0	55	75	Brown	Green	—
MAZ4160	15.30	17.10	11	0.05	14.8	60	40	0.5	170	10.4	12.4	14.0	52	75	Brown	Blue	—
MAZ4180	16.90	19.10	13	0.05	16.4	60	45	0.5	170	12.4	14.4	16.0	47	70	Brown	Gray	—
MAZ4200	18.80	21.20	14	0.05	18.3	60	55	0.5	180	14.4	16.4	18.0	36	60	Red	Black	—
MAZ4220	20.80	23.30	15	0.05	20.3	60	55	0.5	180	16.4	18.4	20.0	34	60	Red	Red	—
MAZ4240	22.80	25.60	17	0.05	22.3	60	70	0.5	180	18.4	20.4	22.0	33	55	Red	Yellow	—

• $V_Z = 27.0\text{ V to } 39.0\text{ V}$ ($I_Z = 2\text{ mA}$)

Part number	Zener voltage		Reverse current				Zener operating resistance	Zener rise operating resistance	Temperature coefficient of zener voltage			Terminal capacitance		Marking symbol (Color indication) Main body: Light green			
	V_Z (V) $I_Z = 2\text{ mA}$		I_{R1} (μA)		I_{R2} (μA)		R_Z (Ω)	R_{ZK} (Ω)	S_Z (mV/ $^\circ\text{C}$)			C_t (pF)		1st.	2nd.	3rd.	
	Min	Max	V_R (V)	Max	V_R (V)	Max	I_Z (mA)	Max	Min	Typ	Max	Typ	Max				
MAZ4270	25.10	28.90	19	0.05	24.8	60	80	0.5	200	21.4	23.4	25.3	30	50	Red	Purple	—
MAZ4300	28.00	32.00	21	0.05	27.8	60	80	0.5	200	24.4	26.6	29.4	27	50	Orange	Black	—
MAZ4330	31.00	35.00	23	0.05	30.7	60	80	0.5	200	27.4	29.7	33.4	25	45	Orange	Orange	—
MAZ4360	34.00	38.00	25	0.05	33.6	60	90	0.5	200	30.4	33.0	37.4	23	45	Orange	Blue	—
MAZ4390	37.00	41.00	27	0.05	36.0	60	130	0.5	250	33.4	36.4	41.2	21	45	Orange	White	—





Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technical information described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuits examples of the products. It neither warrants non-infringement of intellectual property right or any other rights owned by our company or a third party, nor grants any license.
- (3) We are not liable for the infringement of rights owned by a third party arising out of the use of the technical information as described in this material.
- (4) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (5) The products and product specifications described in this material are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (6) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage, and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (7) When using products for which damp-proof packing is required, observe the conditions (including shelf life and amount of time let standing of unsealed items) agreed upon when specification sheets are individually exchanged.
- (8) This material may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.