

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.

TELEPHONE: (201) 376-2922
 (212) 227-6005
 FAX: (201) 376-8960

PARAMETERS

2N2326

SCR, V(DRM) = 200 V TO 299.9 V

Description: SCR, V(DRM) = 200 V to 299.9 V

Manufacturer.....	
Mil/High-Rel? (Y/N).....	
V(drm) Max.....	200
It(stat) Max. (A).....	1.62
@Temp. (test) (xC).....	25#
Supp Curr. I(TSM).....	15%
Firing Char-Igt Max.....	200u
Firing Char-Vgt Max.....	800m
Id(off) Max. (A).....	100u
@Temp. (test) (xC).....	125u
I(h) Max. (A).....	2.0m
V(T) Max.....	2.0%
@It (A).....	3.1
Dv/Dt Worst Case.....	
t(switch) Off Typ. Time (S)...	
@It (test) (A).....	
t(switch) Off Typ. Time (S)...	
Oper. Temp (xC) Min.....	-65
Oper. Temp (xC) Max.....	125u
Pkg Style.....	T0-5
Surface Mounted (Y/N).....	N

u Junction Temperature # Case Temperature % @ above 125xC 2 It(rms)

