




## Small Signal Schottky Diodes

### Features

- For general purpose applications
- The SD101 series is a Metal-on-silicon Schottky barrier device which is protected by a PN junction guard ring
- The low forward voltage drop and fast switching make it ideal for protection of MOS devices, steering, biasing and coupling diodes for fast switching and low logic level applications
- These diodes are also available in the Mini-MELF case with type designations LL101A to LL101C, in the DO-35 case with type- designations SD101A to SD101C and in the SOD-123 case with type designations SD101AW-V to SD101CW-V.
- AEC-Q101 qualified
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS COMPLIANT



20145

### Mechanical Data

**Case:** SOD-323

**Weight:** approx. 4.3 mg

**Packaging Codes/Options:**

GS18/10 k per 13" reel (8 mm tape), 10 k/box

GS08/3 k per 7" reel (8 mm tape), 15 k/box

### Parts Table

Part	Ordering code	Type Marking	Remarks
SD101AWS-V	SD101AWS-V-GS18 or SD101AWS-V-GS08	SA	Tape and Reel
SD101BWS-V	SD101BWS-V-GS18 or SD101BWS-V-GS08	SB	Tape and Reel
SD101CWS-V	SD101CWS-V-GS18 or SD101CWS-V-GS08	SC	Tape and Reel

### Absolute Maximum Ratings

T<sub>amb</sub> = 25 °C, unless otherwise specified

Parameter	Test condition	Part	Symbol	Value	Unit
Peak inverse voltage		SD101AWS-V	V <sub>RRM</sub>	60	V
		SD101BWS-V	V <sub>RRM</sub>	50	V
		SD101CWS-V	V <sub>RRM</sub>	40	V
Power dissipation (Infinite Heat Sink)			P <sub>tot</sub>	150 <sup>1)</sup>	mW
Forward continuous current			I <sub>F</sub>	30	mA
Maximum single cycle surge	10 μs square wave		I <sub>FSM</sub>	2	A

<sup>1)</sup> Valid provided that electrodes are kept at ambient temperature

### Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Thermal resistance junction to ambient air		$R_{thJA}$	650 <sup>1)</sup>	K/W
Junction temperature		$T_j$	125 <sup>1)</sup>	$^{\circ}\text{C}$
Storage temperature range		$T_{stg}$	- 65 to + 150	$^{\circ}\text{C}$

<sup>1)</sup> Valid provided that electrodes are kept at ambient temperature

### Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Reverse breakdown voltage	$I_R = 10\text{ }\mu\text{A}$	SD101AWS-V	$V_{(BR)}$	60			V
		SD101BWS-V	$V_{(BR)}$	50			V
		SD101CWS-V	$V_{(BR)}$	40			V
Leakage current	$V_R = 50\text{ V}$	SD101AWS-V	$I_R$			200	nA
	$V_R = 40\text{ V}$	SD101BWS-V	$I_R$			200	nA
	$V_R = 30\text{ V}$	SD101CWS-V	$I_R$			200	nA
Forward voltage drop	$I_F = 1\text{ mA}$	SD101AWS-V	$V_F$			410	mV
		SD101BWS-V	$V_F$			400	mV
		SD101CWS-V	$V_F$			390	mV
	$I_F = 15\text{ mA}$	SD101AWS-V	$V_F$			1000	mV
		SD101BWS-V	$V_F$			950	mV
		SD101CWS-V	$V_F$			900	mV
Junction capacitance	$V_R = 0\text{ V}$ , $f = 1\text{ MHz}$	SD101AWS-V	$C_D$			2.0	ns
		SD101BWS-V	$C_D$			2.1	ns
		SD101CWS-V	$C_D$			2.2	ns
Reverse recovery time	$I_F = I_R = 5\text{ mA}$ , recover to $0.1\text{ }I_R$		$t_{rr}$			1	ns

### Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified




Figure 1. Typical Variation of Forward Current vs. Forward Voltage




Figure 2. Typical Forward Conduction Curve




Figure 3. Typical Variation of Reverse Current at Various Temperatures






Figure 4. Typical Capacitance Curve as a Function of Reverse Voltage

## Package Dimensions in millimeters (inches): SOD-323



Foot print recommendation:



Document no.:S8-V-3910.02-001 (4)  
 Created - Date: 24.August.2004  
 Rev. 5 - Date: 23.Sept.2009  
 17443



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**