

**TAYCHIPST**

High-Current Density Surface Mount Schottky Rectifier

SSA23L and SSA24

30V-40V 2.0A

FEATURES


- Low power loss, high efficiency
- Low profile surface mount package
- Built-in strain relief
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- Guardring for overvoltage protection
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0

MECHANICAL DATA**Case:** JEDEC DO-214AC molded plastic body**Terminals:** Solder plated, solderable per MIL-STD750, Method 2026

High temperature soldering guaranteed: 250°C/10 seconds at terminals

Polarity: Color band denotes cathode end**Weight:** 0.002 ounce, 0.064 gram

DO-214AC(SMA)

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS****Maximum Ratings and Thermal Characteristics** (TA = 25°C unless otherwise noted)

Parameter	Symbol	SSA23L	SSA24	Unit
Device marking code		23L	S24	V
Maximum repetitive peak reverse voltage	VRRM	30	40	V
Maximum RMS voltage	VRMS	21	28	V
Maximum DC blocking voltage	VDC	30	40	V
Maximum average forward rectified current at TL (See Fig. 1)	IF(AV)	2.0		A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	60		A
Non-repetitive avalanche energy at TA = 25°C, IAS = 1.5A, L = 10mH	EAS	11.25		mJ
Typical thermal resistance ⁽²⁾	RθJA RθJL	110 28		°C/W
Voltage rate of change (rated VR)	dv/dt	10,000		V/μs
Operating junction temperature range	TJ	-65 to + 150		°C
Storage temperature range	TSTG	-65 to + 150		°C

Electrical Characteristics (TA = 25°C unless otherwise noted)

Parameter	Symbol	Typ.	Max.	Typ.	Max.	Unit
Maximum instantaneous forward voltage at 2.0A ⁽¹⁾	VF	0.43	0.45	0.45	0.49	V
		0.32	0.38	0.36	0.42	
Maximum DC reverse current at rated DC blocking voltage ⁽¹⁾	IR	—	0.5	—	0.2	mA
		15	25	12	20	

Notes: (1) Pulse test: 300μs pulse width, 1% duty cycle

(2) Aluminum substrate mounted



RATINGS AND CHARACTERISTIC CURVES

SSA23L and SSA24

Fig. 1 – Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Reverse Characteristics




Fig. 5 - Typical Junction Capacitance

