

# Feed-through terminals

## SAK 4



UL  IEC  LR  DNV		
6.5 x 40 x 51.5		
IEC 60 947-7-1	UL	CSA
800	600	600
32	20	36
4	22...12	26...10
8		
3		
Type	Part No.	Qty.
SAK 4	0128320000	100
SAK 4	0128370000	100
SAK 4	0128330000	100
SAK 4	0128360000 <sup>1)</sup> 2)	100
SAK 4	0128380000 <sup>1)</sup> 2)	100
SAK 4	0105060000 <sup>1)</sup> 2)	100
<hr/>		
SAK 4/10	0322660000 <sup>1)</sup> 2)	10
SAK 4/10	0308860000 <sup>1)</sup> 2)	10
<hr/>		
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117930000	20
AP (1.5)	0117960000	20
AP (1.5)	0117980000	20
<hr/>		
TW (2.5)	0130120000	20
TW (2.5)	0103170000	20
TW (2.5)	0130130000	20
TW (1.5)	0130160000	20
TW (1.5)	0130180000	20
TW (1.0)	0197100000	20
TSch 1	0319160000	100
<hr/>		
Q 2	0336700000	50
Q 3	0336800000	50
Q 4	0336900000	50
Q 10	0368800000	20
<hr/>		
0.5...6		
0.5...4		
0.5...4		
<hr/>		
0.5...4		
A 4		
41 A/6 mm <sup>2</sup>		
36		
<hr/>		
0.5...1.0		
12/M 3/3.5 x 0.6		
Type	Part No.	Qty.
<hr/>		
VL 2	0197000000	100
VH	0285100000	50
BS	0292500000	100
DEK 6.5		

## SAK 6 N



UL  IEC  LR  DNV		
8 x 40 x 51.5		
IEC 60 947-7-1	UL	CSA
800	600	600
41	40	47
6	22...8	20...8
8		
3		
Type	Part No.	Qty.
SAK 6 N	0193220000	100
SAK 6 N		
SAK 6 N	0193230000	100
SAK 6 N	0193260000 <sup>1)</sup>	100
SAK 6 N	0193280000 <sup>1)</sup>	100
<hr/>		
SAK 6 N	0322760000 <sup>1)</sup>	10
SAK 6 N	0308960000 <sup>1)</sup>	10
<hr/>		
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117930000	20
AP (1.5)	0117960000	20
AP (1.5)	0117980000	20
<hr/>		
TW (1.5)	0130120000	20
TW (1.5)	0130130000	20
TW (1.5)	0130160000	20
TW (1.5)	0130180000	20
TW (1.5)	0197100000	20
TSch 1	0319160000	100
<hr/>		
Q 2	0456700000	50
Q 3	0456800000	50
Q 4	0456900000	50
Q 10	0457000000	20
<hr/>		
0.5...10		
0.5...6		
0.5...10		
<hr/>		
0.5...6		
A 5		
57 A/10 mm <sup>2</sup>		
41		
<hr/>		
0.8...1.6		
12 /M 3.5/4.0 x 0.8		
Type	Part No.	Qty.
AD 4 SAK 6N	0196600000	50
BSK M 3 x 22	0128900000	100
VL 2	0194700000	50
VH	0285100000	50
BS	0292500000	100
DEK 8		

## SAK 10



UL  IEC  LR  DNV		
10 x 40 x 51.5		
IEC 60 947-7-1	UL	CSA
800	600	600
57	60	65
10	16...6 <sup>3)</sup>	14...6 <sup>3)</sup>
8		
3		
Type	Part No.	Qty.
SAK 10	0110020000	100
SAK 10	0110070000	100
SAK 10	0110030000	100
SAK 10	0110060000 <sup>1)</sup>	100
SAK 10	0110080000 <sup>1)</sup>	100
<hr/>		
SAK 10	0353160000 <sup>1)</sup>	10
<hr/>		
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117930000	20
AP (1.5)	0117960000	20
AP (1.5)	0117980000	20
<hr/>		
TW (1.5)	0130120000	20
TW (1.5)	0130170000	20
TW (1.5)	0130130000	20
TW (1.5)	0130160000	20
TW (1.5)	0130180000	20
TW (1.5)	0197100000	20
TSch 1	0319160000	100
<hr/>		
Q 2	0457100000	50
Q 3	0457200000	50
Q 4	0457300000	50
Q 10	0457400000	20
<hr/>		
1.5...10		
2.5...16		
1.5...10		
<hr/>		
1.5...10		
B 6		
76 A/16 mm <sup>2</sup>		
57		
<hr/>		
1.2...2.0 <sup>3)</sup>		
12 /M 4/5.5 x 1.0		
Type	Part No.	Qty.
AD 4	0178600000	50
BSK M 3 x 22	0128900000	100
VL 2	0135900000	50
VH	0285100000	50
BS	0292500000	100
DEK 5		

<sup>1)</sup> Finger-safe cross-connection with ADP 4 cover profiles (see main catalogue)

<sup>2)</sup> Not suitable for locking pin SST 3

<sup>3)</sup> Tightening torque for 16 mm<sup>2</sup> and AWG 6: 2 Nm