D57 Desktop (IEC) Unregulated 20 Watts Series

Features

- 230 VAC Input
- Desktop Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 20 Watts
- Safety Agency Approved/CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

| Ault Model | Rated Output Volts DC | Output Current-Amps | Maximum Watts |
|------------------|--------------------------|------------------------|------------------|
| D57-102000-N000G | 10 | 2.00 | 20.0 |
| D57-111818-N000G | 11 | 1.82 | 20.0 |
| D57-121667-N000G | 12 | 1.67 | 20.0 |
| D57-141429-N000G | 14 | 1.43 | 20.0 |
| D57-151333-N000G | 15 | 1.33 | 20.0 |
| D57-181111-N000G | 18 | 1.11 | 20.0 |
| D57-201000-N000G | 20 | 1.00 | 20.0 |
| D57-210952-N000G | 21 | 0.95 | 20.0 |
| D57-220909-N000G | 22 | 0.91 | 20.0 |
| D57-240833-N000G | 24 | 0.83 | 20.0 |

| Input | | | | |
|------------------|----------------------|----------------------------|--|--|
| • | Voltage | 230 VAC | | |
| • | Line Frequency | 50 Hz | | |
| • | Connector | In Case IEC 320 without | | |
| | | ground | | |
| Ele | ectrical | | | |
| • | Topology | DC Unregulated Power | | |
| | | Supply | | |
| • | Dielectric Withstand | 3000 VAC primary-secondary | | |
| • | Protection | Current, Thermal or Energy | | |
| | | Limiting | | |
| • | EMI | Complies with EMC | | |
| | | Directives | | |
| • | CE | CE Compliant | | |
| Safety Approvals | | | | |
| | | | | |

EN60950

| Environmental | | | | |
|---------------|-----------------------|--------------------------------|--|--|
| • | Operating Temperature | 0° to 40° C with no derating | | |
| • | Storage Temperature | -30° to +85° C | | |
| • | Relative Humidity | 5% to 95% non-condensing | | |
| • | Altitude | 0-10,000 feet | | |
| • | Cooling | Convectional - non vented case | | |
| Mechanical | | | | |
| • | Case Dimensions | D57 - In Case IEC 320 | | |
| | | 3.5 L x 2.7 W x 2.1 H (in) | | |
| | | 88 L x 68 W x 54 H (mm) | | |
| • | Case Material | Black 94 V1 Polycarbonate | | |
| • | Weight | 24 ounces, 695 grams, | | |
| | | (excluding cord) | | |
| • | Cord and | 6 ft., 2 Conductor, 20 AWG | | |
| | Connector | Ault #3 Connector | | |
| | | Other Connectors Available | | |

ONE YEAR WARRANTY

Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428

Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911