


**FEATURES**

- High temperature metallurgically bonded construction
- Sintered glass cavity free junction
- Capability of meeting environmental standard of MIL-S-19500
- High temperature soldering guaranteed
- 350°C /10sec/0.375"lead length at 5 lbs tension
- Operate at Ta =55°C with no thermal run away
- Typical Ir<0.1µA

**MECHANICAL DATA**

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C  
 Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy  
 Polarity: color band denotes cathode  
 Mounting position: any



**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	BYV26EGP-15	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	1000	V
Maximum RMS Voltage	Vrms	700	V
Maximum DC blocking Voltage	Vdc	1000	V
Reverse avalanche breakdown voltage at IR = 0.1 mA	V <sub>(BR)R</sub>	1100min	V
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	If(av)	1.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	30	A
Maximum Forward Voltage at rated Forward Current and 50°C	Vf	2.5	V
Non-repetitive peak reverse avalanche energy (Note 1)	Ersm	10	mJ
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	Ir	5.0 150.0	µA
Maximum Reverse Recovery Time (Note 2)	Trr	75	nS
Typical Junction Capacitance (Note 3)	Cj	15.0	pF
Typical Thermal Resistance (Note 4)	Rth(ja)	55.0	°C/W
Storage and Operating Junction Temperature	Tstg, Tj	-65 to +175	°C

Note: 1.R=400mA; Tj=Tjmax prior to surge; inductive load switched off  
 2.Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A  
 3.Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc  
 4.Thermal Resistance from Junction to Ambient at 3/



**TAYCHIPST**


**SINTERED GLASS JUNCTION  
FAST SWITCHING PLASTIC RECTIFIER**

**BYV26EGP-15**  
**1000V 1.0A**


**RATINGS AND CHARACTERISTICS CURVES**

**BYV26EGP-15**


**FIG. 1 - FORWARD CURRENT DERATING CURVE**




**FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**




**FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**



**FIG. 4 - TYPICAL REVERSE CHARACTERISTICS**



**FIG. 5 - TYPICAL JUNCTION CAPACITANCE**



**FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE**

