

Part Number: C1304

Revision Level: 4

Date: 9/24/2007

**3C 20 AWG 26/34 TC RUBBER OAS RUBBER**

**CONTROL CABLE**

**A. CONSTRUCTION**

Conductor: #20 AWG 26/34 Tinned Copper  
 Insulation: 0.020" Wall Rubber  
 Cable: 3 conductors @ 1.50" LHL with overall mylar wrap.  
 Braid: #36 AWG Tinned Copper  
 80% Min.Coverage  
 Tape: Cotton Seperator  
 Jacket: 0.035" Wall Rubber  
 Print Legend: **CAROL C-1304A MADE IN USA**

**DIAMETERS**

0.038" nom.  
 0.080" nom.  
 0.180" nom.  
 0.205" nom.  
 0.215" nom.  
 0.285" +/- 0.014"

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE: 60 C  
 SUGGESTED WORKING VOLTAGE (Vrms): 300Vrms  
 CONDUCTOR D.C. RESISTANCE: 11.3 Ohms/1000 ft nom

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red