

Part Number: C1305

Revision Level: 5

Date: 11/8/2007

**4C 20 AWG 26/34 TC RUBBER OAS RUBBER**
**CONTROL CABLE**
**A. CONSTRUCTION**

Conductor: #20 AWG 26/24 Tinned Copper  
 Insulation: 0.020" Wall Rubber  
 Cable: 4 conductors @ 2.50" LHL with mylar wrap.  
 Braid: #36 AWG Tinned Copper  
       80% min. coverage  
 Tape: Cotton Separator  
 Jacket: 0.035" Wall Rubber - Black  
 Print Legend: **CAROL (R) C-1305A MADE IN USA**

**DIAMETERS**

0.038" nom.  
 0.080" nom.  
 0.200" nom.  
 0.225" nom.  
  
 0.230" nom.  
 0.300" +/- 0.015"

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE: 60 C  
 SUGGESTED WORKING VOLTAGE (V<sub>rms</sub>): 300V<sub>rms</sub>  
 CONDUCTOR D.C. RESISTANCE: 11.3 Ohms/1000 ft nom

**D. COLOR CODE** *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red
4	Green