

Part Number: C1705

Revision Level: 11/19/2012

4C 16AWG 26/30BC PP, PVC**COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 16 AWG 26/30 BC
Insulation: .009" Wall, Polypropylene (PP)
Cable Core: 4C @ 6.00" LHL
Jacket: .030" Polyvinyl Chloride (PVC)
Print Legend:

DIAMETERS

.057" nom
.075" nom
.182" nom
.242" nom

**CAROL® -- C1705 -- 4C 16AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8
CL3 60C -- CSA C/US CMG 80C OR CSA AWM I/II A/B 80C 600V
FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)**

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +80°C
Suggested Working Voltage: 600V Max
Conductor DCR: 4.03 Ohms/M' @ 20°C (nom)
Mutual Capacitance: 21.4 pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
Date: _____