



### SPECIFICATIONS

FREQUENCY RANGE	1 TO 2 GHz
NUMBER OF OUTPUT PORTS	4
MINIMUM ISOLATION	20 dB
MAXIMUM VSWR	1.60
MAXIMUM INSERTION LOSS	.60 dB



**PASTERNAK ENTERPRISES, INC.**  
 P.O BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451  
 WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)  
**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE2012**

DES.

SMA FEMALE POWER DIVIDER FREQUENCY RANGE: 1-2 GHz 4 OUTPUT PORTS

REV. -

**FSCM NO. 53919**

CAD FILE 010809

SCALE N/A

SIZE A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.