



Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311  
Phone: (818) 701-4933  
Fax: (818) 701-4939

2N7002W

## Features

- Low ON-Resistance
- Low Input Capacitance
- Low Gate Threshold Voltage
- Fast Switching Speed
- Low Input/Output Leakage
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## Mechanical Data

- Case: SOT-323, Molded Plastic
- Terminals: Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking: K72

## Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 625K/W Junction To Ambient


| Parameter                                                             | Symbol    | Value                | Unit        |
|-----------------------------------------------------------------------|-----------|----------------------|-------------|
| Drain-Source-Voltage                                                  | $V_{DSS}$ | 60                   | V           |
| Drain-Gate Voltage $R_{GS} \leq 1.0M\Omega$                           | $V_{DGR}$ | 60                   | V           |
| Gate-Source-Voltage Continuous<br>Pulsed                              | $V_{GSS}$ | $\pm 20$<br>$\pm 40$ | V           |
| Drain Current (Note 1) Continuous<br>Continuous @ 100°C<br>Pulsed     | $I_D$     | 115<br>73<br>800     | mA          |
| Total Power Dissipation (Note 1)<br>Derating above $T_A = 25^\circ C$ | $P_D$     | 200<br>1.60          | mW<br>mW/°C |

Note: 1. Valid provided that terminals are kept at specified ambient temperature.

2. Pulse width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$

## N-Channel Enhancement Mode Field Effect Transistor


### SOT-323



#### DIMENSIONS

| DIM | INCHES       |      | MM           |      | NOTE |
|-----|--------------|------|--------------|------|------|
|     | MIN          | MAX  | MIN          | MAX  |      |
| A   | .071         | .087 | 1.80         | 2.20 |      |
| B   | .045         | .053 | 1.15         | 1.35 |      |
| C   | .079         | .087 | 2.00         | 2.20 |      |
| D   | .026 Nominal |      | 0.65 Nominal |      |      |
| E   | .047         | .055 | 1.20         | 1.40 |      |
| F   | .012         | .016 | .30          | .40  |      |
| G   | .000         | .004 | .000         | .100 |      |
| H   | .035         | .039 | .90          | 1.00 |      |
| J   | .004         | .010 | .100         | .250 |      |
| K   | .012         | .016 | .30          | .40  |      |

#### Suggested Solder Pad Layout



# 2N7002W





## Electrical Characteristics @ T<sub>A</sub> = 25 °C unless otherwise specified

| Characteristic                    | Symbol                                              | Min                  | Typ | Max        | Unit        | Test Condition                               |                                                                                                                           |
|-----------------------------------|-----------------------------------------------------|----------------------|-----|------------|-------------|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| OFF CHARACTERISTICS (Note 2)      |                                                     |                      |     |            |             |                                              |                                                                                                                           |
| Drain-Source Breakdown Voltage    | BV <sub>DSS</sub>                                   | 60                   | 70  |            | V           | V <sub>GS</sub> = 0V, I <sub>D</sub> = 10 A  |                                                                                                                           |
| Zero Gate Voltage Drain Current   | @ T <sub>C</sub> = 25°C<br>@ T <sub>C</sub> = 125°C | I <sub>DSS</sub>     |     | 1.0<br>500 | μA          | V <sub>DS</sub> = 60V, V <sub>GS</sub> = 0V  |                                                                                                                           |
| Gate-Body Leakage                 |                                                     | I <sub>GSS</sub>     |     | ±10        | nA          | V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V |                                                                                                                           |
| ON CHARACTERISTICS (Note 2)       |                                                     |                      |     |            |             |                                              |                                                                                                                           |
| Gate Threshold Voltage            |                                                     | V <sub>GS(th)</sub>  | 1.0 |            | 2.0         | V                                            | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250 A                                                               |
| Static Drain-Source On-Resistance | @ T <sub>J</sub> = 25°C<br>@ T <sub>J</sub> = 125°C | R <sub>DS (ON)</sub> |     | 3.2<br>4.4 | 7.5<br>13.5 | Ω                                            | V <sub>GS</sub> = 5.0V, I <sub>D</sub> = 0.05A<br>V <sub>GS</sub> = 10V, I <sub>D</sub> = 0.5A                            |
| On-State Drain Current            |                                                     | I <sub>D(ON)</sub>   | 0.5 | 1.0        |             | A                                            | V <sub>GS</sub> = 10V, V <sub>DS</sub> = 7.5V                                                                             |
| Forward Transconductance          |                                                     | g <sub>FS</sub>      | 80  |            |             | mS                                           | V <sub>DS</sub> = 10V, I <sub>D</sub> = 0.2A                                                                              |
| DYNAMIC CHARACTERISTICS           |                                                     |                      |     |            |             |                                              |                                                                                                                           |
| Input Capacitance                 |                                                     | C <sub>iss</sub>     |     | 22         | 50          | pF                                           | V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V<br>f = 1.0MHz                                                                 |
| Output Capacitance                |                                                     | C <sub>oss</sub>     |     | 11         | 25          | pF                                           |                                                                                                                           |
| Reverse Transfer Capacitance      |                                                     | C <sub>rss</sub>     |     | 2.0        | 5.0         | pF                                           |                                                                                                                           |
| SWITCHING CHARACTERISTICS         |                                                     |                      |     |            |             |                                              |                                                                                                                           |
| Turn-On Delay Time                |                                                     | t <sub>D(ON)</sub>   |     | 7.0        | 20          | ns                                           | V <sub>DD</sub> = 30V, I <sub>D</sub> = 0.2A,<br>R <sub>L</sub> = 150 Ω, V <sub>GEN</sub> = 10V,<br>R <sub>GEN</sub> = 25 |
| Turn-Off Delay Time               |                                                     | t <sub>D(OFF)</sub>  |     | 11         | 20          | ns                                           |                                                                                                                           |

Note: 1. Valid provided that terminals are kept at specified ambient temperature.

2. Pulse width ≤ 300μs, duty cycle ≤ 2%.

# 2N7002W



## Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel |

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.